Testing Laboratory 3787

RADIO TEST REPORT

FCC ID	:	TX2-RTL8852CE
Equipment	:	11ax RTL8852CE Combo module
Brand Name	:	REALTEK
Model Name	:	RTL8852CE
Applicant	:	Realtek Semiconductor Corp. No. 2,Innovation Road II, Hsinchu Science Park, Hsinchu 300,Taiwan
Manufacturer	:	Realtek Semiconductor Corp. No. 2,Innovation Road II, Hsinchu Science Park, Hsinchu 300,Taiwan
Standard	:	47 CFR FCC Part 15.407

The product was received on Nov. 05, 2021, and testing was started from Nov. 24, 2021 and completed on Aug. 08, 2022. We, Sporton International Inc. Hsinchu Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. Hsinchu Laboratory, the test report shall not be reproduced except in full.

Approved by: Sam Chen

Sporton International Inc. Hsinchu Laboratory
No.8, Ln. 724, Bo'ai St., Zhubei City, Hsinchu County 302010, Taiwan

Table of Contents

History of this test report **4**

Summary of Test Result **5**

1 General Description **6**

1.1 Information 6
1.2 Applicable Standards 12
1.3 Testing Location Information 12
1.4 Measurement Uncertainty 13

2 Test Configuration of EUT **14**

2.1 Test Channel Mode 14
2.2 The Worst Case Measurement Configuration 19
2.3 EUT Operation during Test 23
2.4 Accessories 23
2.5 Support Equipment 23
2.6 Test Setup Diagram 24

3 Transmitter Test Result **27**

3.1 AC Power-line Conducted Emissions 27
3.2 Emission Bandwidth 29
3.3 Maximum Equivalent Isotopically Radiated Power (E.I.R.P.) 30
3.4 Peak Power Spectral Density (E.I.R.P.) 33
3.5 Unwanted Emissions 36
3.6 Contention Based Protocol 41
3.7 Frequency Stability 42

4 Test Equipment and Calibration Data **43**

Appendix A. Test Results of AC Power-line Conducted Emissions

Appendix B. Test Results of Emission Bandwidth

Appendix C. Test Results of Maximum Equivalent Isotopically Radiated Power (E.I.R.P.)

Appendix D. Test Results of Peak Power Spectral Density (E.I.R.P.)

Appendix E. Test Results of Unwanted Emissions

Appendix F. Test Results of Contention-Based Protocol

Appendix G. Test Results of Frequency Stability

Appendix H. Test Results of Radiated Emission Co-location

Appendix I. Test Photos

Photographs of EUT v01

History of this test report

Report No.	Version	Description	Issued Date
FR1N0223-06AE	01	Initial issue of report	Sep. 14, 2022
FR1N0223-06AE	02	Removing the UNII6~UNII8 data	Nov. 10, 2022

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
1.1.2	15.203	Antenna Requirement	PASS	-
3.1	15.207	AC Power-line Conducted Emissions	PASS	-
3.2	15.407(a)	Emission Bandwidth	PASS	-
3.3	15.407(a)	Maximum Equivalent Isotopically Radiated Power (E.I.R.P.)	PASS	-
3.4	15.407(a)	Peak Power Spectral Density (E.I.R.P.)	PASS	-
3.5	15.407(b)	Unwanted Emissions	PASS	-
3.6	15.407(d)	Contention-Based Protocol	PASS	Standard Client w/o test
3.7	15.407(g)	Frequency Stability	PASS	-
Note: Reference to Sporton Project No.: 1N0223、1N0223-01.				

Declaration of Conformity:
1. The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results. 2. The measurement uncertainty please refer to report "Measurement Uncertainty".
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Sam Chen
Report Producer: Sandy Chuang

1 General Description

1.1 Information

1.1.1 RF General Information

For Low Power:

Frequency Range (MHz)	IEEE Std. 802.11	Ch. Frequency (MHz)	Channel Number
5925-6425	ax (HEW20)	5955-6415	1-93 [24]
5925-6425	ax (HEW40)	5965-6405	3-91 [12]
5925-6425	ax (HEW80)	5985-6385	7-87 [6]
5925-6425	ax (HEW160)	6025-6385	15-79 [3]

Band	Mode	BWch (MHz)	Nant
UNII 5	ax (HEW20)	20	1TX/2TX
UNII 5	ax (HEW20)-BF	20	2TX
UNII 5	ax (HEW40)	40	1TX/2TX
UNII 5	ax (HEW40)-BF	40	2TX
UNII 5	ax (HEW80)	80	1TX/2TX
UNII 5	ax (HEW80)-BF	80	2TX
UNII 5	ax (HEW160)	160	1TX/2TX
UNII 5	ax (HEW160)-BF	160	2TX

Note:
- HEW20, HEW40, HEW80 and HEW160 use a combination of OFDMA-BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM modulation.
- BWch is the nominal channel bandwidth.
- The channel defined in the IEEE Standard P802.11ax™/D6.1.

1.1.2 Antenna Information

Ant.	Port		Brand	Model Name	Antenna Type	Connector	Gain (dBi)
	WLAN 2.4GHz / 5GHz / 6GHz	Bluetooth					
1	1/2	1	ARISTOTLE	RFA-27-JP378-4B-200	Monopole	I-PEX	Note 1
2	1/2	1	ARISTOTLE	RFA-27-JP326-MH4300	PIFA	I-PEX	
3	1/2	1	ARISTOTLE	RFA-27-C38H1-MH4300	Dipole	I-PEX	

Note 1

Ant.	Port		Gain (dBi)		
	WLAN 2.4GHz / 5GHz / 6GHz	Bluetooth	WLAN 2.4GHz	WLAN 5GHz / 6GHz	Bluetooth
1	1/2	1	3.38	4.86	3.38
2	1/2	1	3.50	5.00	3.50
3	1/2	1	3.00	5.00	3.00

Note 2: The above information was declared by manufacturer.
Note 3: For Conducted measurement Test: Only the highest gain antenna “Ant. 2” was selected to perform the test and recorded in this report.

<For WLAN 2.4GHz function>
For IEEE 802.11b/g/n/VHT/ax (1TX/2RX):
For Conducted:
The EUT supports the antenna with TX diversity functions.
Both Port 1 and Port 2 support transmit and receive functions, but only one of them will be used at one time.
The Port 1 generated the worst case, so it was selected to test and record in the report.
Port 1 and Port 2 could receive simultaneously
For Radiated:
The EUT supports the antenna with TX diversity functions.
Both Port 1 and Port 2 support transmit and receive functions, but only one of them will be used at one time.
The Port 2 generated the worst case, so it was selected to test and record in the report.
Port 1 and Port 2 could receive simultaneously
For IEEE 802.11b/g/n/VHT/ax (2TX/2RX):
Port 1 and Port 2 can be used as transmitting/receiving antenna.
Port 1 and Port 2 could transmit/receive simultaneously.

<For WLAN 5GHz function>
For IEEE 802.11a/n/ac/ax (1TX/2RX):
The EUT supports the antenna with TX diversity functions.
Both Port 1 and Port 2 support transmit and receive functions, but only one of them will be used at one time.
The Port 1 generated the worst case, so it was selected to test and record in the report.
Port 1 and Port 2 could receive simultaneously
For IEEE 802.11a/n/ac/ax (2TX/2RX):
Port 1 and Port 2 can be used as transmitting/receiving antenna.
Port 1 and Port 2 could transmit/receive simultaneously.

<For WLAN 6GHz function>
For IEEE 802.11ax (1TX/2RX):
The EUT supports the antenna with TX diversity functions.
Both Port 1 and Port 2 support transmit and receive functions, but only one of them will be used at one time.
The Port 1 generated the worst case, so it was selected to test and record in the report.
Port 1 and Port 2 could receive simultaneously
For IEEE 802.11ax (2TX/2RX):
Port 1 and Port 2 can be used as transmitting/receiving antenna.
Port 1 and Port 2 could transmit/receive simultaneously.

<For Bluetooth function> (1TX/1RX):
Only Port 1 can be used as transmitting/receiving antenna.

Type	Maximum Output Power	Power Spectral Density
Non-BF	Directional gain = Max.gain + array gain. For power measurements on IEEE 802.11 devices Array Gain = 0 dB (i.e., no array gain) for N ANT ≤ 4	$Directional Gain = 10 \cdot \log\left[\frac{\sum_{i=1}^{N_{SS}}\left\{\sum_{k=1}^{N_{ANT}} g_{i,k}\right\}^2}{N_{ANT}}\right]$
BF	$Directional Gain = 10 \cdot \log\left[\frac{\sum_{i=1}^{N_{SS}}\left\{\sum_{k=1}^{N_{ANT}} g_{i,k}\right\}^2}{N_{ANT}}\right]$	$Directional Gain = 10 \cdot \log\left[\frac{\sum_{i=1}^{N_{SS}}\left\{\sum_{k=1}^{N_{ANT}} g_{i,k}\right\}^2}{N_{ANT}}\right]$

Ex.

Directional Gain (NSS1) formula : $Directional Gain = 10 \cdot \log\left[\frac{\sum_{i=1}^{N_{SS}}\left\{\sum_{k=1}^{N_{ANT}} g_{i,k}\right\}^2}{N_{ANT}}\right]$

NSS1(g1,1) = $10^{G1/20}$; NSS1(g1,2)= $10^{G2/20}$

gj,k =$(Nss1(g1,1) + Nss1(g1,2))^2$

DG = 10 log[$(Nss1(g1,1) + Nss1(g1,2) / N_{ANT}$] => 10 log[$(10^{G1/20} + 10^{G2/20})^2 / N_{ANT}$]

Where ;

Monopole Antenna

2.4G G1 = 3.38 dBi ; G2 = 3.38 dBi ; DG=6.39 dBi

5G G1 = 4.86 dBi ; G2 = 4.86 dBi ; DG=7.87dBi

6G G1 = 4.86 dBi ; G2 = 4.86 dBi ; DG=7.87 dBi

PIFA Antenna

2.4G G1 = 3.5 dBi ; G2 = 3.5 dBi ; DG=6.51 dBi

5G G1 = 5 dBi ; G2 =5 dBi ; DG=8.01dBi

6G G1 = 5 dBi ; G2 =5 dBi ; DG=8.01dBi

Dipole Antenna

2.4G G1 = 3 dBi ; G2 = 3 dBi ; DG=6.01 dBi

5G G1 = 5 dBi ; G2 =5 dBi ; DG=8.01dBi

6G G1 = 5 dBi ; G2 =5 dBi ; DG=8.01dBi

1.1.3 Test Mode of Partial RU

Mode		Partial RU		
802.11ax HEW20	1TX	26	52	106
	2TX	26	52	106

1.1.4 Mode Test Duty Cycle

<Full RU>

Non-Beamforming Mode

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
802.11ax HEW20	0.993	0.03	n/a (DC>=0.98)	n/a (DC>=0.98)
802.11ax HEW40	0.987	0.06	n/a (DC>=0.98)	n/a (DC>=0.98)
802.11ax HEW80	0.976	0.11	281.25u	10k
802.11ax HEW160	0.957	0.19	166.875u	10k

Beamforming Mode

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
802.11ax HEW20-BF	0.993	0.03	n/a (DC>=0.98)	n/a (DC>=0.98)
802.11ax HEW40-BF	0.988	0.05	n/a (DC>=0.98)	n/a (DC>=0.98)
802.11ax HEW80-BF	0.976	0.11	281.25u	10k
802.11ax HEW160-BF	0.957	0.19	167.5u	10k

<Partial RU>

Mode	DC	DCF(dB)	T(s)	VBW(Hz) ≥ 1/T
ax20_RU26	0.993	0.03	n/a (DC>=0.98)	n/a (DC>=0.98)

Note:
- DC is Duty Cycle.
- DCF is Duty Cycle Factor.

1.1.5 EUT Operational Condition

EUT Power Type	From host system			
Beamforming Function	☒	With beamforming	☐	Without beamforming
	The product has beamforming function for 11n/VHT/11ax in 2.4GHz, 11n/11ac/11ax in 5GHz and ax in 6GHz.			
Device Type	☐	Indoor Access Point	☐	Subordinate
	☒	Indoor Client	☐	Standard Power Access Point
	☐	Dual Client	☐	Standard Client
	☐	Fixed Client		
Test Software Version	REALTEK MP V:homo_V1.0.2			
Software / Firmware Version for CBP	6001.0.16.102			

Note: The above information was declared by manufacturer.

1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR FCC Part 15.407
- ANSI C63.10-2013
- FCC KDB 789033 D02 v02r01

The following reference test guidance is not within the scope of accreditation of TAF.

- FCC KDB 987594 D02 v01r01
- FCC KDB 662911 D01 v02r01
- FCC KDB 412172 D01 v01r01
- FCC KDB 414788 D01 v01r01

1.3 Testing Location Information

Testing Location Information	
Test Lab.：Sporton International Inc. Hsinchu Laboratory	
Hsinchu (TAF: 3787)	ADD: No.8, Ln. 724, Bo’ai St., Zhubei City, Hsinchu County 302010, Taiwan TEL: 886-3-656-9065 FAX: 886-3-656-9085 Test site Designation No. TW3787 with FCC. Conformity Assessment Body Identifier (CABID) TW3787 with ISED.

Test Condition	Test Site No.	Test Engineer	Test Environment (°C / %)	Test Date
RF Conducted (Other tests)	TH01-CB	Serway Lee	21~22.3 / 65~69	May 02, 2022~ Jun. 30, 2022
RF Conducted (Maximum Conducted Output Power test)	TH01-CB	Serway Lee	21~22.3 / 65~69	May 02, 2022~ Aug. 08, 2022
Radiated <Below 1GHz>	10CH01-CB	Peter Wu	23~24 / 57~58	May 18, 2022
Radiated <Above 1GHz>	03CH01-CB 03CH03-CB	Ken Yeh	24.2-26.1 / 55-58 23.8-24.9 / 55-58	Jun.11, 2022~ Jul. 05, 2022
Radiated <Co-location>	03CH04-CB	Ken Yeh	24.4-25.5 / 55-58	Jun. 09, 2022
RF Conducted <Contention-Based Protocol test>	DF02-CB	Nyle Chang	20~21.9 / 60~62	Nov. 24, 2021~ May 28, 2022
AC Conduction	CO01-CB	Ryan Huang	23~24 / 56~57	May 13, 2022

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Test Date: Before Jun. 01, 2022

Test Items	Uncertainty	Remark
Conducted Emission (150kHz ~ 30MHz)	3.4 dB	Confidence levels of 95%
Radiated Emission (9kHz ~ 30MHz)	4.2 dB	Confidence levels of 95%
Radiated Emission (30MHz ~ 1,000MHz)	5.5 dB	Confidence levels of 95%
Radiated Emission (1GHz ~ 18GHz)	4.7 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	4.2 dB	Confidence levels of 95%
Conducted Emission	2.5 dB	Confidence levels of 95%
Output Power Measurement	1.3 dB	Confidence levels of 95%
Power Density Measurement	2.5 dB	Confidence levels of 95%
Bandwidth Measurement	0.9%	Confidence levels of 95%

Test Date: After May 31, 2022

Test Items	Uncertainty	Remark
Radiated Emission (1GHz ~ 18GHz)	5.2 dB	Confidence levels of 95%
Radiated Emission (18GHz ~ 40GHz)	4.7 dB	Confidence levels of 95%
Conducted Emission	3.2 dB	Confidence levels of 95%
Output Power Measurement	0.8 dB	Confidence levels of 95%
Power Density Measurement	3.2 dB	Confidence levels of 95%
Bandwidth Measurement	2.0 %	Confidence levels of 95%

2 Test Configuration of EUT

2.1 Test Channel Mode

<Full RU> low power_Non-beamforming mode_1TX

Mode	Power Setting
802.11ax HEW20_Nss1,(MCS0)_1TX	-
5955MHz	5.75
6195MHz	6
6415MHz	6
802.11ax HEW40_Nss1,(MCS0)_1TX	-
5965MHz	8.5
6205MHz	9
6405MHz	8.75
802.11ax HEW80_Nss1,(MCS0)_1TX	-
5985MHz	11.25
6225MHz	11.5
6385MHz	11.5
802.11ax HEW160_Nss1,(MCS0)_1TX	-
6025MHz	13.75
6185MHz	13.75
6345MHz	14.25

<Full RU> low power_Non-beamforming mode_2TX

Mode	Power Setting
802.11ax HEW20_Nss1,(MCS0)_2TX	-
5955MHz	0.25(S1-1)
6195MHz	0.5(S1-0.75)
6415MHz	0.5(S1-0.75)
802.11ax HEW40_Nss1,(MCS0)_2TX	-
5965MHz	3.25
6205MHz	3.5(S0-0.5)
6405MHz	3.5(S0-0.5)
802.11ax HEW80_Nss1,(MCS0)_2TX	-
5985MHz	6.75(S0-1)
6225MHz	7(S0-1)
6385MHz	7(S0-1)
802.11ax HEW160_Nss1,(MCS0)_2TX	-
6025MHz	9.75(S0-1.5)
6185MHz	9.5(S0-1.5)
6345MHz	9.5(S0-1.25)

<Full RU> low power_Beamforming mode_2TX

Mode	Power Setting
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-
5955MHz	0.25(S1-1)
6195MHz	0.5(S1-0.75)
6415MHz	0.5(S1-0.75)
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-
5965MHz	3.25
6205MHz	3.5(S0-0.5)
6405MHz	3.5(S0-0.5)
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-
5985MHz	6.75(S0-1)
6225MHz	7(S0-1)
6385MHz	7(S0-1)
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-
6025MHz	9.75(S0-1.5)
6185MHz	9.5(S0-1.5)
6345MHz	9.5(S0-1.25)

<Partial RU>

low power_RU26_1TX

Mode	Power Setting
802.11ax HEW20_Nss1,(MCS0)_1TX	-
5955MHz	-3.25
6195MHz	-3.25
6415MHz	-3

low power_RU52_1TX

Mode	Power Setting
802.11ax HEW20_Nss1,(MCS0)_1TX	-
5955MHz	-0.5
6195MHz	-0.5
6415MHz	-0.25

low power_RU106_1TX

Mode	Power Setting
802.11ax HEW20_Nss1,(MCS0)_1TX	-
5955MHz	2.75
6195MHz	2.75
6415MHz	2.75

low power_RU26_2TX

Mode	Power Setting
802.11ax HEW20_Nss1,(MCS0)_2TX	-
5955MHz	-8(S1-3)
6195MHz	-7.75(S1-3)
6415MHz	-7.75(S1-3)

low power_RU52_2TX

Mode	Power Setting
802.11ax HEW20_Nss1,(MCS0)_2TX	-
5955MHz	-5.75(S1-0.5)
6195MHz	-5.5(S1-0.5)
6415MHz	-5.5(S1-0.5)

low power_RU106_2TX

Mode	Power Setting
802.11ax HEW20_Nss1,(MCS0)_2TX	-
5955MHz	-3.25(S0-0.75)
6195MHz	-3.25
6415MHz	-3.25(S0-0.25)

Note:
- There are two modes of EUT, one is beamforming mode, and the other is Non-beamforming mode. only beamforming mode was tested and recorded in this report.

2.2 The Worst Case Measurement Configuration

<Full RU>

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Normal Link
1	EUT + WLAN 2.4GHz+ Bluetooth + Ant. 2
2	EUT + WLAN 5GHz+ Bluetooth + Ant. 2
3	EUT + WLAN 6GHz+ Bluetooth + Ant. 2
Mode 2 generated the worst test result, so it was recorded in this report.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	Maximum Equivalent Isotopically Radiated Power (E.I.R.P.)
Test Condition	Conducted measurement at transmit chains
1	EUT with Ant. 2

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emission Bandwidth Peak Power Spectral Density (E.I.R.P.)
Test Condition	Conducted measurement at transmit chains
1	EUT with Ant. 1
2	EUT with Ant. 2
3	EUT with Ant. 3

The Worst Case Mode for Following Conformance Tests	
Tests Item	Frequency Stability
Test Condition	Conducted measurement at transmit chains

The Worst Case Mode for Following Conformance Tests	
Tests Item	Contention Based Protocol
Test Condition	Conducted measurement at transmit chains
1	EUT with 0 dBi
2	EUT with - 5dBi

The Worst Case Mode for Following Conformance Tests	
Tests Item	Unwanted Emissions
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode < 1GHz	Normal Link
1	EUT in X axis + WLAN 2.4GHz + Bluetooth + Ant. 2
2	EUT in Y axis + WLAN 2.4GHz + Bluetooth + Ant. 2
3	EUT in Z axis + WLAN 2.4GHz + Bluetooth + Ant. 2
Mode 3 has been evaluated to be the worst case among Mode 1~3, thus measurement for Mode 4 ~ 5 will follow this same test mode.	
4	EUT in Z axis + WLAN 5GHz + Bluetooth + Ant. 2
5	EUT in Z axis + WLAN 6GHz + Bluetooth + Ant. 2
Mode 3 has been evaluated to be the worst case among Mode 1~5, thus measurement for Mode 6 ~ 7 will follow this same test mode.	
6	EUT in Z axis + WLAN 2.4GHz + Bluetooth + Ant. 3
7	EUT in Z axis + WLAN 2.4GHz + Bluetooth + Ant. 1
For operating mode 3 is the worst case and it was record in this test report.	
Operating Mode > 1GHz	CTX
The EUT was performed at X axis, Y axis and Z axis position, and the worst case as below:	
1	1TX: EUT in Y axis with Ant. 1
	2TX: EUT in Y axis with Ant. 1
2	1TX: EUT in Y axis with Ant. 2
	2TX: EUT in Y axis with Ant. 2
3	1TX: EUT in Y axis with Ant. 3
	2TX: EUT in Y axis with Ant. 3

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emission MASK
Test Condition	Conducted measurement at transmit chains
1	EUT with Ant. 1
2	EUT with Ant. 2
3	EUT with Ant. 3

The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Radiated Emission Co-location
Test Condition	Radiated measurement
Operating Mode	Normal Link
The EUT was performed at X axis, Y axis and Z axis position. EUT X axis in 5GHz + Bluetooth and EUT Y axis in 6GHz + Bluetooth were been evaluated to be the worst case at Radiated measurement <Above 1GHz>; thus, the measurement will follow this same test configuration	
1	EUT in X with Ant. 1 (Port 1)_WLAN 5GHz + Bluetooth
2	EUT in Y with Ant. 1 (Port 1)_WLAN 6GHz + Bluetooth
3	EUT in X with Ant. 2 (Port 1)_WLAN 5GHz + Bluetooth
4	EUT in Y with Ant. 2 (Port 1)_WLAN 6GHz + Bluetooth
5	EUT in X with Ant. 3 (Port 1)_WLAN 5GHz + Bluetooth
6	EUT in Y with Ant. 3 (Port 1)_WLAN 6GHz + Bluetooth
For operating mode 5 is the worst case and it was record in this test report.	
Refer to Appendix F for Radiated Emission Co-location.	

The Worst Case Mode for Following Conformance Tests	
Tests Item	Simultaneous Transmission Analysis - Co-location RF Exposure Evaluation
Operating Mode	
1	Bluetooth + WLAN 5GHz : 2TX
2	Bluetooth + WLAN 6GHz : 2TX
3	WLAN 2.4GHz: 1TX + WLAN 5GHz : 1TX
4	WLAN 2.4GHz: 1TX + WLAN 6GHz : 1TX
5	Bluetooth + WLAN 5GHz : 1TX + WLAN 6GHz : 1TX
Refer to Sporton Test Report No.: FA1N0223-06 for Co-location RF Exposure Evaluation.	

<Partial RU>

The Worst Case Mode for Following Conformance Tests	
Tests Item	Maximum Equivalent Isotopically Radiated Power (E.I.R.P.)
Test Condition	Conducted measurement at transmit chains
1	EUT with Ant. 2

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emission Bandwidth Peak Power Spectral Density (E.I.R.P.)
Test Condition	Conducted measurement at transmit chains
1	EUT with Ant. 1
2	EUT with Ant. 2
3	EUT with Ant. 3

The Worst Case Mode for Following Conformance Tests	
Tests Item	Emission MASK
Test Condition	Conducted measurement at transmit chains
1	EUT with Ant. 1
2	EUT with Ant. 2
3	EUT with Ant. 3

The Worst Case Mode for Following Conformance Tests	
Tests Item	Unwanted Emissions
Test Condition	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.
Operating Mode > 1GHz	CTX
The EUT was performed at X axis, Y axis and Z axis position, and the worst case as below:	
1	1TX: EUT in Y axis with Ant. 1
	2TX: EUT in Y axis with Ant. 1
2	1TX: EUT in Y axis with Ant. 2
	2TX: EUT in Y axis with Ant. 2
3	1TX: EUT in Y axis with Ant. 3
	2TX: EUT in Y axis with Ant. 3

2.3 EUT Operation during Test

For CTX Mode:

The EUT was programmed to be in continuously transmitting mode.

For Normal Link Mode:

During the test, the EUT operation to normal function.

2.4 Accessories

N/A

2.5 Support Equipment

For AC Conduction and Radiated (below 1GHz):

Support Equipment				
No.	**Equipment**	**Brand Name**	**Model Name**	**FCC ID**
A	NB	DELL	PP13S	N/A
B	Earphone	SHYARO CHI	MIC-04	N/A
C	Mouse	Logitech	M-U0026	N/A
D	WIFI AP	ASUS	AX88U	N/A
E	Wireless Connectivity Tester	R&S	CMW270	N/A
F	Test fixture	REALTEK	Ameba adapter	N/A

For Radiated (above 1GHz) and RF Conducted (Other tests):


Support Equipment				
No.	**Equipment**	**Brand Name**	**Model Name**	**FCC ID**
A	NB	DELL	E4300	N/A
B	Test fixture	REALTEK	Ameba adapter	N/A

For RF Conducted (Contention-Based Protocol test):

Support Equipment				
No.	**Equipment**	**Brand Name**	**Model Name**	**FCC ID**
A	Notebook	DELL	E4300	N/A
B	Notebook	DELL	E6230	N/A
C	WLAN AP	LINKSYS	Divo	N/A
D	Test fixture	REALTEK	Ameba adapter	N/A


2.6 Test Setup Diagram

Test Setup Diagram – AC Line Conducted Emission Test




Item	Connection	Shielded	Length
1	Power cable	No	3.1m
2	Audio cable	No	1.1m
3	USB cable	Yes	1.8m

Test Setup Diagram - Radiated Test < 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	3.1m
2	Audio cable	No	1.1m
3	USB cable	Yes	1.8m

Test Setup Diagram - Radiated Test > 1GHz



Item	Connection	Shielded	Length
1	Power cable	No	1.5m

3 Transmitter Test Result

3.1 AC Power-line Conducted Emissions

3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	**Quasi-Peak**	**Average**
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50
Note 1: * Decreases with the logarithm of the frequency.		

3.1.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.1.3 Test Procedures

Test Method
☒ Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.

3.1.4 Test Setup

AC Power-line Conducted Emissions



1—Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long.
2—The I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
3—EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. LISN may be placed on top of, or immediately beneath, reference ground plane.
3.1—All other equipment powered from additional LISN(s).
3.2—A multiple-outlet strip may be used for multiple power cords of non-EUT equipment.
3.3—LISN at least 80 cm from nearest part of EUT chassis.
4—Non-EUT components of EUT system being tested.
5—Rear of EUT, including peripherals, shall all be aligned and flush with edge of tabletop.
6—Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.
7—Antenna can be integral or detachable. If detachable, then the antenna shall be attached for this test.

3.1.5 Measurement Results Calculation

The measured Level is calculated using:

a. Corrected Reading (dBuV) = LISN Factor + Cable Loss + Read Level = Level

b. Margin = - Limit + (Read Level + LISN Factor + Cable Loss)

3.1.6 Test Result of AC Power-line Conducted Emissions

Refer as Appendix A

3.2 Emission Bandwidth

3.2.1 Emission Bandwidth Limit

Emission Bandwidth Limit
UNII Devices
☒ For the 5925-6425 GHz band, N/A
☐ For the 6425-6525 GHz band, N/A
☐ For the 6525-6875 GHz band, N/A
☐ For the 6875-7125 GHz band, N/A
RLAN Devices
☐ For the 5925-6425 GHz band, N/A
☐ For the 6425-6525 GHz band, N/A
☐ For the 6525-6875 GHz band, N/A
☐ For the 6875-7125 GHz band, N/A


3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.2.3 Test Procedures

Test Method	
▪	For the emission bandwidth shall be measured using one of the options below:
	☒ According to KDB 987594 D02 clause II.C, measurement procedure shall refer to FCC KDB 789033 D02, clause C for EBW and clause D for OBW measurement.
	☐ Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
	☐ Refer as IC RSS-Gen, clause 4.6 for bandwidth testing.

3.2.4 Test Setup

Emission Bandwidth


3.2.5 Test Result of Emission Bandwidth

Refer as Appendix B

3.3 Maximum Equivalent Isotopically Radiated Power (E.I.R.P.)

3.3.1 Maximum Equivalent Isotopically Radiated Power (E.I.R.P.) Limit

Maximum Equivalent Isotopically Radiated Power (E.I.R.P.) Limit	
UNII Devices	
☒	For the 5.925 ~ 6.425 GHz band:
	▪ For standard power access point and fixed client device : e.i.r.p < 36 dBm , For outdoor devices, the maximum e.i.r.p. at any elevation angle above 30 degrees not exceed 125 mW (21 dBm).
	▪ For indoor access point : e.i.r.p < 30 dBm.
	▪ For subordinate device control of an indoor access point : e.i.r.p < 30 dBm.
	▪ For client device control of a standard power access point : e.i.r.p < 30 dBm.
	▪ For client device control of an indoor access point : e.i.r.p < 24 dBm.
☐	For the 6.425 ~ 6.525 GHz band:
	▪ For indoor access point : e.i.r.p < 30 dBm.
	▪ For client device control of an indoor access point : e.i.r.p < 24 dBm.
☐	For the 6.525 ~ 6.875 GHz band:
	▪ For standard power access point and fixed client device : e.i.r.p < 36 dBm , For outdoor devices, the maximum e.i.r.p. at any elevation angle above 30 degrees not exceed 125 mW (21 dBm).
	▪ For indoor access point : e.i.r.p < 30 dBm.
	▪ For subordinate device control of an indoor access point : e.i.r.p < 30 dBm.
	▪ For client device control of a standard power access point : e.i.r.p < 30 dBm.
	▪ For client device control of an indoor access point : e.i.r.p < 24 dBm.
☐	For the 6.875 ~ 7.125 GHz band:
	▪ For indoor access point : e.i.r.p < 30 dBm.
	▪ For client device control of an indoor access point : e.i.r.p < 24 dBm.
RLAN Devices	
☐	For the 5.925 ~ 7.125 GHz band:
	▪ For RLAN devices(Indoor) other than client devices < 30 dBm / occupied bandwidth.
	▪ For client devices(Indoor) < 24 dBm / occupied bandwidth.

3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.3.3 Test Procedures

Test Method	
▪	According to FCC KDB 987594 D02 clause II.E, the test measurement procedure shall refer to KDB 789033.
	Average over on/off periods with duty factor
	☐ Refer as FCC KDB 789033 D02, clause E Method SA-2 (spectral trace averaging). Spectrum analyzer setting: RBW/VBW : 1/3MHz ; Detector : RMS ; Trace mode : Average ; Sweep Count 100.
	☐ Refer as FCC KDB 789033 D02, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)
	Wideband RF power meter and average over on/off periods with duty factor
	☒ Refer as FCC KDB 789033 D02, clause E Method PM-G (using an RF average power meter).
☒	For conducted measurement.
	▪ If the EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
	▪ If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \ldots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$
☐	For radiated measurement.
	▪ Refer as FCC KDB 789033 D02 clause II A.1.F ”Antenna-port Conducted versus Radiated Testing”
	▪ Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz.
	▪ Refer as FCC KDB 412172 D01 clause 2.2 for EIRP calculation.

3.3.4 Test Setup

For straddle channel

RF Output Power (Spectrum Analyzer)



For others channel

RF Output Power (Power Meter)



3.3.5 Test Result of Maximum Equivalent Isotopically Radiated Power (E.I.R.P)

Refer as Appendix C

3.4 Peak Power Spectral Density (E.I.R.P.)

3.4.1 Peak Power Spectral Density (E.I.R.P.) Limit

Peak Power Spectral Density (E.I.R.P.) Limit	
UNII Devices	
☒ For the 5.925 ~ 6.425 GHz band:	
	▪ For standard power access point and fixed client device : e.i.r.p PSD < 23 dBm/MHz.
	▪ For indoor access point : e.i.r.p PSD < 5 dBm/MHz.
	▪ For subordinate device control of an indoor access point : e.i.r.p PSD < 5 dBm/MHz.
	▪ For client device control of a standard power access point : e.i.r.p PSD < 17 dBm/MHz.
	▪ For client device control of an indoor access point : e.i.r.p PSD < -1 dBm/MHz.
☐ For the 6.425 ~ 6.525 GHz band:	
	▪ For indoor access point : e.i.r.p PSD < 5 dBm/MHz.
	▪ For client device control of an indoor access point : e.i.r.p PSD < -1 dBm/MHz.
☐ For the 6.525 ~ 6.875 GHz band:	
	▪ For standard power access point and fixed client device : e.i.r.p PSD < 23 dBm/MHz.
	▪ For indoor access point : e.i.r.p PSD < 5 dBm/MHz.
	▪ For subordinate device control of an indoor access point : e.i.r.p PSD < 5 dBm/MHz.
	▪ For client device control of a standard power access point : e.i.r.p PSD < 17 dBm/MHz.
	▪ For client device control of an indoor access point : e.i.r.p PSD < -1 dBm/MHz.
☐ For the 6.875 ~ 7.125 GHz band:	
	▪ For indoor access point : e.i.r.p PSD < 5 dBm/MHz.
	▪ For client device control of an indoor access point : e.i.r.p PSD < -1 dBm/MHz.
RLAN Devices	
☐ For the 5.925 ~ 7.125 GHz band:	
	▪ For RLAN devices(Indoor) other than client devices < 5 dBm / MHz.
	▪ For client devices(Indoor) < -1 dBm / MHz.

3.4.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.4.3 Test Procedures

Test Method	
▪ According to KDB 987594 D02 clause II.F, the measurement procedure shall refer to KDB 789033. Peak power spectral density procedures that the same method as used to determine the conducted output power shall be used to determine the peak power spectral density and use the peak search function on the spectrum analyzer to find the peak of the spectrum. For the peak power spectral density shall be measured using below options:	
	☐ Refer as FCC KDB 789033 D02, F)5) power spectral density can be measured using resolution bandwidths < 1 MHz provided that the results are integrated over 1 MHz bandwidth
	[duty cycle ≥ 98% or external video / power trigger]
	☒ Refer as FCC KDB 789033 D02, clause E Method SA-1 (spectral trace averaging).
	☐ Refer as FCC KDB 789033 D02, clause E Method SA-1 Alt. (RMS detection with slow sweep speed)
	duty cycle < 98% and average over on/off periods with duty factor
	☒ Refer as FCC KDB 789033 D02, clause E Method SA-2 (spectral trace averaging).
	☐ Refer as FCC KDB 789033 D02, clause E Method SA-2 Alt. (RMS detection with slow sweep speed)
☒ For conducted measurement.	
	▪ If the EUT supports multiple transmit chains using options given below:
	☒ Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the NTX output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
	☐ Option 2: Measure and sum spectral maxima across the outputs. With this technique, spectra are measured at each output of the device at the required resolution bandwidth. The maximum value (peak) of each spectrum is determined. These maximum values are then summed mathematically in linear power units across the outputs. These operations shall be performed separately over frequency spans that have different out-of-band or spurious emission limits,
	☐ Option 3: Measure and add 10 log(N) dB, where N is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with 10 log(N). Or each transmit chains shall be add 10 log(N) to compared with the limit.
	▪ If multiple transmit chains, EIRP PPSD calculation could be following as methods: $PPSD_{total} = PPSD_1 + PPSD_2 + \ldots + PPSD_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = PPSD_{total} + DG$
☐ For radiated measurement.	
	▪ Refer as FCC KDB 789033 D02 clause II A.1.F ”Antenna-port Conducted versus Radiated Testing”
	▪ Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz.

Test Method	
	▪ Refer as FCC KDB 412172 D01 clause 2.2 for EIRP calculation.

3.4.4 Test Setup

Conducted Measurement


3.4.5 Test Result of Peak Power Spectral Density (E.I.R.P.)

Refer as Appendix D

3.5 Unwanted Emissions

3.5.1 Transmitter Unwanted Emissions Limit


Unwanted emissions below 1 GHz and restricted band emissions above 1GHz limit			
Frequency Range (MHz)	**Field Strength (uV/m)**	**Field Strength (dBuV/m)**	**Measure Distance (m)**
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m(20 x log (standard distance/ test distance) = 20log(3/1) = 9.54dB.
EX. Above 18GHz emission limit calculation (3m to 1m) = 54dBuV/m at 3m + 9.54dB = 63.54 dBuV/m at 1m.

Un-restricted band emissions above 1GHz Limit	
Frequency	**Limit**
Any outside the 5.945 – 7.125 GHz emission	e.i.r.p. -27 dBm [68.2 dBuV/m@3m]
	Note 1: Using the distance of 1m during the test for above 18 GHz, and the test value to correct for the distance factor at 3m(20 x log (standard distance/ test distance) = 20log(3/1) = 9.54dB. EX. Above 18GHz emission limit calculation (3m to 1m) = 68.2dBuV/m at 3m + 9.54dB = 77.74 dBuV/m at 1m. Note 2:-27 dBm EIRP OOBE is measured RMS which is a deviation from the current 15E rules for 5 GHz bands. In addition, 15.35(b) applies where the peak emissions must be limited to no more than 20 dB above the average limit.
Frequency	**Emission MASK Limit**

5.945 – 7.125 GHz	Power spectral density must be suppressed by 20 dB at 1 MHz outside of channel edge, by 28 dB at one channel bandwidth from the channel center, and by 40 dB at one- and one-half times the channel bandwidth away from channel center. At frequencies between one megahertz outside an unlicensed device's channel edge and one channel bandwidth from the center of the channel, the limits must be linearly interpolated between 20 dB and 28 dB suppression, and at frequencies between one and one- and one-half times an unlicensed device's channel bandwidth, the limits must be linearly interpolated between 28 dB and 40 dB suppression. Emissions removed from the channel center by more than one- and one-half times the channel bandwidth must be suppressed by at least 40 dB. 

3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.


3.5.3 Test Procedures

Test Method			
▪ According to KDB 987594 D02 II.G. the unwanted emission measurement procedure shall refer to KDB 789300(except emission MASK). Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 m for frequencies above 30 MHz, unless it can be further demonstrated that measurements at a distance of 30 m or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).			
▪ The average emission levels shall be measured in [duty cycle ≥ 98 or duty factor].			
▪ For the transmitter unwanted emissions shall be measured using following options below:			
	▪ Refer as FCC KDB 789033 D02, clause G)2) for unwanted emissions into non-restricted bands.		
	▪ Refer as FCC KDB 789033 D02, clause G)1) for unwanted emissions into restricted bands.		
		☒	Refer as FCC KDB 789033 D02, G)6) Method AD (Trace Averaging). (For unrestricted band measurement)
		☐	Refer as FCC KDB 789033 D02, G)6) Method VB (Reduced VBW).
		☒	Refer as ANSI C63.10, clause 11.12.2.5.3 (Reduced VBW). VBW ≥ 1/T, where T is pulse time.(For restricted band average measurement)
		☐	Refer as ANSI C63.10, clause 7.5 average value of pulsed emissions.
		☒	Refer as FCC KDB 789033 D02, clause G)5) measurement procedure peak limit.
		☐	Refer as ANSI C63.10, clause 4.1.4.2.2 measurement procedure peak limit.
	▪ Refer as FCC KDB 789033 D02, clause G)3)d)ii) for Band edge Integration measurements.		
▪ For emission MASK shall be measured using following options below:			
		☒	Refer as FCC draft KDB 987594 D02, J) In-Band Emissions
▪ For radiated measurement.			
	▪ Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.		
	▪ Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.		
	▪ Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1GHz.		
▪ The any unwanted emissions level shall not exceed the fundamental emission level.			
▪ All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.			


3.5.4 Test Setup

Transmitter Radiated Unwanted Emissions


9kHz ~30MHz




30MHz~1GHz



Above 1GHz



Emission MASK



3.5.5 Measurement Results Calculation

The measured Level is calculated using:

Corrected Reading: Antenna factor (AF) + Cable loss (CL) + Read level (Raw) - Preamp factor (PA)(if applicable) = Level

3.5.6 Transmitter Unwanted Emissions (Below 30MHz)

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to KDB414788 Radiated Test Site, and the result came out very similar.
All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.
The radiated emissions were investigated from 9 kHz or the lowest frequency generated within the device, up to the 10th harmonic or 40 GHz, whichever is appropriate.

3.5.7 Test Result of Transmitter Unwanted Emissions

Refer as Appendix E

3.6 Contention Based Protocol

3.6.1 Contention Based Protocol Limit

EUT can detect an AWGN signal with 90% (or better) level of certainty.

3.6.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.6.3 Test Procedures

Test Method	
▪	For Contention Based Protocol shall be measured using following options below:
☒	Refer as FCC draft KDB 987594 D02, I) In-Band Emissions

3.6.4 Test Setup

Contention Based Protocol



3.6.5 Test Result of Contention Based Protocol

Refer as Appendix F

3.7 Frequency Stability

3.7.1 Frequency Stability Limit

Frequency Stability Limit
▪ In-band emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.7.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.7.3 Test Procedures

Test Method	
▪ Refer as ANSI C63.10, clause 6.8 for frequency stability tests	
	▪ Frequency stability with respect to ambient temperature
	▪ Frequency stability when varying supply voltage
	▪ Extreme temperature is -30°C~50°C.

3.7.4 Test Setup

Frequency Stability


3.7.5 Test Result of Frequency Stability

Refer as Appendix G

4 Test Equipment and Calibration Data

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
EMI Receiver	Agilent	N9038A	My52260123	9kHz ~ 8.4GHz	Feb. 22, 2022	Feb. 21, 2023	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Feb. 09, 2022	Feb. 08, 2023	Conduction (CO01-CB)
LISN	Schwarzbeck	NSLK 8127	8127647	9kHz ~ 30MHz	Apr. 12, 2022	Apr. 11, 2023	Conduction (CO01-CB)
Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz ~ 30MHz	Feb. 10, 2022	Feb. 09, 2023	Conduction (CO01-CB)
COND Cable	Woken	Cable	Low cable-CO01	9kHz ~ 30MHz	May 19, 2021	May 18, 2022	Conduction (CO01-CB)
Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Conduction (CO01-CB)
Loop Antenna	Teseq	HLA 6120	31244	9kHz - 30 MHz	Mar. 18, 2022	Mar. 17, 2023	Radiation (10CH01-CB)
10m Semi Anechoic Chamber NSA	TDK	SAC-10M	10CH01-CB	30MHz~1GHz 10m,3m	Jan. 27, 2022	Jan. 26, 2023	Radiation (10CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10783	9kHz ~ 1.3GHz	Mar. 11, 2022	Mar. 10, 2023	Radiation (10CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10784	9kHz ~ 1.3GHz	Mar. 11, 2022	Mar. 10, 2023	Radiation (10CH01-CB)
Low Cable	Woken	SUCOFLEX 104	low cable-01	25MHz ~ 1GHz	Oct. 19, 2021	Oct. 18, 2022	Radiation (10CH01-CB)
High Cable	Woken	SUCOFLEX 104	low cable-02	25MHz ~ 1GHz	Oct. 19, 2021	Oct. 18, 2022	Radiation (10CH01-CB)
Bilog Antenna with 6dB Attenuator	Chase & EMCI	CBL6111A &N-6-06	1543 &AT-N0609	30MHz ~ 1GHz	Jul. 01, 2021	Jun. 30, 2022	Radiation (10CH01-CB)
EMI Test Receiver	Rohde&Schwarz	ESCI	100186	9kHz ~ 3GHz	Jul. 12, 2021	Jul. 11, 2022	Radiation (10CH01-CB)
Spectrum Analyzer	Rohde&Schwarz	FSV30	101026	9kHz ~ 30GHz	Apr. 22, 2022	Apr. 21, 2023	Radiation (10CH01-CB)
Signal Analyzer	R&S	FSV40	101904	9kHz ~ 40GHz	Apr. 26, 2022	Apr. 25, 2023	Radiation (10CH01-CB)
Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (10CH01-CB)
3m Semi Anechoic Chamber VSWR	TDK	SAC-3M	03CH01-CB	1GHz ~18GHz 3m	May 06, 2022	May 05, 2023	Radiation (03CH01-CB)
Horn Antenna	ETS-LINDGREN	3115	00075790	750MHz ~ 18GHz	Nov. 06, 2021	Nov. 05, 2022	Radiation (03CH01-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 05, 2021	Aug. 04, 2022	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02121	1GHz ~ 26.5GHz	May 19, 2022	May 18, 2023	Radiation (03CH01-CB)
Spectrum Analyzer	R&S	FSP40	100056	9kHz ~ 40GHz	May 06, 2022	May 05, 2023	Radiation (03CH01-CB)

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	RG402	High Cable-16	1 GHz ~ 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH01-CB)
RF Cable-high	Woken	RG402	High Cable-16+17	1 GHz ~ 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH01-CB)
High Cable	Woken	WCA0929M	40G#5+7	1GHz ~ 40 GHz	Dec. 14, 2021	Dec. 13, 2022	Radiation (03CH01-CB)
High Cable	Woken	WCA0929M	40G#5	1GHz ~ 40 GHz	Dec. 08, 2021	Dec. 07, 2022	Radiation (03CH01-CB)
High Cable	Woken	WCA0929M	40G#7	1GHz ~ 40 GHz	Dec. 14, 2021	Dec. 13, 2022	Radiation (03CH01-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH01-CB)
Band Rejector	MTJ	6G Band Rejector	CB6G-BRJ-01	1GHz ~ 7.4GHz	Jan. 11, 2022	Jan. 10, 2023	Radiation (03CH01-CB)
Band Rejector	MTJ	6G Band Rejector	CB6G-BRJ-02	1GHz ~ 8GHz	Jan. 11, 2022	Jan. 10, 2023	Radiation (03CH01-CB)
3m Semi Anechoic Chamber VSWR	TDK	SAC-3M	03CH03-CB	1GHz ~18GHz 3m	May 05, 2022	May 04, 2023	Radiation (03CH03-CB)
Horn Antenna	ETS・Lindgren	3115	6821	750MHz~18GHz	Jan. 21, 2022	Jan. 20, 2023	Radiation (03CH03-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 05, 2021	Aug. 04, 2022	Radiation (03CH03-CB)
Pre-Amplifier	Agilent	8449B	3008A02121	1GHz ~ 26.5GHz	May 19, 2022	May 18, 2023	Radiation (03CH03-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Jul. 13, 2021	Jul. 12, 2022	Radiation (03CH03-CB)
Spectrum Analyzer	R&S	FSP40	100019	9kHz ~ 40GHz	Jun. 10, 2022	Jun. 09, 2023	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-20+29	1GHz ~ 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-29	1GHz ~ 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-18	1GHz ~ 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH03-CB)
RF Cable-high	Woken	RG402	High Cable-18+19	1GHz ~ 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH03-CB)
High Cable	Woken	RG402	40G#4	1GHz ~ 40 GHz	Dec. 08, 2021	Dec. 07, 2022	Radiation (03CH03-CB)
High Cable	Woken	WCA0929M	40G#5	1GHz ~ 40 GHz	Dec. 08, 2021	Dec. 07, 2022	Radiation (03CH03-CB)
Band Rejector	MTJ	6G Band Rejector	CB6G-BRJ-01	1GHz ~ 7.4GHz	Jan. 11, 2022	Jan. 10, 2023	Radiation (03CH03-CB)
Band Rejector	MTJ	6G Band Rejector	CB6G-BRJ-02	1GHz ~ 8GHz	Jan. 11, 2022	Jan. 10, 2023	Radiation (03CH03-CB)
Test Software	Audix	E3	6.2009-10-8b	-	N.C.R.	N.C.R.	Radiation (03CH03-CB)
3m Semi Anechoic Chamber NSA	TDK	SAC-3M	03CH04-CB	30 MHz ~ 1 GHz	Aug. 08, 2021	Aug. 07, 2022	Radiation (03CH04-CB)

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
3m Semi Anechoic Chamber VSWR	TDK	SAC-3M	03CH04-CB	1GHz ~18GHz 3m	Feb. 24, 2022	Feb. 23, 2023	Radiation (03CH04-CB)
Horn Antenna	ETS・Lindgren	3115	00143147	750MHz~18GHz	Oct. 25, 2021	Oct. 24, 2022	Radiation (03CH04-CB)
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Aug. 05, 2021	Aug. 04, 2022	Radiation (03CH04-CB)
Pre-Amplifier	Agilent	83017A	MY53270063	0.5GHz ~ 26.5GHz	Jul. 12, 2021	Jul. 11, 2022	Radiation (03CH04-CB)
Pre-Amplifier	MITEQ	TTA1840-35-HG	1864479	18GHz ~ 40GHz	Jul. 13, 2021	Jul. 12, 2022	Radiation (03CH04-CB)
Spectrum Analyzer	R&S	FSP40	100142	9kHz~40GHz	Mar. 28, 2022	Mar. 27, 2023	Radiation (03CH04-CB
RF Cable-high	Woken	RG402	High Cable-21	1GHz - 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH04-CB)
RF Cable-high	Woken	RG402	High Cable-21+67	1GHz - 18GHz	Oct. 04, 2021	Oct. 03, 2022	Radiation (03CH04-CB)
High Cable	Woken	RG402	40G#4	1GHz ~ 40 GHz	Dec. 08, 2021	Dec. 07, 2022	Radiation (03CH04-CB)
High Cable	Woken	WCA0929M	40G#5	1GHz ~ 40 GHz	Dec. 08, 2021	Dec. 07, 2022	Radiation (03CH04-CB)
Test Software	SPORTON	SENSE	V5.10	-	N.C.R.	N.C.R.	Radiation (03CH04-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	May 21, 2021	May 20, 2022	Conducted (TH01-CB)
Signal Analyzer	R&S	FSV40	101904	9kHz ~ 40GHz	Apr. 26, 2022	Apr. 25, 2023	Conducted (TH01-CB)
Spectrum analyzer	R&S	FSV40	100979	9kHz~40GHz	May 27, 2022	May 26, 2023	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	May 28, 2021	May 27, 2022	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	May 23, 2022	May 22, 2023	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-06	1 GHz – 26.5 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-07	1 GHz –26.5 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-08	1 GHz –26.5 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-09	1 GHz –26.5 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-10	1 GHz –26.5 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	High Cable-30	1 GHz –26.5 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (TH01-CB)
Switch	SPTCB	SP-SWI	SWI-01	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	SWI-01-P1	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH01-CB)

Instrument	Brand	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date	Remark
RF Cable-high	Woken	RG402	SWI-01-P2	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	SWI-01-P3	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	SWI-01-P4	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH01-CB)
RF Cable-high	Woken	RG402	SWI-01-P5	1 GHz –26.5 GHz	Dec. 13, 2021	Dec. 12, 2022	Conducted (TH01-CB)
Power Sensor	Agilent	E9327A	US40442088	50MHz~18GHz	Feb. 21, 2022	Feb. 20, 2023	Conducted (TH01-CB)
Power Meter	Agilent	E4416A	GB41291199	50MHz~18GHz	Feb. 21, 2022	Feb. 20, 2023	Conducted (TH01-CB)
Spectrum Analyzer	R&S	FSV40	101025	9kHz ~ 40GHz	Nov. 06, 2021	Nov. 05, 2022	Conducted (DF02-CB)
Vector Signal generator	R&S	SMW200A	109426	100KHz- 7.5GHz	Dec. 28, 2021	Dec. 27, 2022	Conducted (DF02-CB)
RF Power Divider	STI	2 Way	DV-2way -07	1GHz ~ 8GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (DF02-CB)
RF Power Divider	STI	2 Way	DV-2way -08	1GHz ~ 8GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (DF02-CB)
RF Cable-high	Woken	RG402	High Cable-61	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (DF02-CB)
RF Cable-high	Woken	RG402	High Cable-62	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (DF02-CB)
RF Cable-high	Woken	RG402	High Cable-63	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (DF02-CB)
RF Cable-high	Woken	RG402	High Cable-66	1 GHz – 18 GHz	Oct. 04, 2021	Oct. 03, 2022	Conducted (DF02-CB)
100MS/s Digitizer	N.I	USB-5133	F65206	N/A	Nov. 15, 2020	Nov. 14, 2021	Conducted (DF02-CB)
100MS/s Digitizer	N.I	USB-5133	01BFB476	N/A	Mar. 22, 2021	Mar. 21, 2022	Conducted (DF02-CB)
100MS/s Digitizer	N.I	USB-5133	F65206	N/A	Nov. 25, 2021	Nov. 24, 2022	Conducted (DF02-CB)

Note: Calibration Interval of instruments listed above is one year.


NCR means Non-Calibration required.

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Condition
Mode 2	Pass	QP	303k	49.73	60.17	-10.44	Line

Mode 2


13/05/2022



Type	Freq	Level	Limit	Margin	Factor	Condition	Comment	Raw	LISN	CL	AT			
	(Hz)	(dBuV)	(dBuV)	(dB)	(dB)			(dBuV)	(dB)	(dB)	(dB)			
QP	217.5k	51.25	62.92	-11.67	9.97	Line	-	41.28	0.06	0.02	9.89			
AV	217.5k	41.20	52.92	-11.72	9.97	Line	-	31.23	0.06	0.02	9.89			
QP	303k	49.73	60.17	-10.44	9.97	Line	"Worst"	39.76	0.06	0.02	9.89			
AV	303k	35.87	50.17	-14.30	9.97	Line	-	25.90	0.06	0.02	9.89			
QP	1.581M	32.27	56.00	-23.73	10.01	Line	-	22.26	0.08	0.04	9.89			
AV	1.581M	23.37	46.00	-22.63	10.01	Line	-	13.36	0.08	0.04	9.89			
QP	3.512M	36.85	56.00	-19.15	10.07	Line	-	26.78	0.11	0.07	9.89			
AV	3.512M	23.68	46.00	-22.32	10.07	Line	-	13.61	0.11	0.07	9.89			
QP	3.701M	36.56	56.00	-19.44	10.08	Line	-	26.48	0.12	0.07	9.89			
AV	3.701M	23.28	46.00	-22.72	10.08	Line	-	13.20	0.12	0.07	9.89			
QP	16.467M	35.01	60.00	-24.99	10.34	Line	-	24.67	0.28	0.11	9.95			
AV	16.467M	33.72	50.00	-16.28	10.34	Line	-	23.38	0.28	0.11	9.95			

Mode 2

13/05/2022



Type	Freq	Level	Limit	Margin	Factor	Condition	Comment	Raw	LISN	CL	AT
	(Hz)	(dBuV)	(dBuV)	(dB)	(dB)			(dBuV)	(dB)	(dB)	(dB)
QP	217.5k	51.31	62.92	-11.61	9.98	Neutral	"Worst"	41.33	0.07	0.02	9.89
AV	217.5k	40.99	52.92	-11.93	9.98	Neutral	-	31.01	0.07	0.02	9.89
QP	298.5k	48.18	60.28	-12.10	9.98	Neutral	-	38.20	0.07	0.02	9.89
AV	298.5k	34.28	50.28	-16.00	9.98	Neutral	-	24.30	0.07	0.02	9.89
QP	339k	33.53	59.23	-25.70	9.98	Neutral	-	23.55	0.07	0.02	9.89
AV	339k	23.75	49.23	-25.48	9.98	Neutral	-	13.77	0.07	0.02	9.89
QP	3.291M	34.54	56.00	-21.46	10.07	Neutral	-	24.47	0.12	0.06	9.89
AV	3.291M	21.71	46.00	-24.29	10.07	Neutral	-	11.64	0.12	0.06	9.89
QP	10.518M	27.42	60.00	-32.58	10.22	Neutral	-	17.20	0.24	0.07	9.91
AV	10.518M	19.73	50.00	-30.27	10.22	Neutral	-	9.51	0.24	0.07	9.91
QP	16.467M	35.03	60.00	-24.97	10.34	Neutral	-	24.69	0.28	0.11	9.95
AV	16.467M	33.76	50.00	-16.24	10.34	Neutral	-	23.42	0.28	0.11	9.95

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	20.64M	18.921M	18M9D1D	20.55M	18.891M
802.11ax HEW40_Nss1,(MCS0)_1TX	40.26M	38.081M	38M1D1D	40.2M	38.021M
802.11ax HEW80_Nss1,(MCS0)_1TX	81.12M	77.961M	78M0D1D	81M	77.961M
802.11ax HEW160_Nss1,(MCS0)_1TX	298.08M	158.561M	159MD1D	297.36M	158.321M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	20.64M	18.921M
6195MHz	Pass	Inf	20.61M	18.891M
6415MHz	Pass	Inf	20.55M	18.891M
802.11ax HEW40_Nss1,(MCS0)_1TX	-	-	-	-
5965MHz	Pass	Inf	40.2M	38.021M
6205MHz	Pass	Inf	40.26M	38.081M
6405MHz	Pass	Inf	40.26M	38.021M
802.11ax HEW80_Nss1,(MCS0)_1TX	-	-	-	-
5985MHz	Pass	Inf	81.12M	77.961M
6225MHz	Pass	Inf	81.12M	77.961M
6385MHz	Pass	Inf	81M	77.961M
802.11ax HEW160_Nss1,(MCS0)_1TX	-	-	-	-
6025MHz	Pass	Inf	297.36M	158.321M
6185MHz	Pass	Inf	297.6M	158.321M
6345MHz	Pass	Inf	298.08M	158.561M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

5955MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.64M	5.94465G	5.96529G	18.921M	5.945495G	5.964415G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz


13/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.61M	6.18465G	6.20526G	18.891M	6.185495G	6.204385G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


6415MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.55M	6.40465G	6.4252G	18.891M	6.405495G	6.424385G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

5965MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.2M	5.9449G	5.9851G	38.021M	5.94587G	5.983891G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

6205MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.1849G	6.22516G	38.081M	6.18587G	6.223951G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

6405MHz


13/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.3849G	6.42516G	38.021M	6.38587G	6.423891G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW


5985MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	5.94444G	6.02556G	77.961M	5.946019G	6.023981G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW

6225MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	6.18444G	6.26556G	77.961M	6.186019G	6.263981G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW

6385MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81M	6.34444G	6.42544G	77.961M	6.346019G	6.423981G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6025MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
297.36M	5.88652G	6.18388G	158.321M	5.94584G	6.10416G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6185MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
297.6M	6.04628G	6.34388G	158.321M	6.10584G	6.26416G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6345MHz

13/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
298.08M	6.20604G	6.50412G	158.561M	6.26584G	6.4244G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	20.64M	18.921M	18M9D1D	20.55M	18.891M
802.11ax HEW40_Nss1,(MCS0)_1TX	40.26M	38.081M	38M1D1D	40.2M	38.021M
802.11ax HEW80_Nss1,(MCS0)_1TX	81.12M	77.961M	78M0D1D	81M	77.961M
802.11ax HEW160_Nss1,(MCS0)_1TX	298.08M	158.561M	159MD1D	297.36M	158.321M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	20.64M	18.921M
6195MHz	Pass	Inf	20.61M	18.891M
6415MHz	Pass	Inf	20.55M	18.891M
802.11ax HEW40_Nss1,(MCS0)_1TX	-	-	-	-
5965MHz	Pass	Inf	40.2M	38.021M
6205MHz	Pass	Inf	40.26M	38.081M
6405MHz	Pass	Inf	40.26M	38.021M
802.11ax HEW80_Nss1,(MCS0)_1TX	-	-	-	-
5985MHz	Pass	Inf	81.12M	77.961M
6225MHz	Pass	Inf	81.12M	77.961M
6385MHz	Pass	Inf	81M	77.961M
802.11ax HEW160_Nss1,(MCS0)_1TX	-	-	-	-
6025MHz	Pass	Inf	297.36M	158.321M
6185MHz	Pass	Inf	297.6M	158.321M
6345MHz	Pass	Inf	298.08M	158.561M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

5955MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.64M	5.94465G	5.96529G	18.921M	5.945495G	5.964415G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.61M	6.18465G	6.20526G	18.891M	6.185495G	6.204385G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6415MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.55M	6.40465G	6.4252G	18.891M	6.405495G	6.424385G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

5965MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.2M	5.9449G	5.9851G	38.021M	5.94587G	5.983891G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

6205MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.1849G	6.22516G	38.081M	6.18587G	6.223951G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

6405MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.3849G	6.42516G	38.021M	6.38587G	6.423891G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW

5985MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	5.94444G	6.02556G	77.961M	5.946019G	6.023981G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW

6225MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	6.18444G	6.26556G	77.961M	6.186019G	6.263981G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW

6385MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81M	6.34444G	6.42544G	77.961M	6.346019G	6.423981G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6025MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
297.36M	5.88652G	6.18388G	158.321M	5.94584G	6.10416G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6185MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
297.6M	6.04628G	6.34388G	158.321M	6.10584G	6.26416G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6345MHz

13/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
298.08M	6.20604G	6.50412G	158.561M	6.26584G	6.4244G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	20.64M	18.921M	18M9D1D	20.55M	18.891M
802.11ax HEW40_Nss1,(MCS0)_1TX	40.26M	38.081M	38M1D1D	40.2M	38.021M
802.11ax HEW80_Nss1,(MCS0)_1TX	81.12M	77.961M	78M0D1D	81M	77.961M
802.11ax HEW160_Nss1,(MCS0)_1TX	298.08M	158.561M	159MD1D	297.36M	158.321M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	20.64M	18.921M
6195MHz	Pass	Inf	20.61M	18.891M
6415MHz	Pass	Inf	20.55M	18.891M
802.11ax HEW40_Nss1,(MCS0)_1TX	-	-	-	-
5965MHz	Pass	Inf	40.2M	38.021M
6205MHz	Pass	Inf	40.26M	38.081M
6405MHz	Pass	Inf	40.26M	38.021M
802.11ax HEW80_Nss1,(MCS0)_1TX	-	-	-	-
5985MHz	Pass	Inf	81.12M	77.961M
6225MHz	Pass	Inf	81.12M	77.961M
6385MHz	Pass	Inf	81M	77.961M
802.11ax HEW160_Nss1,(MCS0)_1TX	-	-	-	-
6025MHz	Pass	Inf	297.36M	158.321M
6185MHz	Pass	Inf	297.6M	158.321M
6345MHz	Pass	Inf	298.08M	158.561M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

5955MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.64M	5.94465G	5.96529G	18.921M	5.945495G	5.964415G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.61M	6.18465G	6.20526G	18.891M	6.185495G	6.204385G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6415MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.55M	6.40465G	6.4252G	18.891M	6.405495G	6.424385G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

5965MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.2M	5.9449G	5.9851G	38.021M	5.94587G	5.983891G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

6205MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.1849G	6.22516G	38.081M	6.18587G	6.223951G	Inf	1

802.11ax HEW40_Nss1,(MCS0)_1TX EBW

6405MHz


13/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.3849G	6.42516G	38.021M	6.38587G	6.423891G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW


5985MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	5.94444G	6.02556G	77.961M	5.946019G	6.023981G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW

6225MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	6.18444G	6.26556G	77.961M	6.186019G	6.263981G	Inf	1

802.11ax HEW80_Nss1,(MCS0)_1TX EBW

6385MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81M	6.34444G	6.42544G	77.961M	6.346019G	6.423981G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6025MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
297.36M	5.88652G	6.18388G	158.321M	5.94584G	6.10416G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6185MHz

13/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
297.6M	6.04628G	6.34388G	158.321M	6.10584G	6.26416G	Inf	1

802.11ax HEW160_Nss1,(MCS0)_1TX EBW

6345MHz

13/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
298.08M	6.20604G	6.50412G	158.561M	6.26584G	6.4244G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	20.61M	18.921M	18M9D1D	20.49M	18.891M
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	40.32M	38.021M	38M0D1D	40.02M	37.961M
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	81.12M	77.841M	77M8D1D	80.88M	77.841M
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	163.2M	157.361M	157MD1D	162.96M	156.882M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	20.49M	18.891M	20.58M	18.891M
6195MHz	Pass	Inf	20.58M	18.921M	20.61M	18.891M
6415MHz	Pass	Inf	20.58M	18.891M	20.55M	18.891M
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5965MHz	Pass	Inf	40.26M	38.021M	40.2M	38.021M
6205MHz	Pass	Inf	40.02M	38.021M	40.26M	38.021M
6405MHz	Pass	Inf	40.26M	37.961M	40.32M	38.021M
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5985MHz	Pass	Inf	81.12M	77.841M	80.88M	77.841M
6225MHz	Pass	Inf	81M	77.841M	80.88M	77.841M
6385MHz	Pass	Inf	81.12M	77.841M	80.88M	77.841M
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
6025MHz	Pass	Inf	163.2M	157.361M	163.2M	157.121M
6185MHz	Pass	Inf	162.96M	157.121M	162.96M	156.882M
6345MHz	Pass	Inf	163.2M	157.121M	162.96M	156.882M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW

5955MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.49M	5.94471G	5.9652G	18.891M	5.945525G	5.964415G	Inf	1
20.58M	5.94468G	5.96526G	18.891M	5.945525G	5.964415G	Inf	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW

6195MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.58M	6.18471G	6.20529G	18.921M	6.185495G	6.204415G	Inf	1
20.61M	6.18465G	6.20526G	18.891M	6.185525G	6.204415G	Inf	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW

6415MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.58M	6.40468G	6.42526G	18.891M	6.405525G	6.424415G	Inf	1
20.55M	6.40468G	6.42523G	18.891M	6.405525G	6.424415G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

5965MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	5.94496G	5.98522G	38.021M	5.94593G	5.983951G	Inf	1
40.2M	5.94496G	5.98516G	38.021M	5.94593G	5.983951G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

6205MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.02M	6.18502G	6.22504G	38.021M	6.18593G	6.223951G	Inf	1
40.26M	6.18496G	6.22522G	38.021M	6.18593G	6.223951G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

6405MHz


15/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.38496G	6.42522G	37.961M	6.38593G	6.423891G	Inf	1
40.32M	6.3849G	6.42522G	38.021M	6.38593G	6.423951G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW


5985MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	5.94444G	6.02556G	77.841M	5.946139G	6.023981G	Inf	1
80.88M	5.94456G	6.02544G	77.841M	5.946139G	6.023981G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW

6225MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81M	6.18456G	6.26556G	77.841M	6.186139G	6.263981G	Inf	1
80.88M	6.18456G	6.26544G	77.841M	6.186139G	6.263981G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW

6385MHz

16/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	6.34444G	6.42556G	77.841M	6.346139G	6.423981G	Inf	1
80.88M	6.34456G	6.42544G	77.841M	6.346139G	6.423981G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW

6025MHz

17/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
163.2M	5.9434G	6.1066G	157.361M	5.946319G	6.103681G	Inf	1
163.2M	5.9434G	6.1066G	157.121M	5.946319G	6.103441G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW

6185MHz

17/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
162.96M	6.1034G	6.26636G	157.121M	6.106079G	6.263201G	Inf	1
162.96M	6.1034G	6.26636G	156.882M	6.106319G	6.263201G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW

6345MHz

17/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
163.2M	6.2634G	6.4266G	157.121M	6.266319G	6.423441G	Inf	1
162.96M	6.2634G	6.42636G	156.882M	6.266319G	6.423201G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	20.61M	18.921M	18M9D1D	20.49M	18.891M
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	40.32M	38.021M	38M0D1D	40.02M	37.961M
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	81.12M	77.841M	77M8D1D	80.88M	77.841M
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	163.2M	157.361M	157MD1D	162.96M	156.882M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	20.49M	18.891M	20.58M	18.891M
6195MHz	Pass	Inf	20.58M	18.921M	20.61M	18.891M
6415MHz	Pass	Inf	20.58M	18.891M	20.55M	18.891M
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5965MHz	Pass	Inf	40.26M	38.021M	40.2M	38.021M
6205MHz	Pass	Inf	40.02M	38.021M	40.26M	38.021M
6405MHz	Pass	Inf	40.26M	37.961M	40.32M	38.021M
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5985MHz	Pass	Inf	81.12M	77.841M	80.88M	77.841M
6225MHz	Pass	Inf	81M	77.841M	80.88M	77.841M
6385MHz	Pass	Inf	81.12M	77.841M	80.88M	77.841M
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
6025MHz	Pass	Inf	163.2M	157.361M	163.2M	157.121M
6185MHz	Pass	Inf	162.96M	157.121M	162.96M	156.882M
6345MHz	Pass	Inf	163.2M	157.121M	162.96M	156.882M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.49M	5.94471G	5.9652G	18.891M	5.945525G	5.964415G	Inf	1
20.58M	5.94468G	5.96526G	18.891M	5.945525G	5.964415G	Inf	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW

6195MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.58M	6.18471G	6.20529G	18.921M	6.185495G	6.204415G	Inf	1
20.61M	6.18465G	6.20526G	18.891M	6.185525G	6.204415G	Inf	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW

6415MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.58M	6.40468G	6.42526G	18.891M	6.405525G	6.424415G	Inf	1
20.55M	6.40468G	6.42523G	18.891M	6.405525G	6.424415G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

5965MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	5.94496G	5.98522G	38.021M	5.94593G	5.983951G	Inf	1
40.2M	5.94496G	5.98516G	38.021M	5.94593G	5.983951G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

6205MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.02M	6.18502G	6.22504G	38.021M	6.18593G	6.223951G	Inf	1
40.26M	6.18496G	6.22522G	38.021M	6.18593G	6.223951G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

6405MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.38496G	6.42522G	37.961M	6.38593G	6.423891G	Inf	1
40.32M	6.3849G	6.42522G	38.021M	6.38593G	6.423951G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW

5985MHz

16/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	5.94444G	6.02556G	77.841M	5.946139G	6.023981G	Inf	1
80.88M	5.94456G	6.02544G	77.841M	5.946139G	6.023981G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW

6225MHz

16/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81M	6.18456G	6.26556G	77.841M	6.186139G	6.263981G	Inf	1
80.88M	6.18456G	6.26544G	77.841M	6.186139G	6.263981G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW

6385MHz

16/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	6.34444G	6.42556G	77.841M	6.346139G	6.423981G	Inf	1
80.88M	6.34456G	6.42544G	77.841M	6.346139G	6.423981G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW

6025MHz


17/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
163.2M	5.9434G	6.1066G	157.361M	5.946319G	6.103681G	Inf	1
163.2M	5.9434G	6.1066G	157.121M	5.946319G	6.103441G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW


6185MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
162.96M	6.1034G	6.26636G	157.121M	6.106079G	6.263201G	Inf	1
162.96M	6.1034G	6.26636G	156.882M	6.106319G	6.263201G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW

6345MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
163.2M	6.2634G	6.4266G	157.121M	6.266319G	6.423441G	Inf	1
162.96M	6.2634G	6.42636G	156.882M	6.266319G	6.423201G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	20.61M	18.921M	18M9D1D	20.49M	18.891M
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	40.32M	38.021M	38M0D1D	40.02M	37.961M
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	81.12M	77.841M	77M8D1D	80.88M	77.841M
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	163.2M	157.361M	157MD1D	162.96M	156.882M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	20.49M	18.891M	20.58M	18.891M
6195MHz	Pass	Inf	20.58M	18.921M	20.61M	18.891M
6415MHz	Pass	Inf	20.58M	18.891M	20.55M	18.891M
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5965MHz	Pass	Inf	40.26M	38.021M	40.2M	38.021M
6205MHz	Pass	Inf	40.02M	38.021M	40.26M	38.021M
6405MHz	Pass	Inf	40.26M	37.961M	40.32M	38.021M
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5985MHz	Pass	Inf	81.12M	77.841M	80.88M	77.841M
6225MHz	Pass	Inf	81M	77.841M	80.88M	77.841M
6385MHz	Pass	Inf	81.12M	77.841M	80.88M	77.841M
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-
6025MHz	Pass	Inf	163.2M	157.361M	163.2M	157.121M
6185MHz	Pass	Inf	162.96M	157.121M	162.96M	156.882M
6345MHz	Pass	Inf	163.2M	157.121M	162.96M	156.882M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW

5955MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.49M	5.94471G	5.9652G	18.891M	5.945525G	5.964415G	Inf	1
20.58M	5.94468G	5.96526G	18.891M	5.945525G	5.964415G	Inf	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW

6195MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.58M	6.18471G	6.20529G	18.921M	6.185495G	6.204415G	Inf	1
20.61M	6.18465G	6.20526G	18.891M	6.185525G	6.204415G	Inf	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX EBW

6415MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
20.58M	6.40468G	6.42526G	18.891M	6.405525G	6.424415G	Inf	1
20.55M	6.40468G	6.42523G	18.891M	6.405525G	6.424415G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

5965MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	5.94496G	5.98522G	38.021M	5.94593G	5.983951G	Inf	1
40.2M	5.94496G	5.98516G	38.021M	5.94593G	5.983951G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

6205MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.02M	6.18502G	6.22504G	38.021M	6.18593G	6.223951G	Inf	1
40.26M	6.18496G	6.22522G	38.021M	6.18593G	6.223951G	Inf	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX EBW

6405MHz

15/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
40.26M	6.38496G	6.42522G	37.961M	6.38593G	6.423891G	Inf	1
40.32M	6.3849G	6.42522G	38.021M	6.38593G	6.423951G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW

5985MHz

16/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	5.94444G	6.02556G	77.841M	5.946139G	6.023981G	Inf	1
80.88M	5.94456G	6.02544G	77.841M	5.946139G	6.023981G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW

6225MHz

16/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81M	6.18456G	6.26556G	77.841M	6.186139G	6.263981G	Inf	1
80.88M	6.18456G	6.26544G	77.841M	6.186139G	6.263981G	Inf	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX EBW

6385MHz

16/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
81.12M	6.34444G	6.42556G	77.841M	6.346139G	6.423981G	Inf	1
80.88M	6.34456G	6.42544G	77.841M	6.346139G	6.423981G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW

6025MHz


17/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
163.2M	5.9434G	6.1066G	157.361M	5.946319G	6.103681G	Inf	1
163.2M	5.9434G	6.1066G	157.121M	5.946319G	6.103441G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW


6185MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
162.96M	6.1034G	6.26636G	157.121M	6.106079G	6.263201G	Inf	1
162.96M	6.1034G	6.26636G	156.882M	6.106319G	6.263201G	Inf	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX EBW

6345MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
163.2M	6.2634G	6.4266G	157.121M	6.266319G	6.423441G	Inf	1
162.96M	6.2634G	6.42636G	156.882M	6.266319G	6.423201G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.35M	17.511M	17M5D1D	19.08M	17.421M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.35M	17.421M
6195MHz	Pass	Inf	19.26M	17.511M
6415MHz	Pass	Inf	19.08M	17.451M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.35M	5.94471G	5.96406G	17.421M	5.945225G	5.962646G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	6.18474G	6.204G	17.511M	6.185255G	6.202766G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz

18/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.08M	6.40468G	6.42376G	17.451M	6.405225G	6.422676G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.32M	18.081M	18M1D1D	19.29M	18.021M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.32M	18.051M
6195MHz	Pass	Inf	19.29M	18.021M
6415MHz	Pass	Inf	19.29M	18.081M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

5955MHz

18/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.32M	5.94483G	5.96415G	18.051M	5.945405G	5.963456G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz

18/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.18483G	6.20412G	18.021M	6.185405G	6.203426G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz

18/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40483G	6.42412G	18.081M	6.405375G	6.423456G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.41M	18.111M	18M1D1D	19.32M	18.081M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.38M	18.111M
6195MHz	Pass	Inf	19.32M	18.081M
6415MHz	Pass	Inf	19.41M	18.081M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

5955MHz

18/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	5.94486G	5.96424G	18.111M	5.945405G	5.963516G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz


18/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.32M	6.18489G	6.20421G	18.081M	6.185405G	6.203486G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.41M	6.40483G	6.42424G	18.081M	6.405405G	6.423486G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.35M	17.511M	17M5D1D	19.08M	17.421M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.35M	17.421M
6195MHz	Pass	Inf	19.26M	17.511M
6415MHz	Pass	Inf	19.08M	17.451M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.35M	5.94471G	5.96406G	17.421M	5.945225G	5.962646G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	6.18474G	6.204G	17.511M	6.185255G	6.202766G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz

18/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.08M	6.40468G	6.42376G	17.451M	6.405225G	6.422676G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.32M	18.081M	18M1D1D	19.29M	18.021M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.32M	18.051M
6195MHz	Pass	Inf	19.29M	18.021M
6415MHz	Pass	Inf	19.29M	18.081M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.32M	5.94483G	5.96415G	18.051M	5.945405G	5.963456G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.18483G	6.20412G	18.021M	6.185405G	6.203426G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz

18/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40483G	6.42412G	18.081M	6.405375G	6.423456G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.41M	18.111M	18M1D1D	19.32M	18.081M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.38M	18.111M
6195MHz	Pass	Inf	19.32M	18.081M
6415MHz	Pass	Inf	19.41M	18.081M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	5.94486G	5.96424G	18.111M	5.945405G	5.963516G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.32M	6.18489G	6.20421G	18.081M	6.185405G	6.203486G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz

18/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.41M	6.40483G	6.42424G	18.081M	6.405405G	6.423486G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.35M	17.511M	17M5D1D	19.08M	17.421M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.35M	17.421M
6195MHz	Pass	Inf	19.26M	17.511M
6415MHz	Pass	Inf	19.08M	17.451M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.35M	5.94471G	5.96406G	17.421M	5.945225G	5.962646G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


6195MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	6.18474G	6.204G	17.511M	6.185255G	6.202766G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.08M	6.40468G	6.42376G	17.451M	6.405225G	6.422676G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.32M	18.081M	18M1D1D	19.29M	18.021M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.32M	18.051M
6195MHz	Pass	Inf	19.29M	18.021M
6415MHz	Pass	Inf	19.29M	18.081M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.32M	5.94483G	5.96415G	18.051M	5.945405G	5.963456G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.18483G	6.20412G	18.021M	6.185405G	6.203426G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz

18/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40483G	6.42412G	18.081M	6.405375G	6.423456G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	19.41M	18.111M	18M1D1D	19.32M	18.081M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-
5955MHz	Pass	Inf	19.38M	18.111M
6195MHz	Pass	Inf	19.32M	18.081M
6415MHz	Pass	Inf	19.41M	18.081M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_1TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	5.94486G	5.96424G	18.111M	5.945405G	5.963516G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX EBW

6195MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.32M	6.18489G	6.20421G	18.081M	6.185405G	6.203486G	Inf	1

802.11ax HEW20_Nss1,(MCS0)_1TX **EBW**

6415MHz

18/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.41M	6.40483G	6.42424G	18.081M	6.405405G	6.423486G	Inf	1

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.29M	17.331M	17M3D1D	19.02M	16.942M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.26M	17.331M	19.17M	17.061M
6195MHz	Pass	Inf	19.17M	17.151M	19.02M	16.942M
6415MHz	Pass	Inf	19.29M	17.241M	19.08M	17.271M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX EBW


5955MHz



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	5.94471G	5.96397G	17.331M	5.945255G	5.962586G	Inf	1
19.17M	5.94477G	5.96394G	17.061M	5.945285G	5.962346G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX EBW

6195MHz




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.17M	6.1848G	6.20397G	17.151M	6.185285G	6.202436G	Inf	1
19.02M	6.18474G	6.20376G	16.942M	6.185255G	6.202196G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40468G	6.42397G	17.241M	6.405255G	6.422496G	Inf	1
19.08M	6.40465G	6.42373G	17.271M	6.405255G	6.422526G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.29M	18.081M	18M1D1D	19.23M	18.021M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.26M	18.081M	19.23M	18.051M
6195MHz	Pass	Inf	19.26M	18.051M	19.23M	18.021M
6415MHz	Pass	Inf	19.29M	18.051M	19.26M	18.021M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX EBW

5955MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	5.94486G	5.96412G	18.081M	5.945405G	5.963486G	Inf	1
19.23M	5.94489G	5.96412G	18.051M	5.945405G	5.963456G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX EBW

6195MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	6.18486G	6.20412G	18.051M	6.185405G	6.203456G	Inf	1
19.23M	6.18486G	6.20409G	18.021M	6.185405G	6.203426G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40486G	6.42415G	18.051M	6.405405G	6.423456G	Inf	1
19.26M	6.40483G	6.42409G	18.021M	6.405405G	6.423426G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.38M	18.081M	18M1D1D	19.32M	18.051M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.35M	18.081M	19.32M	18.051M
6195MHz	Pass	Inf	19.38M	18.051M	19.35M	18.051M
6415MHz	Pass	Inf	19.38M	18.081M	19.32M	18.051M


Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX

EBW

5955MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.35M	5.94489G	5.96424G	18.081M	5.945435G	5.963516G	Inf	1
19.32M	5.94489G	5.96421G	18.051M	5.945435G	5.963486G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX

EBW

6195MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	6.18486G	6.20424G	18.051M	6.185435G	6.203486G	Inf	1
19.35M	6.18486G	6.20421G	18.051M	6.185435G	6.203486G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	6.40489G	6.42427G	18.081M	6.405435G	6.423516G	Inf	1
19.32M	6.40489G	6.42421G	18.051M	6.405435G	6.423486G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.29M	17.331M	17M3D1D	19.02M	16.942M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth


Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.26M	17.331M	19.17M	17.061M
6195MHz	Pass	Inf	19.17M	17.151M	19.02M	16.942M
6415MHz	Pass	Inf	19.29M	17.241M	19.08M	17.271M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX
EBW
5955MHz


21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	5.94471G	5.96397G	17.331M	5.945255G	5.962586G	Inf	1
19.17M	5.94477G	5.96394G	17.061M	5.945285G	5.962346G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX
EBW
6195MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.17M	6.1848G	6.20397G	17.151M	6.185285G	6.202436G	Inf	1
19.02M	6.18474G	6.20376G	16.942M	6.185255G	6.202196G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40468G	6.42397G	17.241M	6.405255G	6.422496G	Inf	1
19.08M	6.40465G	6.42373G	17.271M	6.405255G	6.422526G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.29M	18.081M	18M1D1D	19.23M	18.021M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.26M	18.081M	19.23M	18.051M
6195MHz	Pass	Inf	19.26M	18.051M	19.23M	18.021M
6415MHz	Pass	Inf	19.29M	18.051M	19.26M	18.021M


Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX

EBW

5955MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	5.94486G	5.96412G	18.081M	5.945405G	5.963486G	Inf	1
19.23M	5.94489G	5.96412G	18.051M	5.945405G	5.963456G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX

EBW

6195MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	6.18486G	6.20412G	18.051M	6.185405G	6.203456G	Inf	1
19.23M	6.18486G	6.20409G	18.021M	6.185405G	6.203426G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40486G	6.42415G	18.051M	6.405405G	6.423456G	Inf	1
19.26M	6.40483G	6.42409G	18.021M	6.405405G	6.423426G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.38M	18.081M	18M1D1D	19.32M	18.051M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.35M	18.081M	19.32M	18.051M
6195MHz	Pass	Inf	19.38M	18.051M	19.35M	18.051M
6415MHz	Pass	Inf	19.38M	18.081M	19.32M	18.051M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX EBW

5955MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.35M	5.94489G	5.96424G	18.081M	5.945435G	5.963516G	Inf	1
19.32M	5.94489G	5.96421G	18.051M	5.945435G	5.963486G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX EBW

6195MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	6.18486G	6.20424G	18.051M	6.185435G	6.203486G	Inf	1
19.35M	6.18486G	6.20421G	18.051M	6.185435G	6.203486G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	6.40489G	6.42427G	18.081M	6.405435G	6.423516G	Inf	1
19.32M	6.40489G	6.42421G	18.051M	6.405435G	6.423486G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.29M	17.331M	17M3D1D	19.02M	16.942M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.26M	17.331M	19.17M	17.061M
6195MHz	Pass	Inf	19.17M	17.151M	19.02M	16.942M
6415MHz	Pass	Inf	19.29M	17.241M	19.08M	17.271M


Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX

EBW

5955MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	5.94471G	5.96397G	17.331M	5.945255G	5.962586G	Inf	1
19.17M	5.94477G	5.96394G	17.061M	5.945285G	5.962346G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX

EBW

6195MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.17M	6.1848G	6.20397G	17.151M	6.185285G	6.202436G	Inf	1
19.02M	6.18474G	6.20376G	16.942M	6.185255G	6.202196G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40468G	6.42397G	17.241M	6.405255G	6.422496G	Inf	1
19.08M	6.40465G	6.42373G	17.271M	6.405255G	6.422526G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.29M	18.081M	18M1D1D	19.23M	18.021M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result

Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.26M	18.081M	19.23M	18.051M
6195MHz	Pass	Inf	19.26M	18.051M	19.23M	18.021M
6415MHz	Pass	Inf	19.29M	18.051M	19.26M	18.021M


Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX

EBW

5955MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	5.94486G	5.96412G	18.081M	5.945405G	5.963486G	Inf	1
19.23M	5.94489G	5.96412G	18.051M	5.945405G	5.963456G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX

EBW

6195MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.26M	6.18486G	6.20412G	18.051M	6.185405G	6.203456G	Inf	1
19.23M	6.18486G	6.20409G	18.021M	6.185405G	6.203426G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.29M	6.40486G	6.42415G	18.051M	6.405405G	6.423456G	Inf	1
19.26M	6.40483G	6.42409G	18.021M	6.405405G	6.423426G	Inf	2

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
5.925-6.425GHz	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	19.38M	18.081M	18M1D1D	19.32M	18.051M

Max-N dB = Maximum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Max-OBW = Maximum 99% occupied bandwidth;
Min-N dB = Minimum 6dB down bandwidth for 5.725-5.85GHz band / Maximum 26dB down bandwidth for other band;
Min-OBW = Minimum 99% occupied bandwidth

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)	Port 2-N dB (Hz)	Port 2-OBW (Hz)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-
5955MHz	Pass	Inf	19.35M	18.081M	19.32M	18.051M
6195MHz	Pass	Inf	19.38M	18.051M	19.35M	18.051M
6415MHz	Pass	Inf	19.38M	18.081M	19.32M	18.051M

Port X-N dB = Port X 6dB down bandwidth for 5.725-5.85GHz band / 26dB down bandwidth for other band
Port X-OBW = Port X 99% occupied bandwidth

802.11ax HEW20_Nss1,(MCS0)_2TX EBW

5955MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.35M	5.94489G	5.96424G	18.081M	5.945435G	5.963516G	Inf	1
19.32M	5.94489G	5.96421G	18.051M	5.945435G	5.963486G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX EBW

6195MHz

21/06/2022




26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	6.18486G	6.20424G	18.051M	6.185435G	6.203486G	Inf	1
19.35M	6.18486G	6.20421G	18.051M	6.185435G	6.203486G	Inf	2

802.11ax HEW20_Nss1,(MCS0)_2TX **EBW**

6415MHz

21/06/2022



26dB(Hz)	Fl-26dB(Hz)	Fh-26dB(Hz)	OBW(Hz)	Fl-OBW(Hz)	Fh-OBW(Hz)	Limit(Hz)	Port
19.38M	6.40489G	6.42427G	18.081M	6.405435G	6.423516G	Inf	1
19.32M	6.40489G	6.42421G	18.051M	6.405435G	6.423486G	Inf	2

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	7.28	0.00535	12.28	0.01690
802.11ax HEW40_Nss1,(MCS0)_1TX	10.25	0.01059	15.25	0.03350
802.11ax HEW80_Nss1,(MCS0)_1TX	12.85	0.01928	17.85	0.06095
802.11ax HEW160_Nss1,(MCS0)_1TX	15.35	0.03428	20.35	0.10839

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-
5955MHz	Pass	5.00	7.28	7.28	12.28	23.98
6195MHz	Pass	5.00	7.13	7.13	12.13	23.98
6415MHz	Pass	5.00	7.04	7.04	12.04	23.98
802.11ax HEW40_Nss1,(MCS0)_1TX	-	-	-	-	-	-
5965MHz	Pass	5.00	10.19	10.19	15.19	23.98
6205MHz	Pass	5.00	10.25	10.25	15.25	23.98
6405MHz	Pass	5.00	10.12	10.12	15.12	23.98
802.11ax HEW80_Nss1,(MCS0)_1TX	-	-	-	-	-	-
5985MHz	Pass	5.00	12.85	12.85	17.85	23.98
6225MHz	Pass	5.00	12.81	12.81	17.81	23.98
6385MHz	Pass	5.00	12.76	12.76	17.76	23.98
802.11ax HEW160_Nss1,(MCS0)_1TX	-	-	-	-	-	-
6025MHz	Pass	5.00	15.35	15.35	20.35	23.98
6185MHz	Pass	5.00	15.04	15.04	20.04	23.98
6345MHz	Pass	5.00	15.30	15.30	20.30	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	3.89	0.00245	8.89	0.00774
802.11ax HEW40_Nss1,(MCS0)_2TX	7.24	0.00530	12.24	0.01675
802.11ax HEW80_Nss1,(MCS0)_2TX	10.02	0.01005	15.02	0.03177
802.11ax HEW160_Nss1,(MCS0)_2TX	12.57	0.01807	17.57	0.05715

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	0.74	0.84	3.80	8.80	23.98
6195MHz	Pass	5.00	0.57	0.87	3.73	8.73	23.98
6415MHz	Pass	5.00	0.65	1.09	3.89	8.89	23.98
802.11ax HEW40_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5965MHz	Pass	5.00	4.31	4.14	7.24	12.24	23.98
6205MHz	Pass	5.00	4.17	4.1	7.15	12.15	23.98
6405MHz	Pass	5.00	4.21	4.16	7.20	12.20	23.98
802.11ax HEW80_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5985MHz	Pass	5.00	7.11	6.91	10.02	15.02	23.98
6225MHz	Pass	5.00	6.84	6.61	9.74	14.74	23.98
6385MHz	Pass	5.00	6.97	6.82	9.91	14.91	23.98
802.11ax HEW160_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
6025MHz	Pass	5.00	9.64	9.48	12.57	17.57	23.98
6185MHz	Pass	5.00	9.06	8.94	12.01	17.01	23.98
6345MHz	Pass	5.00	9.35	9.06	12.22	17.22	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	3.89	0.00245	11.90	0.01549
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	7.24	0.00530	15.25	0.03350
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	10.02	0.01005	18.03	0.06353
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	12.57	0.01807	20.58	0.11429

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5955MHz	Pass	8.01	0.74	0.84	3.80	11.81	23.98
6195MHz	Pass	8.01	0.57	0.87	3.73	11.74	23.98
6415MHz	Pass	8.01	0.65	1.09	3.89	11.90	23.98
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5965MHz	Pass	8.01	4.31	4.14	7.24	15.25	23.98
6205MHz	Pass	8.01	4.17	4.10	7.15	15.16	23.98
6405MHz	Pass	8.01	4.21	4.16	7.20	15.21	23.98
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5985MHz	Pass	8.01	7.11	6.91	10.02	18.03	23.98
6225MHz	Pass	8.01	6.84	6.61	9.74	17.75	23.98
6385MHz	Pass	8.01	6.97	6.82	9.91	17.92	23.98
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
6025MHz	Pass	8.01	9.64	9.48	12.57	20.58	23.98
6185MHz	Pass	8.01	9.06	8.94	12.01	20.02	23.98
6345MHz	Pass	8.01	9.35	9.06	12.22	20.23	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-2.22	0.00060	2.78	0.00190

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-
5955MHz	Pass	5.00	-2.22	-2.22	2.78	23.98
6195MHz	Pass	5.00	-2.61	-2.61	2.39	23.98
6415MHz	Pass	5.00	-2.25	-2.25	2.75	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	0.95	0.00124	5.95	0.00394

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-
5955MHz	Pass	5.00	0.95	0.95	5.95	23.98
6195MHz	Pass	5.00	0.65	0.65	5.65	23.98
6415MHz	Pass	5.00	0.82	0.82	5.82	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	3.63	0.00231	8.63	0.00729

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-
5955MHz	Pass	5.00	3.63	3.63	8.63	23.98
6195MHz	Pass	5.00	3.56	3.56	8.56	23.98
6415MHz	Pass	5.00	3.55	3.55	8.55	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-5.02	0.00031	-0.02	0.00100

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-8.47	-8.12	-5.28	-0.28	23.98
6195MHz	Pass	5.00	-8.38	-8.26	-5.31	-0.31	23.98
6415MHz	Pass	5.00	-8.28	-7.79	-5.02	-0.02	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-1.99	0.00063	3.01	0.00200

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-5.15	-4.85	-1.99	3.01	23.98
6195MHz	Pass	5.00	-5.26	-4.87	-2.05	2.95	23.98
6415MHz	Pass	5.00	-5.08	-4.99	-2.02	2.98	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	Total Power (dBm)	Total Power (W)	EIRP (dBm)	EIRP (W)
5.925-6.425GHz	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	0.70	0.00117	5.70	0.00372

Result

Mode	Result	DG (dBi)	Port 1 (dBm)	Port 2 (dBm)	Total Power (dBm)	EIRP (dBm)	EIRP Limit (dBm)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-2.46	-2.17	0.70	5.70	23.98
6195MHz	Pass	5.00	-2.21	-2.44	0.69	5.69	23.98
6415MHz	Pass	5.00	-2.48	-2.44	0.55	5.55	23.98

DG = Directional Gain; Port X = Port X output power

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-5.93	-1.07
802.11ax HEW40_Nss1,(MCS0)_1TX	-5.91	-1.05
802.11ax HEW80_Nss1,(MCS0)_1TX	-5.89	-1.03
802.11ax HEW160_Nss1,(MCS0)_1TX	-6.03	-1.17

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	4.86	-6.06	-6.06	Inf	-1.20	-1.00
6195MHz	Pass	4.86	-5.93	-5.93	Inf	-1.07	-1.00
6415MHz	Pass	4.86	-5.95	-5.95	Inf	-1.09	-1.00
802.11ax HEW40_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5965MHz	Pass	4.86	-6.12	-6.12	Inf	-1.26	-1.00
6205MHz	Pass	4.86	-6.07	-6.07	Inf	-1.21	-1.00
6405MHz	Pass	4.86	-5.91	-5.91	Inf	-1.05	-1.00
802.11ax HEW80_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5985MHz	Pass	4.86	-6.09	-6.09	Inf	-1.23	-1.00
6225MHz	Pass	4.86	-5.89	-5.89	Inf	-1.03	-1.00
6385MHz	Pass	4.86	-5.93	-5.93	Inf	-1.07	-1.00
802.11ax HEW160_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
6025MHz	Pass	4.86	-6.06	-6.06	Inf	-1.20	-1.00
6185MHz	Pass	4.86	-6.03	-6.03	Inf	-1.17	-1.00
6345MHz	Pass	4.86	-6.08	-6.08	Inf	-1.22	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.06	-6.06	-6.06

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-5.93	-5.93	-5.93

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


6415MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-5.95	-5.95	-5.95

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


5965MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.12	-6.12	-6.12

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


6205MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.07	-6.07	-6.07

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


6405MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-5.91	-5.91	-5.91

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


5985MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.09	-6.09	-6.09

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


6225MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-5.89	-5.89	-5.89

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


6385MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-5.93	-5.93	-5.93

802.11ax HEW160_Nss1,(MCS0)_1TX PSD


6025MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.06	-6.06	-6.06

802.11ax HEW160_Nss1,(MCS0)_1TX PSD


6185MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.03	-6.03	-6.03

802.11ax HEW160_Nss1,(MCS0)_1TX PSD

6345MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.08	-6.08	-6.08

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.06	-1.06
802.11ax HEW40_Nss1,(MCS0)_1TX	-6.07	-1.07
802.11ax HEW80_Nss1,(MCS0)_1TX	-6.09	-1.09
802.11ax HEW160_Nss1,(MCS0)_1TX	-6.03	-1.03

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-6.06	-6.06	Inf	-1.06	-1.00
6195MHz	Pass	5.00	-6.18	-6.18	Inf	-1.18	-1.00
6415MHz	Pass	5.00	-6.21	-6.21	Inf	-1.21	-1.00
802.11ax HEW40_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5965MHz	Pass	5.00	-6.12	-6.12	Inf	-1.12	-1.00
6205MHz	Pass	5.00	-6.07	-6.07	Inf	-1.07	-1.00
6405MHz	Pass	5.00	-6.18	-6.18	Inf	-1.18	-1.00
802.11ax HEW80_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5985MHz	Pass	5.00	-6.09	-6.09	Inf	-1.09	-1.00
6225MHz	Pass	5.00	-6.19	-6.19	Inf	-1.19	-1.00
6385MHz	Pass	5.00	-6.15	-6.15	Inf	-1.15	-1.00
802.11ax HEW160_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
6025MHz	Pass	5.00	-6.06	-6.06	Inf	-1.06	-1.00
6185MHz	Pass	5.00	-6.03	-6.03	Inf	-1.03	-1.00
6345MHz	Pass	5.00	-6.08	-6.08	Inf	-1.08	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.06	-6.06	-6.06

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.18	-6.18	-6.18

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


6415MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.21	-6.21	-6.21

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


5965MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.12	-6.12	-6.12

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


6205MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.07	-6.07	-6.07

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


6405MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.18	-6.18	-6.18

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


5985MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.09	-6.09	-6.09

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


6225MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.19	-6.19	-6.19

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


6385MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.15	-6.15	-6.15

802.11ax HEW160_Nss1,(MCS0)_1TX PSD


6025MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.06	-6.06	-6.06

802.11ax HEW160_Nss1,(MCS0)_1TX PSD


6185MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.03	-6.03	-6.03

802.11ax HEW160_Nss1,(MCS0)_1TX PSD

6345MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.08	-6.08	-6.08

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.06	-1.06
802.11ax HEW40_Nss1,(MCS0)_1TX	-6.07	-1.07
802.11ax HEW80_Nss1,(MCS0)_1TX	-6.09	-1.09
802.11ax HEW160_Nss1,(MCS0)_1TX	-6.03	-1.03

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-6.06	-6.06	Inf	-1.06	-1.00
6195MHz	Pass	5.00	-6.18	-6.18	Inf	-1.18	-1.00
6415MHz	Pass	5.00	-6.21	-6.21	Inf	-1.21	-1.00
802.11ax HEW40_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5965MHz	Pass	5.00	-6.12	-6.12	Inf	-1.12	-1.00
6205MHz	Pass	5.00	-6.07	-6.07	Inf	-1.07	-1.00
6405MHz	Pass	5.00	-6.18	-6.18	Inf	-1.18	-1.00
802.11ax HEW80_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5985MHz	Pass	5.00	-6.09	-6.09	Inf	-1.09	-1.00
6225MHz	Pass	5.00	-6.19	-6.19	Inf	-1.19	-1.00
6385MHz	Pass	5.00	-6.15	-6.15	Inf	-1.15	-1.00
802.11ax HEW160_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
6025MHz	Pass	5.00	-6.06	-6.06	Inf	-1.06	-1.00
6185MHz	Pass	5.00	-6.03	-6.03	Inf	-1.03	-1.00
6345MHz	Pass	5.00	-6.08	-6.08	Inf	-1.08	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.06	-6.06	-6.06

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.18	-6.18	-6.18

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


6415MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.21	-6.21	-6.21

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


5965MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.12	-6.12	-6.12

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


6205MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.07	-6.07	-6.07

802.11ax HEW40_Nss1,(MCS0)_1TX PSD


6405MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.18	-6.18	-6.18

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


5985MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.09	-6.09	-6.09

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


6225MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.19	-6.19	-6.19

802.11ax HEW80_Nss1,(MCS0)_1TX PSD


6385MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.15	-6.15	-6.15

802.11ax HEW160_Nss1,(MCS0)_1TX PSD


6025MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.06	-6.06	-6.06

802.11ax HEW160_Nss1,(MCS0)_1TX PSD


6185MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.03	-6.03	-6.03

802.11ax HEW160_Nss1,(MCS0)_1TX PSD

6345MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.08	-6.08	-6.08

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-8.91	-1.04
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-8.92	-1.05
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-8.99	-1.12
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-9.05	-1.18

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	7.87	-12.25	-11.56	-8.91	Inf	-1.04	-1.00
6195MHz	Pass	7.87	-12.16	-11.87	-9.02	Inf	-1.15	-1.00
6415MHz	Pass	7.87	-12.00	-11.80	-8.95	Inf	-1.08	-1.00
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5965MHz	Pass	7.87	-12.04	-12.22	-9.12	Inf	-1.25	-1.00
6205MHz	Pass	7.87	-12.11	-11.76	-8.92	Inf	-1.05	-1.00
6405MHz	Pass	7.87	-11.98	-12.01	-9.04	Inf	-1.17	-1.00
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5985MHz	Pass	7.87	-11.94	-12.36	-9.13	Inf	-1.26	-1.00
6225MHz	Pass	7.87	-11.89	-12.06	-8.99	Inf	-1.12	-1.00
6385MHz	Pass	7.87	-11.96	-11.98	-9.03	Inf	-1.16	-1.00
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
6025MHz	Pass	7.87	-12.08	-12.14	-9.12	Inf	-1.25	-1.00
6185MHz	Pass	7.87	-12.12	-12.05	-9.07	Inf	-1.20	-1.00
6345MHz	Pass	7.87	-11.86	-12.20	-9.05	Inf	-1.18	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


5955MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-8.91	-8.91	-12.25	-11.56

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.02	-9.02	-12.16	-11.87

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


6415MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-8.95	-8.95	-12.00	-11.80

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


5965MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.04	-12.22

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


6205MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-8.92	-8.92	-12.11	-11.76

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


6405MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-11.98	-12.01

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


5985MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.13	-9.13	-11.94	-12.36

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


6225MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-8.99	-8.99	-11.89	-12.06

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


6385MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.03	-9.03	-11.96	-11.98

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD


6025MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.08	-12.14

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD


6185MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.07	-9.07	-12.12	-12.05

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD

6345MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.05	-9.05	-11.86	-12.20

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-9.15	-1.14
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-9.04	-1.03
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-9.03	-1.02
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-9.05	-1.04

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	8.01	-12.28	-12.18	-9.23	Inf	-1.22	-1.00
6195MHz	Pass	8.01	-12.55	-11.94	-9.25	Inf	-1.24	-1.00
6415MHz	Pass	8.01	-12.47	-11.86	-9.15	Inf	-1.14	-1.00
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5965MHz	Pass	8.01	-12.04	-12.22	-9.12	Inf	-1.11	-1.00
6205MHz	Pass	8.01	-12.13	-12.25	-9.23	Inf	-1.22	-1.00
6405MHz	Pass	8.01	-11.98	-12.01	-9.04	Inf	-1.03	-1.00
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5985MHz	Pass	8.01	-11.94	-12.36	-9.13	Inf	-1.12	-1.00
6225MHz	Pass	8.01	-12.17	-12.24	-9.24	Inf	-1.23	-1.00
6385MHz	Pass	8.01	-11.96	-11.98	-9.03	Inf	-1.02	-1.00
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
6025MHz	Pass	8.01	-12.08	-12.14	-9.12	Inf	-1.11	-1.00
6185MHz	Pass	8.01	-12.12	-12.05	-9.07	Inf	-1.06	-1.00
6345MHz	Pass	8.01	-11.86	-12.20	-9.05	Inf	-1.04	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


5955MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.23	-9.23	-12.28	-12.18

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.25	-9.25	-12.55	-11.94

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


6415MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.15	-9.15	-12.47	-11.86

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


5965MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.04	-12.22

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


6205MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.23	-9.23	-12.13	-12.25

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


6405MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-11.98	-12.01

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


5985MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.13	-9.13	-11.94	-12.36

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


6225MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.24	-9.24	-12.17	-12.24

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


6385MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.03	-9.03	-11.96	-11.98

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD


6025MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.08	-12.14

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD


6185MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.07	-9.07	-12.12	-12.05

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD

6345MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.05	-9.05	-11.86	-12.20

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-9.15	-1.14
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-9.04	-1.03
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-9.03	-1.02
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-9.05	-1.04

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	8.01	-12.28	-12.18	-9.23	Inf	-1.22	-1.00
6195MHz	Pass	8.01	-12.55	-11.94	-9.25	Inf	-1.24	-1.00
6415MHz	Pass	8.01	-12.47	-11.86	-9.15	Inf	-1.14	-1.00
802.11ax HEW40-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5965MHz	Pass	8.01	-12.04	-12.22	-9.12	Inf	-1.11	-1.00
6205MHz	Pass	8.01	-12.13	-12.25	-9.23	Inf	-1.22	-1.00
6405MHz	Pass	8.01	-11.98	-12.01	-9.04	Inf	-1.03	-1.00
802.11ax HEW80-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5985MHz	Pass	8.01	-11.94	-12.36	-9.13	Inf	-1.12	-1.00
6225MHz	Pass	8.01	-12.17	-12.24	-9.24	Inf	-1.23	-1.00
6385MHz	Pass	8.01	-11.96	-11.98	-9.03	Inf	-1.02	-1.00
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
6025MHz	Pass	8.01	-12.08	-12.14	-9.12	Inf	-1.11	-1.00
6185MHz	Pass	8.01	-12.12	-12.05	-9.07	Inf	-1.06	-1.00
6345MHz	Pass	8.01	-11.86	-12.20	-9.05	Inf	-1.04	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


5955MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.23	-9.23	-12.28	-12.18

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.25	-9.25	-12.55	-11.94

802.11ax HEW20-BF_Nss1,(MCS0)_2TX PSD


6415MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.15	-9.15	-12.47	-11.86

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


5965MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.04	-12.22

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


6205MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.23	-9.23	-12.13	-12.25

802.11ax HEW40-BF_Nss1,(MCS0)_2TX PSD


6405MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-11.98	-12.01

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


5985MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.13	-9.13	-11.94	-12.36

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


6225MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.24	-9.24	-12.17	-12.24

802.11ax HEW80-BF_Nss1,(MCS0)_2TX PSD


6385MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.03	-9.03	-11.96	-11.98

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD


6025MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.08	-12.14

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD


6185MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.07	-9.07	-12.12	-12.05

802.11ax HEW160-BF_Nss1,(MCS0)_2TX PSD

6345MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.05	-9.05	-11.86	-12.20

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.03	-1.17

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	4.86	-6.14	-6.14	Inf	-1.28	-1.00
6195MHz	Pass	4.86	-6.13	-6.13	Inf	-1.27	-1.00
6415MHz	Pass	4.86	-6.03	-6.03	Inf	-1.17	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.14	-6.14	-6.14

802.11ax HEW20_Nss1,(MCS0)_1TX PSD

6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.13	-6.13	-6.13


802.11ax HEW20_Nss1,(MCS0)_1TX
PSD
6415MHz
18/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
Port 1
0
-10
-20
-30
-40
-50
-60
-70
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
PD
Port 1
(dBm/RBW)
(dBm/RBW)
(dBm/RBW)
-6.03
-6.03
-6.03

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.02	-1.16

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	4.86	-6.03	-6.03	Inf	-1.17	-1.00
6195MHz	Pass	4.86	-6.08	-6.08	Inf	-1.22	-1.00
6415MHz	Pass	4.86	-6.02	-6.02	Inf	-1.16	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.03	-6.03	-6.03

802.11ax HEW20_Nss1,(MCS0)_1TX PSD

6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.08	-6.08	-6.08


802.11ax HEW20_Nss1,(MCS0)_1TX
PSD
6415MHz
18/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
Port 1
0
-5
-10
-15
-20
-25
-30
-35
-40
-45
-50
-55
-60
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
PD
Port 1
(dBm/RBW)
(dBm/RBW)
(dBm/RBW)
-6.02
-6.02
-6.02

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.05	-1.19

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	4.86	-6.14	-6.14	Inf	-1.28	-1.00
6195MHz	Pass	4.86	-6.05	-6.05	Inf	-1.19	-1.00
6415MHz	Pass	4.86	-6.09	-6.09	Inf	-1.23	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.14	-6.14	-6.14

802.11ax HEW20_Nss1,(MCS0)_1TX PSD

6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.05	-6.05	-6.05


802.11ax HEW20_Nss1,(MCS0)_1TX
PSD
6415MHz
18/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
Port 1
0
-5
-10
-15
-20
-25
-30
-35
-40
-45
-50
-55
-60
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
PD
Port 1
(dBm/RBW)
(dBm/RBW)
(dBm/RBW)
-6.09
-6.09
-6.09

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.03	-1.03

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-6.14	-6.14	Inf	-1.14	-1.00
6195MHz	Pass	5.00	-6.13	-6.13	Inf	-1.13	-1.00
6415MHz	Pass	5.00	-6.03	-6.03	Inf	-1.03	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.14	-6.14	-6.14

802.11ax HEW20_Nss1,(MCS0)_1TX PSD

6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.13	-6.13	-6.13


802.11ax HEW20_Nss1,(MCS0)_1TX
PSD
6415MHz
18/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
Port 1
0
-10
-20
-30
-40
-50
-60
-70
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
PD
Port 1
(dBm/RBW)
(dBm/RBW)
(dBm/RBW)
-6.03
-6.03
-6.03

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.02	-1.02

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-6.03	-6.03	Inf	-1.03	-1.00
6195MHz	Pass	5.00	-6.08	-6.08	Inf	-1.08	-1.00
6415MHz	Pass	5.00	-6.02	-6.02	Inf	-1.02	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.03	-6.03	-6.03

802.11ax HEW20_Nss1,(MCS0)_1TX PSD

6195MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.08	-6.08	-6.08

802.11ax HEW20_Nss1,(MCS0)_1TX **PSD**

6415MHz

18/06/2022



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.02	-6.02	-6.02

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.05	-1.05

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-6.14	-6.14	Inf	-1.14	-1.00
6195MHz	Pass	5.00	-6.05	-6.05	Inf	-1.05	-1.00
6415MHz	Pass	5.00	-6.09	-6.09	Inf	-1.09	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.14	-6.14	-6.14

802.11ax HEW20_Nss1,(MCS0)_1TX PSD

6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.05	-6.05	-6.05


802.11ax HEW20_Nss1,(MCS0)_1TX
PSD
6415MHz
18/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
Port 1
0
-5
-10
-15
-20
-25
-30
-35
-40
-45
-50
-55
-60
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
PD
Port 1
(dBm/RBW)
(dBm/RBW)
(dBm/RBW)
-6.09
-6.09
-6.09

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.03	-1.03

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-6.14	-6.14	Inf	-1.14	-1.00
6195MHz	Pass	5.00	-6.13	-6.13	Inf	-1.13	-1.00
6415MHz	Pass	5.00	-6.03	-6.03	Inf	-1.03	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.14	-6.14	-6.14

802.11ax HEW20_Nss1,(MCS0)_1TX PSD

6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.13	-6.13	-6.13


802.11ax HEW20_Nss1,(MCS0)_1TX
PSD
6415MHz
18/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
Port 1
0
-10
-20
-30
-40
-50
-60
-70
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
PD
Port 1
(dBm/RBW)
(dBm/RBW)
(dBm/RBW)
-6.03
-6.03
-6.03

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.02	-1.02

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;

Result


Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-6.03	-6.03	Inf	-1.03	-1.00
6195MHz	Pass	5.00	-6.08	-6.08	Inf	-1.08	-1.00
6415MHz	Pass	5.00	-6.02	-6.02	Inf	-1.02	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX

PSD

5955MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.03	-6.03	-6.03


802.11ax HEW20_Nss1,(MCS0)_1TX

PSD

6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.08	-6.08	-6.08


802.11ax HEW20_Nss1,(MCS0)_1TX
PSD
6415MHz
18/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
Port 1
0
-5
-10
-15
-20
-25
-30
-35
-40
-45
-50
-55
-60
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
PD
Port 1
(dBm/RBW)
(dBm/RBW)
(dBm/RBW)
-6.02
-6.02
-6.02

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	-6.05	-1.05

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_1TX	-	-	-	-	-	-	-
5955MHz	Pass	5.00	-6.14	-6.14	Inf	-1.14	-1.00
6195MHz	Pass	5.00	-6.05	-6.05	Inf	-1.05	-1.00
6415MHz	Pass	5.00	-6.09	-6.09	Inf	-1.09	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_1TX PSD


5955MHz




Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.14	-6.14	-6.14

802.11ax HEW20_Nss1,(MCS0)_1TX PSD

6195MHz



Sum	PD	Port 1
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-6.05	-6.05	-6.05


802.11ax HEW20_Nss1,(MCS0)_1TX
PSD
6415MHz
18/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
Port 1
0
-5
-10
-15
-20
-25
-30
-35
-40
-45
-50
-55
-60
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
PD
Port 1
(dBm/RBW)
(dBm/RBW)
(dBm/RBW)
-6.09
-6.09
-6.09

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-9.06	-1.19

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;

Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	7.87	-12.49	-11.79	-9.12	Inf	-1.25	-1.00
6195MHz	Pass	7.87	-12.24	-12.02	-9.15	Inf	-1.28	-1.00
6415MHz	Pass	7.87	-12.27	-11.81	-9.06	Inf	-1.19	-1.00


DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX

PSD

5955MHz

21/06/2022




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.49	-11.79

802.11ax HEW20_Nss1,(MCS0)_2TX

PSD

6195MHz


21/06/2022



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.15	-9.15	-12.24	-12.02

802.11ax HEW20_Nss1,(MCS0)_2TX **PSD**

6415MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.06	-9.06	-12.27	-11.81

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-9.04	-1.17

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	7.87	-12.30	-12.00	-9.14	Inf	-1.27	-1.00
6195MHz	Pass	7.87	-12.20	-11.72	-9.04	Inf	-1.17	-1.00
6415MHz	Pass	7.87	-12.20	-11.74	-9.10	Inf	-1.23	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX PSD


5955MHz




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.14	-9.14	-12.30	-12.00

802.11ax HEW20_Nss1,(MCS0)_2TX PSD

6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-12.20	-11.72



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.10	-9.10	-12.20	-11.74

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-8.88	-1.01

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	7.87	-12.32	-11.97	-9.13	Inf	-1.26	-1.00
6195MHz	Pass	7.87	-11.95	-12.10	-9.04	Inf	-1.17	-1.00
6415MHz	Pass	7.87	-11.64	-11.92	-8.88	Inf	-1.01	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX PSD


5955MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.13	-9.13	-12.32	-11.97

802.11ax HEW20_Nss1,(MCS0)_2TX PSD


6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-11.95	-12.10

802.11ax HEW20_Nss1,(MCS0)_2TX **PSD**

6415MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-8.88	-8.88	-11.64	-11.92

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-9.06	-1.05

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;

Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	8.01	-12.49	-11.79	-9.12	Inf	-1.11	-1.00
6195MHz	Pass	8.01	-12.24	-12.02	-9.15	Inf	-1.14	-1.00
6415MHz	Pass	8.01	-12.27	-11.81	-9.06	Inf	-1.05	-1.00


DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX

PSD

5955MHz

21/06/2022




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.49	-11.79

802.11ax HEW20_Nss1,(MCS0)_2TX

PSD

6195MHz


21/06/2022



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.15	-9.15	-12.24	-12.02

802.11ax HEW20_Nss1,(MCS0)_2TX **PSD**

6415MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.06	-9.06	-12.27	-11.81

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-9.04	-1.03

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	8.01	-12.30	-12.00	-9.14	Inf	-1.13	-1.00
6195MHz	Pass	8.01	-12.20	-11.72	-9.04	Inf	-1.03	-1.00
6415MHz	Pass	8.01	-12.20	-11.74	-9.10	Inf	-1.09	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX PSD


5955MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.14	-9.14	-12.30	-12.00

802.11ax HEW20_Nss1,(MCS0)_2TX PSD


6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-12.20	-11.72

802.11ax HEW20_Nss1,(MCS0)_2TX **PSD**

6415MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.10	-9.10	-12.20	-11.74

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-9.04	-1.03

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	8.01	-12.32	-11.97	-9.13	Inf	-1.12	-1.00
6195MHz	Pass	8.01	-11.95	-12.10	-9.04	Inf	-1.03	-1.00
6415MHz	Pass	8.01	-12.11	-12.13	-9.16	Inf	-1.15	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX PSD


5955MHz




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.13	-9.13	-12.32	-11.97

802.11ax HEW20_Nss1,(MCS0)_2TX PSD

6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-11.95	-12.10



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.16	-9.16	-12.11	-12.13

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-9.06	-1.05

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;

Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	8.01	-12.49	-11.79	-9.12	Inf	-1.11	-1.00
6195MHz	Pass	8.01	-12.24	-12.02	-9.15	Inf	-1.14	-1.00
6415MHz	Pass	8.01	-12.27	-11.81	-9.06	Inf	-1.05	-1.00


DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX

PSD

5955MHz

21/06/2022




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.12	-9.12	-12.49	-11.79

802.11ax HEW20_Nss1,(MCS0)_2TX

PSD

6195MHz


21/06/2022



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.15	-9.15	-12.24	-12.02

802.11ax HEW20_Nss1,(MCS0)_2TX **PSD**

6415MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.06	-9.06	-12.27	-11.81

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-9.04	-1.03

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	8.01	-12.30	-12.00	-9.14	Inf	-1.13	-1.00
6195MHz	Pass	8.01	-12.20	-11.72	-9.04	Inf	-1.03	-1.00
6415MHz	Pass	8.01	-12.20	-11.74	-9.10	Inf	-1.09	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX PSD


5955MHz




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.14	-9.14	-12.30	-12.00

802.11ax HEW20_Nss1,(MCS0)_2TX PSD

6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-12.20	-11.72


802.11ax HEW20_Nss1,(MCS0)_2TX
PSD
6415MHz
21/06/2022
CF
6.415GHz
Span
30MHz
RBW
1MHz
VBW
3MHz
Sweep Time
20ms
Detector Type
RMS
0
-5
-10
-15
-20
-25
-30
-35
-40
-45
-50
-55
-60
6.4G
6.402G
6.404G
6.406G
6.408G
6.41G
6.412G
6.414G
6.416G
6.418G
6.42G
6.422G
6.424G
6.426G
6.428G
6.43G
Sum
Port 1
Port 2
Sum (dBm/RBW) -9.10
PD (dBm/RBW) -9.10
Port 1 (dBm/RBW) -12.20
Port 2 (dBm/RBW) -11.74

Summary

Mode	PD (dBm/RBW)	EIRP PD (dBm/RBW)
5.925-6.425GHz	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	-9.04	-1.03

RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;


Result

Mode	Result	DG (dBi)	Port 1 (dBm/RBW)	Port 2 (dBm/RBW)	PD (dBm/RBW)	PD Limit (dBm/RBW)	EIRP PD (dBm/RBW)	EIRP PD Limit (dBm/RBW)
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-	-
5955MHz	Pass	8.01	-12.32	-11.97	-9.13	Inf	-1.12	-1.00
6195MHz	Pass	8.01	-11.95	-12.10	-9.04	Inf	-1.03	-1.00
6415MHz	Pass	8.01	-12.11	-12.13	-9.16	Inf	-1.15	-1.00

DG = Directional Gain; RBW = 500kHz for 5.725-5.85GHz band / 1MHz for other band;
PD = trace bin-by-bin of each transmits port summing can be performed maximum power density; Port X = Port X Power Density;

802.11ax HEW20_Nss1,(MCS0)_2TX PSD


5955MHz




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.13	-9.13	-12.32	-11.97

802.11ax HEW20_Nss1,(MCS0)_2TX PSD

6195MHz



Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.04	-9.04	-11.95	-12.10




Sum	PD	Port 1	Port 2
(dBm/RBW)	(dBm/RBW)	(dBm/RBW)	(dBm/RBW)
-9.16	-9.16	-12.11	-12.13

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 3	Pass	PK	60.01M	35.92	40.00	-4.08	Vertical

Mode 3


18/05/2022



Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comment	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
PK	30.85M	35.61	40.00	-4.39	-13.16	3	Vertical	55	1.00	-	48.77	14.00	0.73	27.89
PK	60.01M	35.92	40.00	-4.08	-16.67	3	Vertical	193	1.00	"Worst"	52.59	9.80	1.30	27.77
PK	99.62M	33.36	43.50	-10.14	-16.35	3	Vertical	79	1.00	-	49.71	9.56	1.90	27.81
PK	115.6M	31.39	43.50	-12.11	-15.05	3	Vertical	190	2.00	-	46.44	10.50	2.13	27.68
PK	366.4M	35.26	46.00	-10.74	-7.69	3	Vertical	4	2.00	-	42.95	15.38	3.97	27.04
PK	399.6M	33.01	46.00	-12.99	-7.02	3	Vertical	38	2.00	-	40.03	16.22	4.10	27.34

Mode 3

18/05/2022




Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comment	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB)	(m)		(°)	(m)		(dBuV)	(dB)	(dB)	(dB)
PK	100.04M	31.53	43.50	-11.97	-16.31	3	Horizontal	133	1.00	"Worst"	47.84	9.60	1.90	27.81
PK	199.92M	27.68	43.50	-15.82	-9.56	3	Horizontal	229	3.00	-	37.24	14.51	3.20	27.27
PK	299.6M	28.37	46.00	-17.63	-9.67	3	Horizontal	286	1.00	-	38.04	13.20	3.50	26.37
PK	366.4M	32.51	46.00	-13.49	-7.69	3	Horizontal	214	2.00	-	40.20	15.38	3.97	27.04
PK	399.6M	31.24	46.00	-14.76	-7.02	3	Horizontal	11	1.00	-	38.26	16.22	4.10	27.34
PK	499.6M	31.66	46.00	-14.34	-5.79	3	Horizontal	15	1.00	-	37.45	17.51	4.60	27.90

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.90748G	53.94	54.00	-0.06	3	Horizontal	207	1.80	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 17.25
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9202G	63.78	88.20	-24.42	55.01	3	Vertical	45	1.34	-	34.98	6.60	32.81
RMS	5.925G	52.24	68.20	-15.96	43.45	3	Vertical	45	1.34	-	35.00	6.60	32.81
PK	5.9546G	114.30	Inf	-Inf	105.40	3	Vertical	45	1.34	-	35.12	6.60	32.82
RMS	5.9578G	103.83	Inf	-Inf	94.92	3	Vertical	45	1.34	-	35.13	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 17.25
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9246G	62.94	88.20	-25.26	54.15	3	Horizontal	0	2.30	-	35.00	6.60	32.81
RMS	5.925G	51.66	68.20	-16.54	42.87	3	Horizontal	0	2.30	-	35.00	6.60	32.81
PK	5.9546G	111.77	Inf	-Inf	102.87	3	Horizontal	0	2.30	-	35.12	6.60	32.82
RMS	5.9578G	101.37	Inf	-Inf	92.46	3	Horizontal	0	2.30	-	35.13	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.90424G	59.34	74.00	-14.66	43.44	3	Vertical	3	1.80	-	38.50	8.98	31.58
AV	11.90712G	47.24	54.00	-6.76	31.34	3	Vertical	3	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.91348G	66.39	74.00	-7.61	50.48	3	Horizontal	207	1.80	-	38.50	8.98	31.57
AV	11.90748G	53.94	54.00	-0.06	38.04	3	Horizontal	207	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-C-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9142G	58.33	88.20	-29.87	51.72	3	Vertical	219	1.76	-	34.66	7.51	35.56
RMS	5.925G	47.05	68.20	-21.15	40.38	3	Vertical	219	1.76	-	34.70	7.53	35.56
PK	6.195G	113.62	Inf	-Inf	106.26	3	Vertical	219	1.76	-	35.18	7.70	35.52
RMS	6.1938G	103.58	Inf	-Inf	96.22	3	Vertical	219	1.76	-	35.18	7.70	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-C-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9094G	57.84	88.20	-30.36	51.24	3	Horizontal	8	1.90	-	34.64	7.51	35.55
RMS	5.925G	47.05	68.20	-21.15	40.38	3	Horizontal	8	1.90	-	34.70	7.53	35.56
PK	6.195G	111.45	Inf	-Inf	104.09	3	Horizontal	8	1.90	-	35.18	7.70	35.52
RMS	6.1962G	101.61	Inf	-Inf	94.25	3	Horizontal	8	1.90	-	35.18	7.70	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3836G	56.88	74.00	-17.12	42.30	3	Vertical	234	1.80	-	38.88	11.11	35.41
AV	12.3895G	43.41	54.00	-10.59	28.82	3	Vertical	234	1.80	-	38.89	11.11	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39162G	64.06	74.00	-9.94	49.47	3	Horizontal	210	1.80	-	38.89	11.11	35.41
AV	12.38742G	50.36	54.00	-3.64	35.77	3	Horizontal	210	1.80	-	38.89	11.11	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59982G	45.57	83.54	-37.97	42.87	1	Vertical	189	2.22	-	37.76	14.94	50.00
AV	18.58998G	31.54	63.54	-32.00	28.85	1	Vertical	189	2.22	-	37.76	14.94	50.01

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.57372G	45.13	83.54	-38.41	42.46	1	Horizontal	256	1.27	-	37.77	14.93	50.03
AV	18.58242G	31.50	63.54	-32.04	28.82	1	Horizontal	256	1.27	-	37.77	14.93	50.02

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-C-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	59.33	88.20	-28.87	52.68	3	Vertical	321	2.10	-	34.69	7.52	35.56
RMS	5.925G	47.00	68.20	-21.20	40.34	3	Vertical	321	2.10	-	34.70	7.52	35.56
PK	6.415G	112.39	Inf	-Inf	105.25	3	Vertical	321	2.10	-	34.84	7.73	35.43
RMS	6.415G	102.43	Inf	-Inf	95.29	3	Vertical	321	2.10	-	34.84	7.73	35.43

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-C-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8678G	57.44	88.20	-30.76	51.09	3	Horizontal	4	1.90	-	34.41	7.47	35.53
RMS	5.9158G	46.95	68.20	-21.25	40.33	3	Horizontal	4	1.90	-	34.66	7.52	35.56
PK	6.4174G	110.52	Inf	-Inf	103.39	3	Horizontal	4	1.90	-	34.83	7.73	35.43
RMS	6.415G	101.03	Inf	-Inf	93.89	3	Horizontal	4	1.90	-	34.84	7.73	35.43

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.829G	59.81	88.20	-28.39	43.65	3	Vertical	265	1.67	-	39.33	11.46	34.63
RMS	12.8275G	45.83	68.20	-22.37	29.68	3	Vertical	265	1.67	-	39.33	11.46	34.64

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83372G	65.14	88.20	-23.06	48.96	3	Horizontal	199	1.74	-	39.33	11.47	34.62
RMS	12.82754G	50.99	68.20	-17.21	34.84	3	Horizontal	199	1.74	-	39.33	11.46	34.64

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.24014G	46.59	83.54	-36.95	43.33	1	Vertical	197	2.63	-	37.71	15.20	49.65
AV	19.24188G	32.31	63.54	-31.23	29.05	1	Vertical	197	2.63	-	37.71	15.20	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.25616G	45.98	83.54	-37.56	42.73	1	Horizontal	234	2.22	-	37.70	15.20	49.65
AV	19.24158G	32.39	63.54	-31.15	29.13	1	Horizontal	234	2.22	-	37.71	15.20	49.65

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9226G	81.99	88.20	-6.21	73.21	3	Vertical	45	1.31	-	34.99	6.60	32.81
RMS	5.9242G	67.72	68.20	-0.48	58.93	3	Vertical	45	1.31	-	35.00	6.60	32.81
PK	5.9674G	112.78	Inf	-Inf	103.84	3	Vertical	45	1.31	-	35.17	6.60	32.83
RMS	5.9738G	102.58	Inf	-Inf	93.61	3	Vertical	45	1.31	-	35.20	6.60	32.83

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9226G	79.38	88.20	-8.82	70.60	3	Horizontal	355	1.21	-	34.99	6.60	32.81
RMS	5.925G	65.69	68.20	-2.51	56.90	3	Horizontal	355	1.21	-	35.00	6.60	32.81
PK	5.9674G	109.90	Inf	-Inf	100.96	3	Horizontal	355	1.21	-	35.17	6.60	32.83
RMS	5.9738G	100.31	Inf	-Inf	91.34	3	Horizontal	355	1.21	-	35.20	6.60	32.83

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.91446G	59.96	74.00	-14.04	44.05	3	Vertical	54	1.80	-	38.50	8.98	31.57
AV	11.93462G	47.40	54.00	-6.60	31.49	3	Vertical	54	1.80	-	38.50	8.98	31.57

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.93364G	66.40	74.00	-7.60	50.49	3	Horizontal	207	1.80	-	38.50	8.98	31.57
AV	11.93462G	51.63	54.00	-2.37	35.72	3	Horizontal	207	1.80	-	38.50	8.98	31.57

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8762G	58.56	88.20	-29.64	52.16	3	Vertical	222	1.77	-	34.46	7.48	35.54
RMS	5.6122G	47.51	68.20	-20.69	40.94	3	Vertical	222	1.77	-	34.58	7.40	35.41
PK	6.2074G	111.62	Inf	-Inf	104.27	3	Vertical	222	1.77	-	35.17	7.70	35.52
RMS	6.2074G	101.59	Inf	-Inf	94.24	3	Vertical	222	1.77	-	35.17	7.70	35.52

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7514G	58.52	88.20	-29.68	52.40	3	Horizontal	4	1.87	-	34.20	7.40	35.48
RMS	5.605G	47.50	68.20	-20.70	40.91	3	Horizontal	4	1.87	-	34.59	7.40	35.40
PK	6.2026G	109.68	Inf	-Inf	102.31	3	Horizontal	4	1.87	-	35.19	7.70	35.52
RMS	6.2026G	99.85	Inf	-Inf	92.48	3	Horizontal	4	1.87	-	35.19	7.70	35.52

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.40208G	57.41	74.00	-16.59	42.80	3	Vertical	234	1.80	-	38.90	11.12	35.41
AV	12.40568G	43.71	54.00	-10.29	29.11	3	Vertical	234	1.80	-	38.89	11.12	35.41

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.40652G	61.34	74.00	-12.66	46.73	3	Horizontal	210	1.79	-	38.89	11.13	35.41
AV	12.40586G	47.61	54.00	-6.39	33.01	3	Horizontal	210	1.79	-	38.89	11.12	35.41

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.60084G	45.16	83.54	-38.38	42.46	1	Vertical	7	1.34	-	37.76	14.94	50.00
AV	18.6012G	31.45	63.54	-32.09	28.75	1	Vertical	7	1.34	-	37.76	14.94	50.00

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.615G	45.16	83.54	-38.38	42.44	1	Horizontal	344	1.03	-	37.75	14.95	49.98
AV	18.6051G	31.46	63.54	-32.08	28.75	1	Horizontal	344	1.03	-	37.76	14.94	49.99

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9058G	58.19	88.20	-30.01	51.61	3	Vertical	320	1.95	-	34.62	7.51	35.55
RMS	5.605G	47.47	68.20	-20.73	40.88	3	Vertical	320	1.95	-	34.59	7.40	35.40
PK	6.4082G	108.95	Inf	-Inf	101.80	3	Vertical	320	1.95	-	34.87	7.72	35.44
RMS	6.4082G	99.76	Inf	-Inf	92.61	3	Vertical	320	1.95	-	34.87	7.72	35.44
PK	7.1666G	62.28	88.20	-25.92	53.41	3	Vertical	320	1.95	-	36.20	8.20	35.53
RMS	7.1506G	51.60	68.20	-16.60	42.83	3	Vertical	320	1.95	-	36.10	8.20	35.53

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7618G	58.54	88.20	-29.66	52.42	3	Horizontal	8	1.66	-	34.20	7.40	35.48
RMS	5.6082G	47.52	68.20	-20.68	40.94	3	Horizontal	8	1.66	-	34.58	7.40	35.40
PK	6.4018G	108.13	Inf	-Inf	100.98	3	Horizontal	8	1.66	-	34.89	7.70	35.44
RMS	6.4018G	98.41	Inf	-Inf	91.26	3	Horizontal	8	1.66	-	34.89	7.70	35.44
PK	7.1922G	61.88	88.20	-26.32	52.87	3	Horizontal	8	1.66	-	36.35	8.20	35.54
RMS	7.1474G	51.59	68.20	-16.61	42.84	3	Horizontal	8	1.66	-	36.08	8.20	35.53

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.81564G	58.87	88.20	-29.33	42.76	3	Vertical	264	1.76	-	39.32	11.45	34.66
RMS	12.80574G	44.98	68.20	-23.22	28.92	3	Vertical	264	1.76	-	39.31	11.44	34.69

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.81042G	62.92	88.20	-25.28	46.84	3	Horizontal	198	1.76	-	39.31	11.45	34.68
RMS	12.8058G	48.87	68.20	-19.33	32.81	3	Horizontal	198	1.76	-	39.31	11.44	34.69

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.203G	46.34	83.54	-37.20	43.04	1	Vertical	226	2.03	-	37.76	15.18	49.64
AV	19.21608G	32.79	63.54	-30.75	29.50	1	Vertical	226	2.03	-	37.74	15.19	49.64

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.22916G	46.51	83.54	-37.03	43.24	1	Horizontal	46	2.16	-	37.73	15.19	49.65
AV	19.22244G	32.91	63.54	-30.63	29.63	1	Horizontal	46	2.16	-	37.73	15.19	49.64

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 18
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9214G	80.33	88.20	-7.87	71.55	3	Vertical	46	1.32	-	34.99	6.60	32.81
RMS	5.9184G	67.45	68.20	-0.75	58.69	3	Vertical	46	1.32	-	34.97	6.60	32.81
PK	5.973G	108.51	Inf	-Inf	99.55	3	Vertical	46	1.32	-	35.19	6.60	32.83
RMS	5.9712G	98.79	Inf	-Inf	89.84	3	Vertical	46	1.32	-	35.18	6.60	32.83

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 18
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9214G	79.00	88.20	-9.20	70.22	3	Horizontal	357	1.19	-	34.99	6.60	32.81
RMS	5.9184G	65.82	68.20	-2.38	57.06	3	Horizontal	357	1.19	-	34.97	6.60	32.81
PK	6.018G	106.85	Inf	-Inf	97.80	3	Horizontal	357	1.19	-	35.26	6.63	32.84
RMS	6.0174G	96.68	Inf	-Inf	87.62	3	Horizontal	357	1.19	-	35.27	6.63	32.84

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 18
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.97488G	58.55	74.00	-15.45	42.61	3	Vertical	272	2.60	-	38.50	8.99	31.55
AV	11.97128G	48.50	54.00	-5.50	32.56	3	Vertical	272	2.60	-	38.50	8.99	31.55
PK	17.95116G	60.16	74.00	-13.84	36.90	3	Vertical	5	1.82	-	42.85	11.09	30.68
AV	17.9503G	50.38	54.00	-3.62	27.12	3	Vertical	5	1.82	-	42.85	11.09	30.68

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 18
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.96626G	58.51	74.00	-15.49	42.57	3	Horizontal	324	2.79	-	38.50	8.99	31.55
AV	11.96908G	48.87	54.00	-5.13	32.93	3	Horizontal	324	2.79	-	38.50	8.99	31.55
PK	17.95846G	60.35	74.00	-13.65	37.08	3	Horizontal	125	2.13	-	42.86	11.09	30.68
AV	17.95785G	50.70	54.00	-3.30	27.43	3	Horizontal	125	2.13	-	42.86	11.09	30.68

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.821G	58.29	88.20	-29.91	52.14	3	Vertical	220	1.69	-	34.24	7.42	35.51
RMS	5.925G	47.56	68.20	-20.64	40.89	3	Vertical	220	1.69	-	34.70	7.53	35.56
PK	6.219G	108.14	Inf	-Inf	100.83	3	Vertical	220	1.69	-	35.12	7.70	35.51
RMS	6.231G	98.49	Inf	-Inf	91.22	3	Vertical	220	1.69	-	35.08	7.70	35.51

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.903G	58.68	88.20	-29.52	52.12	3	Horizontal	8	1.74	-	34.61	7.50	35.55
RMS	5.925G	47.51	68.20	-20.69	40.84	3	Horizontal	8	1.74	-	34.70	7.53	35.56
PK	6.229G	106.38	Inf	-Inf	99.11	3	Horizontal	8	1.74	-	35.08	7.70	35.51
RMS	6.221G	96.62	Inf	-Inf	89.31	3	Horizontal	8	1.74	-	35.12	7.70	35.51

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.44448G	56.68	74.00	-17.32	42.06	3	Vertical	235	1.80	-	38.86	11.16	35.40
AV	12.45018G	45.74	54.00	-8.26	31.13	3	Vertical	235	1.80	-	38.85	11.16	35.40

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.46212G	59.50	74.00	-14.50	44.89	3	Horizontal	204	2.85	-	38.84	11.17	35.40
AV	12.44526G	48.49	54.00	-5.51	33.88	3	Horizontal	204	2.85	-	38.85	11.16	35.40

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6876G	45.18	83.54	-38.36	42.39	1	Vertical	225	1.80	-	37.72	14.98	49.91
AV	18.67038G	34.59	63.54	-28.95	31.82	1	Vertical	225	1.80	-	37.73	14.97	49.93

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.67512G	44.83	83.54	-38.71	42.05	1	Horizontal	23	1.74	-	37.73	14.97	49.92
AV	18.67938G	34.45	63.54	-29.09	31.67	1	Horizontal	23	1.74	-	37.73	14.97	49.92

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8978G	58.42	88.20	-29.78	51.88	3	Vertical	322	2.07	-	34.59	7.50	35.55
RMS	5.8922G	47.44	68.20	-20.76	40.95	3	Vertical	322	2.07	-	34.55	7.49	35.55
PK	6.3878G	104.73	Inf	-Inf	97.57	3	Vertical	322	2.07	-	34.90	7.70	35.44
RMS	6.3822G	94.72	Inf	-Inf	87.57	3	Vertical	322	2.07	-	34.90	7.70	35.45

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8838G	58.47	88.20	-29.73	52.03	3	Horizontal	8	1.70	-	34.50	7.48	35.54
RMS	5.923G	47.44	68.20	-20.76	40.79	3	Horizontal	8	1.70	-	34.69	7.52	35.56
PK	6.3878G	103.93	Inf	-Inf	96.77	3	Horizontal	8	1.70	-	34.90	7.70	35.44
RMS	6.3878G	93.81	Inf	-Inf	86.65	3	Horizontal	8	1.70	-	34.90	7.70	35.44

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.7814G	56.22	88.20	-31.98	40.27	3	Vertical	242	2.37	-	39.26	11.43	34.74
RMS	12.77486G	45.34	68.20	-22.86	29.43	3	Vertical	242	2.37	-	39.25	11.42	34.76

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.779G	56.60	88.20	-31.60	40.67	3	Horizontal	254	2.19	-	39.26	11.42	34.75
RMS	12.78188G	46.14	68.20	-22.06	30.19	3	Horizontal	254	2.19	-	39.26	11.43	34.74

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.14846G	46.01	83.54	-37.53	42.66	1	Vertical	121	2.14	-	37.82	15.16	49.63
AV	19.15428G	35.26	63.54	-28.28	31.92	1	Vertical	121	2.14	-	37.81	15.16	49.63

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.14402G	45.71	83.54	-37.83	42.35	1	Horizontal	55	2.76	-	37.83	15.16	49.63
AV	19.14714G	35.16	63.54	-28.38	31.81	1	Horizontal	55	2.76	-	37.82	15.16	49.63

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.901G	83.26	88.20	-4.94	74.56	3	Vertical	72	1.40	-	34.90	6.60	32.80
RMS	5.901G	67.84	68.20	-0.36	59.14	3	Vertical	72	1.40	-	34.90	6.60	32.80
PK	6G	104.42	Inf	-Inf	95.36	3	Vertical	72	1.40	-	35.30	6.60	32.84
RMS	6.03G	94.84	Inf	-Inf	85.80	3	Vertical	72	1.40	-	35.24	6.64	32.84

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.901G	79.97	88.20	-8.23	71.27	3	Horizontal	360	1.17	-	34.90	6.60	32.80
RMS	5.923G	65.41	68.20	-2.79	56.63	3	Horizontal	360	1.17	-	34.99	6.60	32.81
PK	6.103G	102.26	Inf	-Inf	93.05	3	Horizontal	360	1.17	-	35.30	6.75	32.84
RMS	6.03G	92.94	Inf	-Inf	83.90	3	Horizontal	360	1.17	-	35.24	6.64	32.84

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.05054G	58.43	74.00	-15.57	42.41	3	Vertical	299	2.00	-	38.55	9.02	31.55
AV	12.05398G	48.75	54.00	-5.25	32.73	3	Vertical	299	2.00	-	38.55	9.02	31.55

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.05132G	59.09	74.00	-14.91	43.07	3	Horizontal	42	2.03	-	38.55	9.02	31.55
AV	12.05398G	48.58	54.00	-5.42	32.56	3	Horizontal	42	2.03	-	38.55	9.02	31.55

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.07096G	45.92	83.54	-37.62	43.82	1	Vertical	239	1.55	-	37.64	14.73	50.27
AV	18.0788G	35.10	63.54	-28.44	33.00	1	Vertical	239	1.55	-	37.64	14.73	50.27

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.07216G	44.34	83.54	-39.20	42.24	1	Horizontal	271	1.50	-	37.64	14.73	50.27
AV	18.07634G	34.96	63.54	-28.58	32.86	1	Horizontal	271	1.50	-	37.64	14.73	50.27

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.921G	69.81	88.20	-18.39	63.17	3	Vertical	221	1.79	-	34.68	7.52	35.56
RMS	5.921G	53.67	68.20	-14.53	47.03	3	Vertical	221	1.79	-	34.68	7.52	35.56
PK	6.181G	105.03	Inf	-Inf	97.75	3	Vertical	221	1.79	-	35.12	7.69	35.53
RMS	6.181G	95.62	Inf	-Inf	88.34	3	Vertical	221	1.79	-	35.12	7.69	35.53

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.907G	67.06	88.20	-21.14	60.47	3	Horizontal	5	1.89	-	34.63	7.51	35.55
RMS	5.919G	51.51	68.20	-16.69	44.87	3	Horizontal	5	1.89	-	34.68	7.52	35.56
PK	6.181G	103.65	Inf	-Inf	96.37	3	Horizontal	5	1.89	-	35.12	7.69	35.53
RMS	6.189G	94.06	Inf	-Inf	86.73	3	Horizontal	5	1.89	-	35.16	7.69	35.52

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38074G	59.75	74.00	-14.25	45.18	3	Vertical	176	2.54	-	38.88	11.10	35.41
AV	12.38338G	48.25	54.00	-5.75	33.67	3	Vertical	176	2.54	-	38.88	11.11	35.41

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38392G	59.59	74.00	-14.41	45.01	3	Horizontal	203	2.62	-	38.88	11.11	35.41
AV	12.3811G	48.06	54.00	-5.94	33.49	3	Horizontal	203	2.62	-	38.88	11.10	35.41

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.55476G	45.59	83.54	-37.95	42.94	1	Vertical	68	1.16	-	37.78	14.92	50.05
AV	18.56256G	34.90	63.54	-28.64	32.24	1	Vertical	68	1.16	-	37.77	14.93	50.04

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.56118G	45.09	83.54	-38.45	42.43	1	Horizontal	19	2.83	-	37.78	14.92	50.04
AV	18.54672G	34.34	63.54	-29.20	31.69	1	Horizontal	19	2.83	-	37.78	14.92	50.05

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.913G	58.69	88.20	-29.51	52.09	3	Vertical	320	1.91	-	34.65	7.51	35.56
RMS	5.919G	47.67	68.20	-20.53	41.03	3	Vertical	320	1.91	-	34.68	7.52	35.56
PK	6.342G	103.16	Inf	-Inf	96.00	3	Vertical	320	1.91	-	34.92	7.70	35.46
RMS	6.342G	93.52	Inf	-Inf	86.36	3	Vertical	320	1.91	-	34.92	7.70	35.46

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.658G	58.69	88.20	-29.51	52.25	3	Horizontal	6	1.69	-	34.47	7.40	35.43
RMS	5.922G	47.70	68.20	-20.50	41.05	3	Horizontal	6	1.69	-	34.69	7.52	35.56
PK	6.342G	101.82	Inf	-Inf	94.66	3	Horizontal	6	1.69	-	34.92	7.70	35.46
RMS	6.342G	92.14	Inf	-Inf	84.98	3	Horizontal	6	1.69	-	34.92	7.70	35.46

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.69474G	56.55	74.00	-17.45	41.05	3	Vertical	8	2.32	-	39.08	11.36	34.94
AV	12.69648G	45.79	54.00	-8.21	30.28	3	Vertical	8	2.32	-	39.09	11.36	34.94

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.68412G	56.71	74.00	-17.29	41.28	3	Horizontal	316	2.50	-	39.05	11.35	34.97
AV	12.6867G	45.50	54.00	-8.50	30.05	3	Horizontal	316	2.50	-	39.06	11.35	34.96

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.02072G	45.62	83.54	-37.92	42.13	1	Vertical	319	1.48	-	37.98	15.11	49.60
AV	19.0239G	34.78	63.54	-28.76	31.30	1	Vertical	319	1.48	-	37.97	15.11	49.60

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom



EUT Y_1TX
Setting 15
03-B-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.03326G	45.79	83.54	-37.75	42.33	1	Horizontal	187	2.99	-	37.96	15.11	49.61
AV	19.02924G	34.87	63.54	-28.67	31.41	1	Horizontal	187	2.99	-	37.96	15.11	49.61

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW160_Nss1,(MCS0)_1TX	Pass	RMS	5.9162G	68.17	68.20	-0.03	3	Vertical	19	2.31	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 19
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	71.66	88.20	-16.54	62.87	3	Vertical	36	1.82	-	35.00	6.60	32.81
RMS	5.9246G	54.25	68.20	-13.95	45.46	3	Vertical	36	1.82	-	35.00	6.60	32.81
PK	5.9546G	116.58	Inf	-Inf	107.68	3	Vertical	36	1.82	-	35.12	6.60	32.82
RMS	5.9578G	106.14	Inf	-Inf	97.23	3	Vertical	36	1.82	-	35.13	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 19
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9242G	63.11	88.20	-25.09	54.32	3	Horizontal	58	1.79	-	35.00	6.60	32.81
RMS	5.925G	51.41	68.20	-16.79	42.62	3	Horizontal	58	1.79	-	35.00	6.60	32.81
PK	5.9546G	106.87	Inf	-Inf	97.97	3	Horizontal	58	1.79	-	35.12	6.60	32.82
RMS	5.9578G	96.39	Inf	-Inf	87.48	3	Horizontal	58	1.79	-	35.13	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 19
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.915G	57.61	74.00	-16.39	41.70	3	Vertical	228	1.80	-	38.50	8.98	31.57
AV	11.9078G	45.60	54.00	-8.40	29.70	3	Vertical	228	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 19
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.91306G	66.41	74.00	-7.59	50.50	3	Horizontal	204	1.80	-	38.50	8.98	31.57
AV	11.90862G	53.76	54.00	-0.24	37.86	3	Horizontal	204	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9108G	61.07	88.20	-27.13	52.33	3	Vertical	243	1.74	-	34.94	6.60	32.80
RMS	5.915G	48.20	68.20	-20.00	39.45	3	Vertical	243	1.74	-	34.96	6.60	32.81
PK	6.195G	117.65	Inf	-Inf	108.13	3	Vertical	243	1.74	-	35.48	6.89	32.85
RMS	6.1964G	105.46	Inf	-Inf	95.93	3	Vertical	243	1.74	-	35.49	6.89	32.85

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8576G	61.31	88.20	-26.89	52.67	3	Horizontal	176	2.71	-	34.82	6.60	32.78
RMS	5.9206G	48.19	68.20	-20.01	39.42	3	Horizontal	176	2.71	-	34.98	6.60	32.81
PK	6.195G	111.25	Inf	-Inf	101.73	3	Horizontal	176	2.71	-	35.48	6.89	32.85
RMS	6.1964G	98.34	Inf	-Inf	88.81	3	Horizontal	176	2.71	-	35.49	6.89	32.85

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38976G	61.93	74.00	-12.07	45.65	3	Vertical	236	1.79	-	38.68	9.18	31.58
AV	12.3888G	48.07	54.00	-5.93	31.80	3	Vertical	236	1.79	-	38.68	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39336G	66.25	74.00	-7.75	49.96	3	Horizontal	205	1.80	-	38.69	9.18	31.58
AV	12.38912G	52.71	54.00	-1.29	36.43	3	Horizontal	205	1.80	-	38.68	9.18	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58529G	46.98	83.54	-36.56	44.29	1	Vertical	132	1.66	-	37.77	14.93	50.01
AV	18.58879G	34.25	63.54	-29.29	31.56	1	Vertical	132	1.66	-	37.76	14.94	50.01

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58887G	47.71	83.54	-35.83	45.02	1	Horizontal	254	1.69	-	37.76	14.94	50.01
AV	18.58138G	34.35	63.54	-29.19	31.67	1	Horizontal	254	1.69	-	37.77	14.93	50.02

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8966G	60.58	88.20	-27.62	51.89	3	Vertical	324	1.72	-	34.89	6.60	32.80
RMS	5.9206G	48.17	68.20	-20.03	39.40	3	Vertical	324	1.72	-	34.98	6.60	32.81
PK	6.4174G	115.96	Inf	-Inf	106.29	3	Vertical	324	1.72	-	35.53	7.00	32.86
RMS	6.415G	104.82	Inf	-Inf	95.14	3	Vertical	324	1.72	-	35.54	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9206G	60.77	88.20	-27.43	52.00	3	Horizontal	157	1.62	-	34.98	6.60	32.81
RMS	5.9206G	48.23	68.20	-19.97	39.46	3	Horizontal	157	1.62	-	34.98	6.60	32.81
PK	6.4174G	107.25	Inf	-Inf	97.58	3	Horizontal	157	1.62	-	35.53	7.00	32.86
RMS	6.415G	96.41	Inf	-Inf	86.73	3	Horizontal	157	1.62	-	35.54	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83336G	63.59	88.20	-24.61	45.86	3	Vertical	273	1.80	-	39.23	9.38	30.88
RMS	12.8276G	49.41	68.20	-18.79	31.70	3	Vertical	273	1.80	-	39.23	9.37	30.89

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83336G	66.37	88.20	-21.83	48.64	3	Horizontal	202	1.80	-	39.23	9.38	30.88
RMS	12.82736G	52.65	68.20	-15.55	34.94	3	Horizontal	202	1.80	-	39.23	9.37	30.89

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.24286G	48.46	83.54	-35.08	45.20	1	Vertical	130	2.21	-	37.71	15.20	49.65
AV	19.24458G	35.05	63.54	-28.49	31.79	1	Vertical	130	2.21	-	37.71	15.20	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.24324G	47.92	83.54	-35.62	44.66	1	Horizontal	275	2.22	-	37.71	15.20	49.65
AV	19.24198G	34.31	63.54	-29.23	31.05	1	Horizontal	275	2.22	-	37.71	15.20	49.65

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 8.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	79.76	88.20	-8.44	70.98	3	Vertical	18	2.35	-	34.99	6.60	32.81
RMS	5.9238G	67.90	68.20	-0.30	59.11	3	Vertical	18	2.35	-	35.00	6.60	32.81
PK	5.9678G	113.55	Inf	-Inf	104.61	3	Vertical	18	2.35	-	35.17	6.60	32.83
RMS	5.9674G	103.18	Inf	-Inf	94.24	3	Vertical	18	2.35	-	35.17	6.60	32.83

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 8.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	71.61	88.20	-16.59	62.82	3	Horizontal	344	2.88	-	35.00	6.60	32.81
RMS	5.925G	59.96	68.20	-8.24	51.17	3	Horizontal	344	2.88	-	35.00	6.60	32.81
PK	5.9678G	104.85	Inf	-Inf	95.91	3	Horizontal	344	2.88	-	35.17	6.60	32.83
RMS	5.9678G	94.70	Inf	-Inf	85.76	3	Horizontal	344	2.88	-	35.17	6.60	32.83

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 8.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.93672G	59.78	74.00	-14.22	43.87	3	Vertical	229	1.77	-	38.50	8.98	31.57
AV	11.93336G	47.13	54.00	-6.87	31.22	3	Vertical	229	1.77	-	38.50	8.98	31.57

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 8.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.93696G	60.57	74.00	-13.43	44.66	3	Horizontal	205	1.78	-	38.50	8.98	31.57
AV	11.92964G	50.20	54.00	-3.80	34.29	3	Horizontal	205	1.78	-	38.50	8.98	31.57

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9074G	60.27	88.20	-27.93	51.54	3	Vertical	315	1.78	-	34.93	6.60	32.80
RMS	5.9218G	50.02	68.20	-18.18	41.24	3	Vertical	315	1.78	-	34.99	6.60	32.81
PK	6.2074G	113.85	Inf	-Inf	104.36	3	Vertical	315	1.78	-	35.44	6.90	32.85
RMS	6.2026G	104.52	Inf	-Inf	94.99	3	Vertical	315	1.78	-	35.48	6.90	32.85

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	60.51	88.20	-27.69	51.73	3	Horizontal	175	2.71	-	34.99	6.60	32.81
RMS	5.9242G	50.01	68.20	-18.19	41.22	3	Horizontal	175	2.71	-	35.00	6.60	32.81
PK	6.2038G	108.14	Inf	-Inf	98.62	3	Horizontal	175	2.71	-	35.47	6.90	32.85
RMS	6.2026G	98.79	Inf	-Inf	89.26	3	Horizontal	175	2.71	-	35.48	6.90	32.85

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.40632G	60.27	74.00	-13.73	43.98	3	Vertical	235	1.80	-	38.69	9.18	31.58
AV	12.40584G	46.78	54.00	-7.22	30.49	3	Vertical	235	1.80	-	38.69	9.18	31.58

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39928G	63.47	74.00	-10.53	47.17	3	Horizontal	205	1.79	-	38.70	9.18	31.58
AV	12.40584G	50.74	54.00	-3.26	34.45	3	Horizontal	205	1.79	-	38.69	9.18	31.58

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.61766G	47.91	83.54	-35.63	45.19	1	Vertical	204	2.89	-	37.75	14.95	49.98
AV	18.61759G	33.61	63.54	-29.93	30.89	1	Vertical	204	2.89	-	37.75	14.95	49.98

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.61364G	47.39	83.54	-36.15	44.68	1	Horizontal	38	1.18	-	37.75	14.95	49.99
AV	18.61729G	33.67	63.54	-29.87	30.95	1	Horizontal	38	1.18	-	37.75	14.95	49.98

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.877G	60.62	88.20	-27.58	51.96	3	Vertical	321	1.74	-	34.85	6.60	32.79
RMS	5.9226G	49.97	68.20	-18.23	41.19	3	Vertical	321	1.74	-	34.99	6.60	32.81
PK	6.4002G	112.62	Inf	-Inf	102.88	3	Vertical	321	1.74	-	35.60	7.00	32.86
RMS	6.4074G	103.64	Inf	-Inf	93.93	3	Vertical	321	1.74	-	35.57	7.00	32.86

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9082G	60.67	88.20	-27.53	51.94	3	Horizontal	156	1.81	-	34.93	6.60	32.80
RMS	5.9226G	49.97	68.20	-18.23	41.19	3	Horizontal	156	1.81	-	34.99	6.60	32.81
PK	6.4002G	103.94	Inf	-Inf	94.20	3	Horizontal	156	1.81	-	35.60	7.00	32.86
RMS	6.4074G	94.90	Inf	-Inf	85.19	3	Horizontal	156	1.81	-	35.57	7.00	32.86

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.80568G	61.35	88.20	-26.85	43.72	3	Vertical	278	1.80	-	39.21	9.36	30.94
RMS	12.80568G	48.05	68.20	-20.15	30.42	3	Vertical	278	1.80	-	39.21	9.36	30.94

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.80152G	64.30	88.20	-23.90	46.68	3	Horizontal	207	1.80	-	39.20	9.36	30.94
RMS	12.80568G	51.12	68.20	-17.08	33.49	3	Horizontal	207	1.80	-	39.21	9.36	30.94

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.21399G	48.76	83.54	-34.78	45.47	1	Vertical	2	1.99	-	37.74	15.19	49.64
AV	19.21822G	34.23	63.54	-29.31	30.94	1	Vertical	2	1.99	-	37.74	15.19	49.64

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.21762G	48.03	83.54	-35.51	44.74	1	Horizontal	137	1.32	-	37.74	15.19	49.64
AV	19.21438G	34.17	63.54	-29.37	30.88	1	Horizontal	137	1.32	-	37.74	15.19	49.64

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 11.25
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.922G	80.58	88.20	-7.62	71.80	3	Vertical	18	2.44	-	34.99	6.60	32.81
RMS	5.923G	67.72	68.20	-0.48	58.94	3	Vertical	18	2.44	-	34.99	6.60	32.81
PK	6.01G	107.45	Inf	-Inf	98.39	3	Vertical	18	2.44	-	35.28	6.62	32.84
RMS	6.018G	100.24	Inf	-Inf	91.19	3	Vertical	18	2.44	-	35.26	6.63	32.84

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 11.25
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.916G	73.27	88.20	-14.93	64.52	3	Horizontal	349	2.87	-	34.96	6.60	32.81
RMS	5.925G	60.30	68.20	-7.90	51.51	3	Horizontal	349	2.87	-	35.00	6.60	32.81
PK	5.967G	99.87	Inf	-Inf	90.93	3	Horizontal	349	2.87	-	35.17	6.60	32.83
RMS	5.968G	91.98	Inf	-Inf	83.04	3	Horizontal	349	2.87	-	35.17	6.60	32.83

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 11.25
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9669G	58.17	74.00	-15.83	42.23	3	Vertical	289	1.20	-	38.50	8.99	31.55
AV	11.96678G	48.95	54.00	-5.05	33.01	3	Vertical	289	1.20	-	38.50	8.99	31.55

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 11.25
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.96662G	58.19	74.00	-15.81	42.25	3	Horizontal	177	2.21	-	38.50	8.99	31.55
AV	11.97014G	48.81	54.00	-5.19	32.87	3	Horizontal	177	2.21	-	38.50	8.99	31.55

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	61.72	88.20	-26.48	52.94	3	Vertical	318	1.75	-	34.99	6.60	32.81
RMS	5.921G	50.18	68.20	-18.02	41.41	3	Vertical	318	1.75	-	34.98	6.60	32.81
PK	6.229G	111.19	Inf	-Inf	101.86	3	Vertical	318	1.75	-	35.27	6.91	32.85
RMS	6.223G	101.20	Inf	-Inf	91.82	3	Vertical	318	1.75	-	35.32	6.91	32.85

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.873G	60.92	88.20	-27.28	52.26	3	Horizontal	173	2.56	-	34.85	6.60	32.79
RMS	5.921G	50.03	68.20	-18.17	41.26	3	Horizontal	173	2.56	-	34.98	6.60	32.81
PK	6.219G	105.28	Inf	-Inf	95.87	3	Horizontal	173	2.56	-	35.35	6.91	32.85
RMS	6.219G	95.75	Inf	-Inf	86.34	3	Horizontal	173	2.56	-	35.35	6.91	32.85

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.45122G	58.44	74.00	-15.56	42.23	3	Vertical	337	2.01	-	38.60	9.20	31.59
AV	12.44683G	47.40	54.00	-6.60	31.17	3	Vertical	337	2.01	-	38.61	9.20	31.58

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.44619G	58.32	74.00	-15.68	42.09	3	Horizontal	79	1.52	-	38.61	9.20	31.58
AV	12.45341G	47.30	54.00	-6.70	31.10	3	Horizontal	79	1.52	-	38.59	9.20	31.59

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.67842G	47.33	83.54	-36.21	44.55	1	Vertical	227	1.79	-	37.73	14.97	49.92
AV	18.67343G	36.73	63.54	-26.81	33.96	1	Vertical	227	1.79	-	37.73	14.97	49.93

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6775G	48.00	83.54	-35.54	45.22	1	Horizontal	227	1.79	-	37.73	14.97	49.92
AV	18.67151G	37.27	63.54	-26.27	34.50	1	Horizontal	227	1.79	-	37.73	14.97	49.93

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8762G	60.54	88.20	-27.66	51.88	3	Vertical	320	1.67	-	34.85	6.60	32.79
RMS	5.9218G	50.00	68.20	-18.20	41.22	3	Vertical	320	1.67	-	34.99	6.60	32.81
PK	6.3874G	108.11	Inf	-Inf	98.46	3	Vertical	320	1.67	-	35.52	6.99	32.86
RMS	6.3826G	99.17	Inf	-Inf	89.54	3	Vertical	320	1.67	-	35.50	6.99	32.86

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.905G	60.91	88.20	-27.29	52.19	3	Horizontal	157	1.62	-	34.92	6.60	32.80
RMS	5.9242G	49.99	68.20	-18.21	41.20	3	Horizontal	157	1.62	-	35.00	6.60	32.81
PK	6.3874G	100.98	Inf	-Inf	91.33	3	Horizontal	157	1.62	-	35.52	6.99	32.86
RMS	6.3874G	91.75	Inf	-Inf	82.10	3	Horizontal	157	1.62	-	35.52	6.99	32.86

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.76796G	58.57	88.20	-29.63	41.10	3	Vertical	112	1.64	-	39.14	9.35	31.02
RMS	12.76952G	48.10	68.20	-20.10	30.62	3	Vertical	112	1.64	-	39.14	9.35	31.01

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.76924G	58.97	88.20	-29.23	41.49	3	Horizontal	270	1.17	-	39.14	9.35	31.01
RMS	12.7681G	48.24	68.20	-19.96	30.77	3	Horizontal	270	1.17	-	39.14	9.35	31.02

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.15255G	48.35	83.54	-35.19	45.00	1	Vertical	310	1.05	-	37.82	15.16	49.63
AV	19.15858G	37.22	63.54	-26.32	33.88	1	Vertical	310	1.05	-	37.81	15.16	49.63

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.15113G	48.28	83.54	-35.26	44.93	1	Horizontal	311	1.67	-	37.82	15.16	49.63
AV	19.15796G	37.34	63.54	-26.20	34.00	1	Horizontal	311	1.67	-	37.81	15.16	49.63

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.25
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8906G	81.04	88.20	-7.16	72.36	3	Vertical	19	2.31	-	34.88	6.60	32.80
RMS	5.9162G	68.17	68.20	-0.03	59.42	3	Vertical	19	2.31	-	34.96	6.60	32.81
PK	6.0538G	103.42	Inf	-Inf	94.37	3	Vertical	19	2.31	-	35.21	6.68	32.84
RMS	6.0986G	96.13	Inf	-Inf	86.92	3	Vertical	19	2.31	-	35.30	6.75	32.84

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.25
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8906G	72.77	88.20	-15.43	64.09	3	Horizontal	349	2.93	-	34.88	6.60	32.80
RMS	5.9018G	59.29	68.20	-8.91	50.58	3	Horizontal	349	2.93	-	34.91	6.60	32.80
PK	5.993G	94.72	Inf	-Inf	85.69	3	Horizontal	349	2.93	-	35.27	6.60	32.84
RMS	5.993G	86.69	Inf	-Inf	77.66	3	Horizontal	349	2.93	-	35.27	6.60	32.84

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.25
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.052G	58.44	74.00	-15.56	42.42	3	Vertical	348	2.50	-	38.55	9.02	31.55
AV	12.04626G	48.52	54.00	-5.48	32.49	3	Vertical	348	2.50	-	38.55	9.02	31.54

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.25
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.0466G	58.21	74.00	-15.79	42.18	3	Horizontal	348	1.98	-	38.55	9.02	31.54
AV	12.04716G	49.02	54.00	-4.98	32.99	3	Horizontal	348	1.98	-	38.55	9.02	31.54

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.25
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.07482G	44.86	83.54	-38.68	42.76	1	Vertical	281	1.52	-	37.64	14.73	50.27
AV	18.07146G	35.19	63.54	-28.35	33.09	1	Vertical	281	1.52	-	37.64	14.73	50.27

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 16.25
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.07252G	45.44	83.54	-38.10	43.34	1	Horizontal	359	1.58	-	37.64	14.73	50.27
AV	18.07706G	35.16	63.54	-28.38	33.06	1	Horizontal	359	1.58	-	37.64	14.73	50.27

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9178G	62.67	88.20	-25.53	53.91	3	Vertical	287	1.80	-	34.97	6.60	32.81
RMS	5.921G	51.69	68.20	-16.51	42.92	3	Vertical	287	1.80	-	34.98	6.60	32.81
PK	6.169G	108.10	Inf	-Inf	98.72	3	Vertical	287	1.80	-	35.38	6.85	32.85
RMS	6.1882G	98.56	Inf	-Inf	89.08	3	Vertical	287	1.80	-	35.45	6.88	32.85

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.921G	65.74	88.20	-22.46	56.97	3	Horizontal	182	2.90	-	34.98	6.60	32.81
RMS	5.921G	52.48	68.20	-15.72	43.71	3	Horizontal	182	2.90	-	34.98	6.60	32.81
PK	6.1818G	103.48	Inf	-Inf	94.03	3	Horizontal	182	2.90	-	35.43	6.87	32.85
RMS	6.1882G	93.89	Inf	-Inf	84.41	3	Horizontal	182	2.90	-	35.45	6.88	32.85

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3707G	57.10	74.00	-16.90	40.87	3	Vertical	54	2.67	-	38.64	9.17	31.58
AV	12.37355G	46.85	54.00	-7.15	30.61	3	Vertical	54	2.67	-	38.65	9.17	31.58

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.36813G	57.90	74.00	-16.10	41.67	3	Horizontal	188	1.74	-	38.64	9.17	31.58
AV	12.37174G	47.02	54.00	-6.98	30.79	3	Horizontal	188	1.74	-	38.64	9.17	31.58

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.55788G	47.25	83.54	-36.29	44.59	1	Vertical	193	2.74	-	37.78	14.92	50.04
AV	18.55284G	36.66	63.54	-26.88	34.01	1	Vertical	193	2.74	-	37.78	14.92	50.05

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5565G	46.72	83.54	-36.82	44.06	1	Horizontal	256	2.31	-	37.78	14.92	50.04
AV	18.55202G	36.37	63.54	-27.17	33.72	1	Horizontal	256	2.31	-	37.78	14.92	50.05

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.909G	60.59	88.20	-27.61	51.85	3	Vertical	226	1.85	-	34.94	6.60	32.80
RMS	5.921G	50.76	68.20	-17.44	41.99	3	Vertical	226	1.85	-	34.98	6.60	32.81
PK	6.369G	106.66	Inf	-Inf	97.12	3	Vertical	226	1.85	-	35.41	6.98	32.85
RMS	6.349G	97.80	Inf	-Inf	88.38	3	Vertical	226	1.85	-	35.30	6.97	32.85

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.909G	61.49	88.20	-26.71	52.75	3	Horizontal	174	2.67	-	34.94	6.60	32.80
RMS	5.923G	50.71	68.20	-17.49	41.93	3	Horizontal	174	2.67	-	34.99	6.60	32.81
PK	6.357G	101.57	Inf	-Inf	92.10	3	Horizontal	174	2.67	-	35.34	6.98	32.85
RMS	6.349G	92.53	Inf	-Inf	83.11	3	Horizontal	174	2.67	-	35.30	6.97	32.85

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.69354G	58.77	74.00	-15.23	41.66	3	Vertical	283	2.03	-	38.98	9.31	31.18
AV	12.6933G	48.22	54.00	-5.78	31.11	3	Vertical	283	2.03	-	38.98	9.31	31.18

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.68715G	58.93	74.00	-15.07	41.85	3	Horizontal	265	1.14	-	38.96	9.31	31.19
AV	12.68997G	48.05	54.00	-5.95	30.95	3	Horizontal	265	1.14	-	38.97	9.31	31.18

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.03575G	47.40	83.54	-36.14	43.94	1	Vertical	313	1.83	-	37.96	15.11	49.61
AV	19.03209G	36.53	63.54	-27.01	33.07	1	Vertical	313	1.83	-	37.96	15.11	49.61

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom



EUT Y_1TX
Setting 15
01-C-K-3


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.03204G	47.62	83.54	-35.92	44.16	1	Horizontal	253	1.97	-	37.96	15.11	49.61
AV	19.03874G	36.75	63.54	-26.79	33.29	1	Horizontal	253	1.97	-	37.95	15.12	49.61

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW80_Nss1,(MCS0)_1TX	Pass	AV	11.9841G	53.97	54.00	-0.03	3	Horizontal	211	1.79	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 14
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9242G	68.73	88.20	-19.47	59.94	3	Vertical	90	1.46	-	35.00	6.60	32.81
RMS	5.925G	52.83	68.20	-15.37	44.04	3	Vertical	90	1.46	-	35.00	6.60	32.81
PK	5.9546G	112.85	Inf	-Inf	103.95	3	Vertical	90	1.46	-	35.12	6.60	32.82
RMS	5.9538G	102.29	Inf	-Inf	93.39	3	Vertical	90	1.46	-	35.12	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 14
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.91264G	57.97	74.00	-16.03	42.06	3	Vertical	38	1.80	-	38.50	8.98	31.57
AV	11.91726G	48.32	54.00	-5.68	32.41	3	Vertical	38	1.80	-	38.50	8.98	31.57

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 14
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9076G	63.81	74.00	-10.19	47.91	3	Horizontal	211	1.80	-	38.50	8.98	31.58
AV	11.9115G	53.77	54.00	-0.23	37.87	3	Horizontal	211	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	58.62	88.20	-29.58	51.97	3	Vertical	70	1.78	-	34.69	7.52	35.56
RMS	5.921G	47.58	68.20	-20.62	40.94	3	Vertical	70	1.78	-	34.68	7.52	35.56
PK	6.195G	117.98	Inf	-Inf	110.62	3	Vertical	70	1.78	-	35.18	7.70	35.52
RMS	6.195G	108.34	Inf	-Inf	100.98	3	Vertical	70	1.78	-	35.18	7.70	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39114G	58.51	74.00	-15.49	43.92	3	Vertical	229	1.69	-	38.89	11.11	35.41
AV	12.38742G	45.04	54.00	-8.96	30.45	3	Vertical	229	1.69	-	38.89	11.11	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39366G	65.07	74.00	-8.93	50.48	3	Horizontal	204	2.31	-	38.89	11.11	35.41
AV	12.38736G	50.97	54.00	-3.03	36.38	3	Horizontal	204	2.31	-	38.89	11.11	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5901G	46.41	83.54	-37.13	43.72	1	Vertical	97	2.66	-	37.76	14.94	50.01
AV	18.58704G	32.44	63.54	-31.10	29.75	1	Vertical	97	2.66	-	37.77	14.93	50.01

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.57942G	45.81	83.54	-37.73	43.13	1	Horizontal	144	2.34	-	37.77	14.93	50.02
AV	18.58572G	32.42	63.54	-31.12	29.73	1	Horizontal	144	2.34	-	37.77	14.93	50.01

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8774G	59.32	88.20	-28.88	52.92	3	Vertical	70	1.80	-	34.46	7.48	35.54
RMS	5.9158G	47.49	68.20	-20.71	40.87	3	Vertical	70	1.80	-	34.66	7.52	35.56
PK	6.4182G	117.54	Inf	-Inf	110.40	3	Vertical	70	1.80	-	34.83	7.74	35.43
RMS	6.415G	108.99	Inf	-Inf	101.85	3	Vertical	70	1.80	-	34.84	7.73	35.43
PK	7.1382G	60.71	88.20	-27.49	52.01	3	Vertical	70	1.80	-	36.03	8.20	35.53
RMS	7.2118G	50.29	68.20	-17.91	41.15	3	Vertical	70	1.80	-	36.47	8.22	35.55

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.82724G	58.69	88.20	-29.51	42.54	3	Vertical	227	1.80	-	39.33	11.46	34.64
RMS	12.8273G	44.66	68.20	-23.54	28.51	3	Vertical	227	1.80	-	39.33	11.46	34.64

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83372G	64.25	88.20	-23.95	48.07	3	Horizontal	204	2.20	-	39.33	11.47	34.62
RMS	12.8273G	50.54	68.20	-17.66	34.39	3	Horizontal	204	2.20	-	39.33	11.46	34.64

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.25586G	46.52	83.54	-37.02	43.27	1	Vertical	158	1.19	-	37.70	15.20	49.65
AV	19.23G	33.00	63.54	-30.54	29.74	1	Vertical	158	1.19	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 19.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2345G	45.81	83.54	-37.73	42.55	1	Horizontal	248	2.89	-	37.72	15.19	49.65
AV	19.23006G	32.84	63.54	-30.70	29.58	1	Horizontal	248	2.89	-	37.72	15.19	49.65

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 17.5
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	82.98	88.20	-5.22	74.20	3	Vertical	88	1.36	-	34.99	6.60	32.81
RMS	5.9238G	67.68	68.20	-0.52	58.89	3	Vertical	88	1.36	-	35.00	6.60	32.81
PK	5.9678G	113.67	Inf	-Inf	104.73	3	Vertical	88	1.36	-	35.17	6.60	32.83
RMS	5.9738G	103.46	Inf	-Inf	94.49	3	Vertical	88	1.36	-	35.20	6.60	32.83

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 17.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.94368G	58.59	74.00	-15.41	42.66	3	Vertical	3	1.05	-	38.50	8.99	31.56
AV	11.94086G	46.04	54.00	-7.96	30.11	3	Vertical	3	1.05	-	38.50	8.99	31.56

802.11ax HEW40_Nss1,(MCS0)_1TX

5965MHz_TnomVnom




EUT Y_1TX
Setting 17.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.93708G	64.57	74.00	-9.43	48.66	3	Horizontal	206	1.65	-	38.50	8.98	31.57
AV	11.92946G	51.81	54.00	-2.19	35.90	3	Horizontal	206	1.65	-	38.50	8.98	31.57

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.787G	58.07	88.20	-30.13	51.96	3	Vertical	74	1.80	-	34.20	7.40	35.49
RMS	5.919G	47.53	68.20	-20.67	40.89	3	Vertical	74	1.80	-	34.68	7.52	35.56
PK	6.209G	115.48	Inf	-Inf	108.14	3	Vertical	74	1.80	-	35.16	7.70	35.52
RMS	6.207G	105.66	Inf	-Inf	98.31	3	Vertical	74	1.80	-	35.17	7.70	35.52

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.40604G	57.89	74.00	-16.11	43.29	3	Vertical	284	1.80	-	38.89	11.12	35.41
AV	12.41348G	43.60	54.00	-10.40	28.99	3	Vertical	284	1.80	-	38.89	11.13	35.41

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.41066G	62.64	74.00	-11.36	48.03	3	Horizontal	207	2.36	-	38.89	11.13	35.41
AV	12.4058G	49.00	54.00	-5.00	34.40	3	Horizontal	207	2.36	-	38.89	11.12	35.41

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.61254G	46.10	83.54	-37.44	43.39	1	Vertical	1	1.38	-	37.75	14.95	49.99
AV	18.61098G	31.91	63.54	-31.63	29.20	1	Vertical	1	1.38	-	37.76	14.94	49.99

802.11ax HEW40_Nss1,(MCS0)_1TX

6205MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.618G	45.18	83.54	-38.36	42.46	1	Horizontal	238	2.12	-	37.75	14.95	49.98
AV	18.61074G	31.80	63.54	-31.74	29.09	1	Horizontal	238	2.12	-	37.76	14.94	49.99

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7586G	57.85	88.20	-30.35	51.73	3	Vertical	70	1.80	-	34.20	7.40	35.48
RMS	5.9058G	47.43	68.20	-20.77	40.85	3	Vertical	70	1.80	-	34.62	7.51	35.55
PK	6.4082G	114.78	Inf	-Inf	107.63	3	Vertical	70	1.80	-	34.87	7.72	35.44
RMS	6.4018G	105.53	Inf	-Inf	98.38	3	Vertical	70	1.80	-	34.89	7.70	35.44
PK	7.205G	60.46	88.20	-27.74	51.36	3	Vertical	70	1.80	-	36.43	8.21	35.54
RMS	7.205G	50.13	68.20	-18.07	41.03	3	Vertical	70	1.80	-	36.43	8.21	35.54

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.80382G	57.09	88.20	-31.11	41.04	3	Vertical	228	1.87	-	39.30	11.44	34.69
RMS	12.80574G	43.65	68.20	-24.55	27.59	3	Vertical	228	1.87	-	39.31	11.44	34.69

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8136G	62.54	88.20	-25.66	46.45	3	Horizontal	206	1.79	-	39.31	11.45	34.67
RMS	12.80586G	48.71	68.20	-19.49	32.65	3	Horizontal	206	1.79	-	39.31	11.44	34.69

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.21434G	46.91	83.54	-36.63	43.62	1	Vertical	182	2.33	-	37.74	15.19	49.64
AV	19.22478G	32.75	63.54	-30.79	29.47	1	Vertical	182	2.33	-	37.73	15.19	49.64

802.11ax HEW40_Nss1,(MCS0)_1TX

6405MHz_TnomVnom




EUT Y_1TX
Setting 18.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.22958G	46.20	83.54	-37.34	42.94	1	Horizontal	266	1.32	-	37.72	15.19	49.65
AV	19.22538G	32.88	63.54	-30.66	29.61	1	Horizontal	266	1.32	-	37.73	15.19	49.65

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.921G	81.07	88.20	-7.13	72.30	3	Vertical	88	1.47	-	34.98	6.60	32.81
RMS	5.923G	67.50	68.20	-0.70	58.72	3	Vertical	88	1.47	-	34.99	6.60	32.81
PK	6.018G	110.53	Inf	-Inf	101.48	3	Vertical	88	1.47	-	35.26	6.63	32.84
RMS	6.019G	100.33	Inf	-Inf	91.28	3	Vertical	88	1.47	-	35.26	6.63	32.84

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.97282G	58.40	74.00	-15.60	42.46	3	Vertical	213	1.80	-	38.50	8.99	31.55
AV	11.96712G	48.85	54.00	-5.15	32.91	3	Vertical	213	1.80	-	38.50	8.99	31.55

802.11ax HEW80_Nss1,(MCS0)_1TX

5985MHz_TnomVnom




EUT Y_1TX
Setting 16.75
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.98476G	63.18	74.00	-10.82	47.23	3	Horizontal	211	1.79	-	38.50	9.00	31.55
AV	11.9841G	53.97	54.00	-0.03	38.02	3	Horizontal	211	1.79	-	38.50	9.00	31.55

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.915G	60.16	88.20	-28.04	53.55	3	Vertical	70	1.74	-	34.66	7.51	35.56
RMS	5.921G	47.95	68.20	-20.25	41.31	3	Vertical	70	1.74	-	34.68	7.52	35.56
PK	6.219G	112.92	Inf	-Inf	105.61	3	Vertical	70	1.74	-	35.12	7.70	35.51
RMS	6.221G	103.30	Inf	-Inf	95.99	3	Vertical	70	1.74	-	35.12	7.70	35.51

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.45396G	56.53	74.00	-17.47	41.92	3	Vertical	283	2.10	-	38.85	11.16	35.40
AV	12.45678G	45.75	54.00	-8.25	31.14	3	Vertical	283	2.10	-	38.84	11.17	35.40

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.46218G	60.28	74.00	-13.72	45.67	3	Horizontal	204	2.18	-	38.84	11.17	35.40
AV	12.44568G	49.46	54.00	-4.54	34.85	3	Horizontal	204	2.18	-	38.85	11.16	35.40

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.66504G	44.67	83.54	-38.87	41.90	1	Vertical	91	1.03	-	37.73	14.97	49.93
AV	18.66606G	34.01	63.54	-29.53	31.24	1	Vertical	91	1.03	-	37.73	14.97	49.93

802.11ax HEW80_Nss1,(MCS0)_1TX

6225MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.66114G	44.63	83.54	-38.91	41.87	1	Horizontal	230	2.67	-	37.74	14.96	49.94
AV	18.66126G	34.51	63.54	-29.03	31.75	1	Horizontal	230	2.67	-	37.74	14.96	49.94

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8104G	58.14	88.20	-30.06	52.02	3	Vertical	69	1.80	-	34.22	7.41	35.51
RMS	5.909G	47.49	68.20	-20.71	40.89	3	Vertical	69	1.80	-	34.64	7.51	35.55
PK	6.385G	109.70	Inf	-Inf	102.55	3	Vertical	69	1.80	-	34.90	7.70	35.45
RMS	6.3884G	100.43	Inf	-Inf	93.27	3	Vertical	69	1.80	-	34.90	7.70	35.44
PK	7.2316G	60.19	88.20	-28.01	50.89	3	Vertical	69	1.80	-	36.59	8.26	35.55
RMS	7.235G	50.36	68.20	-17.84	41.03	3	Vertical	69	1.80	-	36.61	8.27	35.55

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.77396G	55.01	88.20	-33.19	39.10	3	Vertical	208	2.23	-	39.25	11.42	34.76
RMS	12.77744G	44.28	68.20	-23.92	28.36	3	Vertical	208	2.23	-	39.25	11.42	34.75

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.76112G	55.65	88.20	-32.55	39.81	3	Horizontal	99	2.36	-	39.22	11.41	34.79
RMS	12.77774G	44.49	68.20	-23.71	28.56	3	Horizontal	99	2.36	-	39.26	11.42	34.75

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.1628G	45.64	83.54	-37.90	42.30	1	Vertical	145	1.31	-	37.80	15.17	49.63
AV	19.15332G	35.57	63.54	-27.97	32.22	1	Vertical	145	1.31	-	37.82	15.16	49.63

802.11ax HEW80_Nss1,(MCS0)_1TX

6385MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.1412G	45.59	83.54	-37.95	42.23	1	Horizontal	305	2.85	-	37.83	15.16	49.63
AV	19.15494G	34.83	63.54	-28.71	31.49	1	Horizontal	305	2.85	-	37.81	15.16	49.63

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.901G	83.45	88.20	-4.75	74.75	3	Vertical	89	1.48	-	34.90	6.60	32.80
RMS	5.907G	67.57	68.20	-0.63	58.84	3	Vertical	89	1.48	-	34.93	6.60	32.80
PK	6G	105.45	Inf	-Inf	96.39	3	Vertical	89	1.48	-	35.30	6.60	32.84
RMS	6.03G	96.16	Inf	-Inf	87.12	3	Vertical	89	1.48	-	35.24	6.64	32.84

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.05492G	59.15	74.00	-14.85	43.13	3	Vertical	222	1.80	-	38.55	9.02	31.55
AV	12.03908G	48.97	54.00	-5.03	32.95	3	Vertical	222	1.80	-	38.54	9.02	31.54

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.06206G	61.65	74.00	-12.35	45.61	3	Horizontal	210	1.80	-	38.56	9.03	31.55
AV	12.06308G	53.47	54.00	-0.53	37.43	3	Horizontal	210	1.80	-	38.56	9.03	31.55

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.0747G	44.71	83.54	-38.83	42.61	1	Vertical	111	2.76	-	37.64	14.73	50.27
AV	18.06408G	35.46	63.54	-28.08	33.35	1	Vertical	111	2.76	-	37.65	14.73	50.27

802.11ax HEW160_Nss1,(MCS0)_1TX

6025MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.0675G	45.55	83.54	-37.99	43.44	1	Horizontal	73	1.67	-	37.65	14.73	50.27
AV	18.08466G	35.34	63.54	-28.20	33.25	1	Horizontal	73	1.67	-	37.63	14.73	50.27

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.919G	73.05	88.20	-15.15	66.41	3	Vertical	69	1.76	-	34.68	7.52	35.56
RMS	5.921G	56.60	68.20	-11.60	49.96	3	Vertical	69	1.76	-	34.68	7.52	35.56
PK	6.181G	110.35	Inf	-Inf	103.07	3	Vertical	69	1.76	-	35.12	7.69	35.53
RMS	6.189G	100.93	Inf	-Inf	93.60	3	Vertical	69	1.76	-	35.16	7.69	35.52

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.37942G	56.10	74.00	-17.90	41.53	3	Vertical	281	1.76	-	38.88	11.10	35.41
AV	12.3811G	45.42	54.00	-8.58	30.85	3	Vertical	281	1.76	-	38.88	11.10	35.41

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3838G	61.22	74.00	-12.78	46.64	3	Horizontal	206	2.30	-	38.88	11.11	35.41
AV	12.38134G	50.29	54.00	-3.71	35.71	3	Horizontal	206	2.30	-	38.88	11.11	35.41

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5559G	45.79	83.54	-37.75	43.13	1	Vertical	180	2.82	-	37.78	14.92	50.04
AV	18.54132G	34.73	63.54	-28.81	32.09	1	Vertical	180	2.82	-	37.78	14.92	50.06

802.11ax HEW160_Nss1,(MCS0)_1TX

6185MHz_TnomVnom




EUT Y_1TX
Setting 23
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.55782G	45.68	83.54	-37.86	43.02	1	Horizontal	89	1.79	-	37.78	14.92	50.04
AV	18.55242G	34.93	63.54	-28.61	32.28	1	Horizontal	89	1.79	-	37.78	14.92	50.05

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.919G	61.27	88.20	-26.93	54.63	3	Vertical	69	1.73	-	34.68	7.52	35.56
RMS	5.922G	48.02	68.20	-20.18	41.37	3	Vertical	69	1.73	-	34.69	7.52	35.56
PK	6.342G	107.81	Inf	-Inf	100.65	3	Vertical	69	1.73	-	34.92	7.70	35.46
RMS	6.342G	98.53	Inf	-Inf	91.37	3	Vertical	69	1.73	-	34.92	7.70	35.46

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.68868G	55.63	74.00	-18.37	40.17	3	Vertical	48	1.20	-	39.07	11.35	34.96
AV	12.68676G	45.59	54.00	-8.41	30.14	3	Vertical	48	1.20	-	39.06	11.35	34.96

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.69356G	56.31	74.00	-17.69	40.82	3	Horizontal	25	2.75	-	39.08	11.35	34.94
AV	12.6912G	44.67	54.00	-9.33	29.20	3	Horizontal	25	2.75	-	39.07	11.35	34.95

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.038G	46.13	83.54	-37.41	42.67	1	Vertical	73	2.70	-	37.95	15.12	49.61
AV	19.03002G	36.03	63.54	-27.51	32.57	1	Vertical	73	2.70	-	37.96	15.11	49.61

802.11ax HEW160_Nss1,(MCS0)_1TX

6345MHz_TnomVnom



EUT Y_1TX
Setting 15
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.02096G	46.15	83.54	-37.39	42.67	1	Horizontal	294	2.32	-	37.97	15.11	49.60
AV	19.02996G	35.93	63.54	-27.61	32.47	1	Horizontal	294	2.32	-	37.96	15.11	49.61

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	Pass	AV	11.9112G	53.86	54.00	-0.14	3	Horizontal	220	1.80	-

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9242G	80.87	88.20	-7.33	72.08	3	Vertical	48	1.49	-	35.00	6.60	32.81
RMS	5.924G	63.69	68.20	-4.51	54.90	3	Vertical	48	1.49	-	35.00	6.60	32.81
PK	5.9544G	120.66	Inf	-Inf	111.76	3	Vertical	48	1.49	-	35.12	6.60	32.82
RMS	5.9582G	109.56	Inf	-Inf	100.65	3	Vertical	48	1.49	-	35.13	6.60	32.82

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	66.47	88.20	-21.73	57.68	3	Horizontal	45	2.30	-	35.00	6.60	32.81
RMS	5.9232G	52.98	68.20	-15.22	44.20	3	Horizontal	45	2.30	-	34.99	6.60	32.81
PK	5.9546G	115.08	Inf	-Inf	106.18	3	Horizontal	45	2.30	-	35.12	6.60	32.82
RMS	5.96G	103.79	Inf	-Inf	94.87	3	Horizontal	45	2.30	-	35.14	6.60	32.82

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9254G	61.87	74.00	-12.13	45.96	3	Vertical	55	1.80	-	38.50	8.98	31.57
AV	11.9084G	48.19	54.00	-5.81	32.29	3	Vertical	55	1.80	-	38.50	8.98	31.58

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.916G	68.77	74.00	-5.23	52.86	3	Horizontal	220	1.80	-	38.50	8.98	31.57
AV	11.9112G	53.86	54.00	-0.14	37.96	3	Horizontal	220	1.80	-	38.50	8.98	31.58

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.6126G	62.29	88.20	-25.91	55.73	3	Vertical	125	1.98	-	34.57	7.40	35.41
RMS	5.545G	50.33	68.20	-17.87	43.75	3	Vertical	125	1.98	-	34.60	7.35	35.37
PK	6.1976G	116.53	Inf	-Inf	109.16	3	Vertical	125	1.98	-	35.19	7.70	35.52
RMS	6.195G	104.87	Inf	-Inf	97.51	3	Vertical	125	1.98	-	35.18	7.70	35.52

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.6282G	61.38	88.20	-26.82	54.85	3	Horizontal	360	1.89	-	34.54	7.40	35.41
RMS	5.6204G	50.29	68.20	-17.91	43.74	3	Horizontal	360	1.89	-	34.56	7.40	35.41
PK	6.195G	117.18	Inf	-Inf	109.82	3	Horizontal	360	1.89	-	35.18	7.70	35.52
RMS	6.195G	104.18	Inf	-Inf	96.82	3	Horizontal	360	1.89	-	35.18	7.70	35.52

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3939G	62.14	74.00	-11.86	47.54	3	Vertical	234	1.79	-	38.89	11.12	35.41
AV	12.39084G	47.29	54.00	-6.71	32.70	3	Vertical	234	1.79	-	38.89	11.11	35.41

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39036G	64.95	74.00	-9.05	50.36	3	Horizontal	207	1.80	-	38.89	11.11	35.41
AV	12.38802G	51.39	54.00	-2.61	36.80	3	Horizontal	207	1.80	-	38.89	11.11	35.41

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59568G	49.36	83.54	-34.18	46.66	1	Vertical	45	1.02	-	37.76	14.94	50.00
AV	18.59952G	34.47	63.54	-29.07	31.77	1	Vertical	45	1.02	-	37.76	14.94	50.00

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59598G	48.40	83.54	-35.14	45.70	1	Horizontal	74	1.44	-	37.76	14.94	50.00
AV	18.58782G	34.44	63.54	-29.10	31.75	1	Horizontal	74	1.44	-	37.76	14.94	50.01

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8522G	61.96	88.20	-26.24	55.73	3	Vertical	328	2.08	-	34.31	7.45	35.53
RMS	5.925G	50.25	68.20	-17.95	43.58	3	Vertical	328	2.08	-	34.70	7.53	35.56
PK	6.415G	118.55	Inf	-Inf	111.41	3	Vertical	328	2.08	-	34.84	7.73	35.43
RMS	6.415G	105.58	Inf	-Inf	98.44	3	Vertical	328	2.08	-	34.84	7.73	35.43

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8662G	61.06	88.20	-27.14	54.72	3	Horizontal	360	1.80	-	34.40	7.47	35.53
RMS	5.9222G	50.21	68.20	-17.99	43.56	3	Horizontal	360	1.80	-	34.69	7.52	35.56
PK	6.415G	116.14	Inf	-Inf	109.00	3	Horizontal	360	1.80	-	34.84	7.73	35.43
RMS	6.415G	104.82	Inf	-Inf	97.68	3	Horizontal	360	1.80	-	34.84	7.73	35.43

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83084G	61.58	88.20	-26.62	45.42	3	Vertical	238	1.74	-	39.33	11.46	34.63
RMS	12.83072G	48.07	68.20	-20.13	31.91	3	Vertical	238	1.74	-	39.33	11.46	34.63

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83378G	65.64	88.20	-22.56	49.46	3	Horizontal	208	1.80	-	39.33	11.47	34.62
RMS	12.83144G	51.42	68.20	-16.78	35.25	3	Horizontal	208	1.80	-	39.33	11.47	34.63

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2339G	48.65	83.54	-34.89	45.39	1	Vertical	242	2.72	-	37.72	15.19	49.65
AV	19.23468G	35.10	63.54	-28.44	31.84	1	Vertical	242	2.72	-	37.72	15.19	49.65

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.25688G	49.38	83.54	-34.16	46.12	1	Horizontal	159	2.60	-	37.71	15.20	49.65
AV	19.2324G	35.11	63.54	-28.43	31.85	1	Horizontal	159	2.60	-	37.72	15.19	49.65

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 17.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	84.82	88.20	-3.38	76.03	3	Vertical	48	1.44	-	35.00	6.60	32.81
RMS	5.925G	67.26	68.20	-0.94	58.47	3	Vertical	48	1.44	-	35.00	6.60	32.81
PK	5.9734G	110.78	Inf	-Inf	101.82	3	Vertical	48	1.44	-	35.19	6.60	32.83
RMS	5.9726G	100.87	Inf	-Inf	91.91	3	Vertical	48	1.44	-	35.19	6.60	32.83

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 17.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	85.18	88.20	-3.02	76.39	3	Horizontal	33	2.32	-	35.00	6.60	32.81
RMS	5.9222G	64.09	68.20	-4.11	55.31	3	Horizontal	33	2.32	-	34.99	6.60	32.81
PK	5.949G	111.96	Inf	-Inf	103.08	3	Horizontal	33	2.32	-	35.10	6.60	32.82
RMS	5.9762G	98.70	Inf	-Inf	89.73	3	Horizontal	33	2.32	-	35.20	6.60	32.83

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 17.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.93132G	63.36	74.00	-10.64	47.45	3	Vertical	146	2.21	-	38.50	8.98	31.57
AV	11.92864G	48.43	54.00	-5.57	32.52	3	Vertical	146	2.21	-	38.50	8.98	31.57
PK	17.88452G	65.43	74.00	-8.57	42.29	3	Vertical	221	1.98	-	42.74	11.07	30.67
AV	17.89532G	50.18	54.00	-3.82	27.00	3	Vertical	221	1.98	-	42.78	11.07	30.67

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 17.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.93116G	63.07	74.00	-10.93	47.16	3	Horizontal	69	1.40	-	38.50	8.98	31.57
AV	11.92856G	48.45	54.00	-5.55	32.54	3	Horizontal	69	1.40	-	38.50	8.98	31.57
PK	17.8624G	62.78	74.00	-11.22	39.73	3	Horizontal	125	1.68	-	42.65	11.06	30.66
AV	17.86351G	48.66	54.00	-5.34	25.61	3	Horizontal	125	1.68	-	42.65	11.06	30.66

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.5526G	61.47	88.20	-26.73	54.90	3	Vertical	222	1.20	-	34.60	7.35	35.38
RMS	5.6086G	50.23	68.20	-17.97	43.65	3	Vertical	222	1.20	-	34.58	7.40	35.40
PK	6.2022G	112.18	Inf	-Inf	104.81	3	Vertical	222	1.20	-	35.19	7.70	35.52
RMS	6.2078G	101.88	Inf	-Inf	94.53	3	Vertical	222	1.20	-	35.17	7.70	35.52

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.673G	61.71	88.20	-26.49	55.34	3	Horizontal	360	1.80	-	34.41	7.40	35.44
RMS	5.6114G	50.19	68.20	-18.01	43.62	3	Horizontal	360	1.80	-	34.58	7.40	35.41
PK	6.1994G	111.07	Inf	-Inf	103.69	3	Horizontal	360	1.80	-	35.20	7.70	35.52
RMS	6.2022G	99.89	Inf	-Inf	92.52	3	Horizontal	360	1.80	-	35.19	7.70	35.52

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.40352G	58.77	74.00	-15.23	44.16	3	Vertical	233	1.80	-	38.90	11.12	35.41
AV	12.40604G	44.65	54.00	-9.35	30.05	3	Vertical	233	1.80	-	38.89	11.12	35.41

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.4109G	62.35	74.00	-11.65	47.74	3	Horizontal	208	1.78	-	38.89	11.13	35.41
AV	12.4055G	47.79	54.00	-6.21	33.19	3	Horizontal	208	1.78	-	38.89	11.12	35.41

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.60648G	49.32	83.54	-34.22	46.61	1	Vertical	57	2.47	-	37.76	14.94	49.99
AV	18.61434G	34.49	63.54	-29.05	31.78	1	Vertical	57	2.47	-	37.75	14.95	49.99

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.60498G	49.31	83.54	-34.23	46.61	1	Horizontal	172	1.09	-	37.76	14.94	50.00
AV	18.60492G	34.45	63.54	-29.09	31.75	1	Horizontal	172	1.09	-	37.76	14.94	50.00

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.6146G	61.72	88.20	-26.48	55.16	3	Vertical	324	2.19	-	34.57	7.40	35.41
RMS	5.6114G	50.27	68.20	-17.93	43.70	3	Vertical	324	2.19	-	34.58	7.40	35.41
PK	6.405G	113.85	Inf	-Inf	106.70	3	Vertical	324	2.19	-	34.88	7.71	35.44
RMS	6.4018G	102.52	Inf	-Inf	95.37	3	Vertical	324	2.19	-	34.89	7.70	35.44
PK	7.157G	65.97	88.20	-22.23	57.16	3	Vertical	324	2.19	-	36.14	8.20	35.53
RMS	7.157G	54.87	68.20	-13.33	46.06	3	Vertical	324	2.19	-	36.14	8.20	35.53

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7554G	62.76	88.20	-25.44	56.64	3	Horizontal	360	1.80	-	34.20	7.40	35.48
RMS	5.605G	50.25	68.20	-17.95	43.66	3	Horizontal	360	1.80	-	34.59	7.40	35.40
PK	6.405G	112.91	Inf	-Inf	105.76	3	Horizontal	360	1.80	-	34.88	7.71	35.44
RMS	6.4082G	101.95	Inf	-Inf	94.80	3	Horizontal	360	1.80	-	34.87	7.72	35.44
PK	7.1378G	66.17	88.20	-22.03	57.47	3	Horizontal	360	1.80	-	36.03	8.20	35.53
RMS	7.1634G	54.86	68.20	-13.34	46.01	3	Horizontal	360	1.80	-	36.18	8.20	35.53

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8112G	59.30	88.20	-28.90	43.21	3	Vertical	178	1.44	-	39.31	11.45	34.67
RMS	12.80784G	45.40	68.20	-22.80	29.32	3	Vertical	178	1.44	-	39.31	11.45	34.68

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.81474G	58.98	88.20	-29.22	42.89	3	Horizontal	181	2.33	-	39.31	11.45	34.67
RMS	12.80244G	45.38	68.20	-22.82	29.33	3	Horizontal	181	2.33	-	39.30	11.44	34.69

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.21854G	49.77	83.54	-33.77	46.48	1	Vertical	313	2.57	-	37.74	15.19	49.64
AV	19.22556G	35.06	63.54	-28.48	31.79	1	Vertical	313	2.57	-	37.73	15.19	49.65

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2219G	49.21	83.54	-34.33	45.93	1	Horizontal	230	1.19	-	37.73	15.19	49.64
AV	19.22364G	35.07	63.54	-28.47	31.79	1	Horizontal	230	1.19	-	37.73	15.19	49.64

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 15.5
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9226G	79.52	88.20	-8.68	70.74	3	Vertical	344	1.80	-	34.99	6.60	32.81
RMS	5.9226G	66.07	68.20	-2.13	57.29	3	Vertical	344	1.80	-	34.99	6.60	32.81
PK	6.0006G	108.03	Inf	-Inf	98.97	3	Vertical	344	1.80	-	35.30	6.60	32.84
RMS	5.9598G	97.97	Inf	-Inf	89.05	3	Vertical	344	1.80	-	35.14	6.60	32.82

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 15.5
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9226G	82.18	88.20	-6.02	73.40	3	Horizontal	341	1.15	-	34.99	6.60	32.81
RMS	5.9232G	68.03	68.20	-0.17	59.25	3	Horizontal	341	1.15	-	34.99	6.60	32.81
PK	5.973G	108.41	Inf	-Inf	99.45	3	Horizontal	341	1.15	-	35.19	6.60	32.83
RMS	5.9688G	96.56	Inf	-Inf	87.61	3	Horizontal	341	1.15	-	35.18	6.60	32.83

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 15.5
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.97176G	58.67	74.00	-15.33	42.73	3	Vertical	70	1.30	-	38.50	8.99	31.55
AV	11.96658G	48.36	54.00	-5.64	32.42	3	Vertical	70	1.30	-	38.50	8.99	31.55

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 15.5
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.97226G	58.52	74.00	-15.48	42.58	3	Horizontal	181	1.74	-	38.50	8.99	31.55
AV	11.96586G	48.54	54.00	-5.46	32.60	3	Horizontal	181	1.74	-	38.50	8.99	31.55

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.769G	64.52	88.20	-23.68	58.40	3	Vertical	325	1.96	-	34.20	7.40	35.48
RMS	5.607G	50.17	68.20	-18.03	43.58	3	Vertical	325	1.96	-	34.59	7.40	35.40
PK	6.24G	109.74	Inf	-Inf	102.50	3	Vertical	325	1.96	-	35.04	7.70	35.50
RMS	6.222G	99.35	Inf	-Inf	92.05	3	Vertical	325	1.96	-	35.11	7.70	35.51

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.781G	61.39	88.20	-26.81	55.28	3	Horizontal	358	1.84	-	34.20	7.40	35.49
RMS	5.61G	50.22	68.20	-17.98	43.65	3	Horizontal	358	1.84	-	34.58	7.40	35.41
PK	6.228G	108.96	Inf	-Inf	101.68	3	Horizontal	358	1.84	-	35.09	7.70	35.51
RMS	6.228G	96.80	Inf	-Inf	89.52	3	Horizontal	358	1.84	-	35.09	7.70	35.51

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.43776G	59.52	74.00	-14.48	44.91	3	Vertical	0	2.98	-	38.86	11.15	35.40
AV	12.44736G	47.98	54.00	-6.02	33.37	3	Vertical	0	2.98	-	38.85	11.16	35.40

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.46218G	60.67	74.00	-13.33	46.06	3	Horizontal	200	1.80	-	38.84	11.17	35.40
AV	12.44574G	49.32	54.00	-4.68	34.71	3	Horizontal	200	1.80	-	38.85	11.16	35.40

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.68724G	47.77	83.54	-35.77	44.98	1	Vertical	29	2.20	-	37.73	14.97	49.91
AV	18.67092G	36.92	63.54	-26.62	34.15	1	Vertical	29	2.20	-	37.73	14.97	49.93

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.68946G	47.83	83.54	-35.71	45.04	1	Horizontal	290	1.42	-	37.72	14.98	49.91
AV	18.66492G	36.83	63.54	-26.71	34.07	1	Horizontal	290	1.42	-	37.73	14.97	49.94

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	61.46	88.20	-26.74	54.81	3	Vertical	329	2.14	-	34.69	7.52	35.56
RMS	5.925G	50.39	68.20	-17.81	43.73	3	Vertical	329	2.14	-	34.70	7.52	35.56
PK	6.3878G	111.06	Inf	-Inf	103.90	3	Vertical	329	2.14	-	34.90	7.70	35.44
RMS	6.3878G	98.84	Inf	-Inf	91.68	3	Vertical	329	2.14	-	34.90	7.70	35.44

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7578G	63.54	88.20	-24.66	57.42	3	Horizontal	360	1.86	-	34.20	7.40	35.48
RMS	5.9062G	50.27	68.20	-17.93	43.69	3	Horizontal	360	1.86	-	34.62	7.51	35.55
PK	6.3878G	110.10	Inf	-Inf	102.94	3	Horizontal	360	1.86	-	34.90	7.70	35.44
RMS	6.3878G	97.94	Inf	-Inf	90.78	3	Horizontal	360	1.86	-	34.90	7.70	35.44

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.78242G	59.28	88.20	-28.92	43.33	3	Vertical	223	1.99	-	39.26	11.43	34.74
RMS	12.76814G	48.39	68.20	-19.81	32.51	3	Vertical	223	1.99	-	39.24	11.41	34.77

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.76118G	58.98	88.20	-29.22	43.14	3	Horizontal	353	1.74	-	39.22	11.41	34.79
RMS	12.75608G	48.41	68.20	-19.79	32.60	3	Horizontal	353	1.74	-	39.21	11.40	34.80

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.1604G	48.82	83.54	-34.72	45.48	1	Vertical	297	2.95	-	37.81	15.16	49.63
AV	19.1517G	38.45	63.54	-25.09	35.10	1	Vertical	297	2.95	-	37.82	15.16	49.63

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.16958G	48.72	83.54	-34.82	45.38	1	Horizontal	25	1.97	-	37.80	15.17	49.63
AV	19.15644G	38.12	63.54	-25.42	34.78	1	Horizontal	25	1.97	-	37.81	15.16	49.63

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 14.75
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8866G	82.53	88.20	-5.67	73.85	3	Vertical	33	1.20	-	34.87	6.60	32.79
RMS	5.9226G	67.71	68.20	-0.49	58.93	3	Vertical	33	1.20	-	34.99	6.60	32.81
PK	6.0002G	105.28	Inf	-Inf	96.22	3	Vertical	33	1.20	-	35.30	6.60	32.84
RMS	6.0298G	94.76	Inf	-Inf	85.72	3	Vertical	33	1.20	-	35.24	6.64	32.84

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 14.75
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8866G	84.10	88.20	-4.10	75.42	3	Horizontal	342	1.06	-	34.87	6.60	32.79
RMS	5.925G	67.18	68.20	-1.02	58.39	3	Horizontal	342	1.06	-	35.00	6.60	32.81
PK	6.0002G	107.52	Inf	-Inf	98.46	3	Horizontal	342	1.06	-	35.30	6.60	32.84
RMS	6.0298G	96.52	Inf	-Inf	87.48	3	Horizontal	342	1.06	-	35.24	6.64	32.84

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 14.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.0538G	58.83	74.00	-15.17	42.81	3	Vertical	146	1.45	-	38.55	9.02	31.55
AV	12.05058G	48.90	54.00	-5.10	32.88	3	Vertical	146	1.45	-	38.55	9.02	31.55

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 14.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.0501G	59.20	74.00	-14.80	43.18	3	Horizontal	283	1.26	-	38.55	9.02	31.55
AV	12.048G	49.22	54.00	-4.78	33.19	3	Horizontal	283	1.26	-	38.55	9.02	31.54

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 14.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.0751G	44.53	83.54	-39.01	42.43	1	Vertical	300	1.52	-	37.64	14.73	50.27
AV	18.07326G	34.78	63.54	-28.76	32.68	1	Vertical	300	1.52	-	37.64	14.73	50.27

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 14.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.073G	44.37	83.54	-39.17	42.27	1	Horizontal	268	1.51	-	37.64	14.73	50.27
AV	18.0704G	34.64	63.54	-28.90	32.54	1	Horizontal	268	1.51	-	37.64	14.73	50.27

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9218G	68.33	88.20	-19.87	61.68	3	Vertical	226	1.70	-	34.69	7.52	35.56
RMS	5.919G	52.28	68.20	-15.92	45.64	3	Vertical	226	1.70	-	34.68	7.52	35.56
PK	6.1822G	108.44	Inf	-Inf	101.15	3	Vertical	226	1.70	-	35.13	7.69	35.53
RMS	6.1794G	97.97	Inf	-Inf	90.69	3	Vertical	226	1.70	-	35.12	7.69	35.53

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9218G	66.75	88.20	-21.45	60.10	3	Horizontal	-0	2.12	-	34.69	7.52	35.56
RMS	5.919G	51.33	68.20	-16.87	44.69	3	Horizontal	-0	2.12	-	34.68	7.52	35.56
PK	6.1878G	107.12	Inf	-Inf	99.80	3	Horizontal	-0	2.12	-	35.15	7.69	35.52
RMS	6.1822G	96.06	Inf	-Inf	88.77	3	Horizontal	-0	2.12	-	35.13	7.69	35.53

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.35608G	59.05	74.00	-14.95	44.53	3	Vertical	287	1.80	-	38.86	11.08	35.42
AV	12.36202G	48.04	54.00	-5.96	33.51	3	Vertical	287	1.80	-	38.86	11.09	35.42

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.37018G	59.60	74.00	-14.40	45.05	3	Horizontal	16	1.84	-	38.87	11.10	35.42
AV	12.35704G	48.49	54.00	-5.51	33.96	3	Horizontal	16	1.84	-	38.86	11.09	35.42

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.54786G	48.40	83.54	-35.14	45.75	1	Vertical	61	2.66	-	37.78	14.92	50.05
AV	18.55584G	37.44	63.54	-26.10	34.78	1	Vertical	61	2.66	-	37.78	14.92	50.04

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.55512G	48.84	83.54	-34.70	46.18	1	Horizontal	182	1.91	-	37.78	14.92	50.04
AV	18.5673G	37.78	63.54	-25.76	35.11	1	Horizontal	182	1.91	-	37.77	14.93	50.03

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.757G	61.67	88.20	-26.53	55.55	3	Vertical	333	1.55	-	34.20	7.40	35.48
RMS	5.607G	50.46	68.20	-17.74	43.87	3	Vertical	333	1.55	-	34.59	7.40	35.40
PK	6.348G	104.88	Inf	-Inf	97.74	3	Vertical	333	1.55	-	34.90	7.70	35.46
RMS	6.339G	94.25	Inf	-Inf	87.09	3	Vertical	333	1.55	-	34.92	7.70	35.46

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-B-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.739G	61.46	88.20	-26.74	55.31	3	Horizontal	0	1.80	-	34.22	7.40	35.47
RMS	5.607G	50.36	68.20	-17.84	43.77	3	Horizontal	0	1.80	-	34.59	7.40	35.40
PK	6.342G	104.94	Inf	-Inf	97.78	3	Horizontal	0	1.80	-	34.92	7.70	35.46
RMS	6.339G	94.11	Inf	-Inf	86.95	3	Horizontal	0	1.80	-	34.92	7.70	35.46

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.69378G	59.60	74.00	-14.40	44.10	3	Vertical	334	1.10	-	39.08	11.36	34.94
AV	12.67914G	48.82	54.00	-5.18	33.42	3	Vertical	334	1.10	-	39.04	11.34	34.98

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.68712G	60.19	74.00	-13.81	44.74	3	Horizontal	210	2.44	-	39.06	11.35	34.96
AV	12.68376G	48.80	54.00	-5.20	33.37	3	Horizontal	210	2.44	-	39.05	11.35	34.97

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-B-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.04958G	48.80	83.54	-34.74	45.35	1	Vertical	156	2.84	-	37.94	15.12	49.61
AV	19.04496G	38.01	63.54	-25.53	34.55	1	Vertical	156	2.84	-	37.95	15.12	49.61

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom



EUT Y_2TX
Setting 16
03-B-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.04058G	48.20	83.54	-35.34	44.74	1	Horizontal	178	1.60	-	37.95	15.12	49.61
AV	19.03506G	37.94	63.54	-25.60	34.48	1	Horizontal	178	1.60	-	37.96	15.11	49.61

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20-BF_Nss1,(MCS0)_2TX	Pass	RMS	5.925G	68.11	68.20	-0.09	3	Vertical	44	1.80	-

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 21.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	85.03	88.20	-3.17	76.24	3	Vertical	44	1.80	-	35.00	6.60	32.81
RMS	5.925G	68.11	68.20	-0.09	59.32	3	Vertical	44	1.80	-	35.00	6.60	32.81
PK	5.9558G	120.70	Inf	-Inf	111.80	3	Vertical	44	1.80	-	35.12	6.60	32.82
RMS	5.9558G	112.83	Inf	-Inf	103.93	3	Vertical	44	1.80	-	35.12	6.60	32.82

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 21.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	82.53	88.20	-5.67	73.74	3	Horizontal	348	2.86	-	35.00	6.60	32.81
RMS	5.925G	67.48	68.20	-0.72	58.69	3	Horizontal	348	2.86	-	35.00	6.60	32.81
PK	5.9566G	116.08	Inf	-Inf	107.17	3	Horizontal	348	2.86	-	35.13	6.60	32.82
RMS	5.9618G	107.06	Inf	-Inf	98.13	3	Horizontal	348	2.86	-	35.15	6.60	32.82

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 21.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.91076G	61.62	74.00	-12.38	45.72	3	Vertical	339	1.19	-	38.50	8.98	31.58
AV	11.90836G	48.54	54.00	-5.46	32.64	3	Vertical	339	1.19	-	38.50	8.98	31.58

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 21.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.91374G	61.20	74.00	-12.80	45.29	3	Horizontal	6	2.88	-	38.50	8.98	31.57
AV	11.9082G	48.54	54.00	-5.46	32.64	3	Horizontal	6	2.88	-	38.50	8.98	31.58

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.919G	63.80	88.20	-24.40	55.03	3	Vertical	23	1.80	-	34.98	6.60	32.81
RMS	5.925G	53.20	68.20	-15.00	44.41	3	Vertical	23	1.80	-	35.00	6.60	32.81
PK	6.1962G	119.32	Inf	-Inf	109.80	3	Vertical	23	1.80	-	35.48	6.89	32.85
RMS	6.1962G	107.67	Inf	-Inf	98.15	3	Vertical	23	1.80	-	35.48	6.89	32.85

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9226G	63.53	88.20	-24.67	54.75	3	Horizontal	179	3.00	-	34.99	6.60	32.81
RMS	5.9238G	53.10	68.20	-15.10	44.31	3	Horizontal	179	3.00	-	35.00	6.60	32.81
PK	6.1938G	115.33	Inf	-Inf	105.81	3	Horizontal	179	3.00	-	35.48	6.89	32.85
RMS	6.1962G	103.21	Inf	-Inf	93.69	3	Horizontal	179	3.00	-	35.48	6.89	32.85

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38304G	63.08	74.00	-10.92	46.82	3	Vertical	272	1.80	-	38.67	9.17	31.58
AV	12.3906G	49.56	54.00	-4.44	33.28	3	Vertical	272	1.80	-	38.68	9.18	31.58

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38928G	65.49	74.00	-8.51	49.21	3	Horizontal	210	1.80	-	38.68	9.18	31.58
AV	12.38748G	52.22	54.00	-1.78	35.96	3	Horizontal	210	1.80	-	38.67	9.17	31.58

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58601G	50.22	83.54	-33.32	47.53	1	Vertical	53	2.37	-	37.77	14.93	50.01
AV	18.58801G	36.12	63.54	-27.42	33.43	1	Vertical	53	2.37	-	37.76	14.94	50.01

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58632G	49.96	83.54	-33.58	47.27	1	Horizontal	237	1.62	-	37.77	14.93	50.01
AV	18.58574G	36.64	63.54	-26.90	33.95	1	Horizontal	237	1.62	-	37.77	14.93	50.01

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8942G	63.63	88.20	-24.57	54.94	3	Vertical	304	1.72	-	34.89	6.60	32.80
RMS	5.923G	53.16	68.20	-15.04	44.38	3	Vertical	304	1.72	-	34.99	6.60	32.81
PK	6.415G	118.56	Inf	-Inf	108.88	3	Vertical	304	1.72	-	35.54	7.00	32.86
RMS	6.415G	108.36	Inf	-Inf	98.68	3	Vertical	304	1.72	-	35.54	7.00	32.86

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8534G	63.25	88.20	-24.95	54.62	3	Horizontal	136	1.80	-	34.81	6.60	32.78
RMS	5.925G	53.14	68.20	-15.06	44.35	3	Horizontal	136	1.80	-	35.00	6.60	32.81
PK	6.4174G	110.86	Inf	-Inf	101.19	3	Horizontal	136	1.80	-	35.53	7.00	32.86
RMS	6.415G	101.25	Inf	-Inf	91.57	3	Horizontal	136	1.80	-	35.54	7.00	32.86

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8318G	64.77	88.20	-23.43	47.05	3	Vertical	278	1.79	-	39.23	9.37	30.88
RMS	12.83144G	50.49	68.20	-17.71	32.77	3	Vertical	278	1.79	-	39.23	9.37	30.88

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83384G	66.29	88.20	-21.91	48.56	3	Horizontal	210	1.80	-	39.23	9.38	30.88
RMS	12.82832G	52.55	68.20	-15.65	34.84	3	Horizontal	210	1.80	-	39.23	9.37	30.89

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.24482G	49.87	83.54	-33.67	46.61	1	Vertical	352	1.01	-	37.71	15.20	49.65
AV	19.24241G	36.31	63.54	-27.23	33.05	1	Vertical	352	1.01	-	37.71	15.20	49.65

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.24429G	50.27	83.54	-33.27	47.01	1	Horizontal	5	1.08	-	37.71	15.20	49.65
AV	19.24368G	37.00	63.54	-26.54	33.74	1	Horizontal	5	1.08	-	37.71	15.20	49.65

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 17
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	86.00	88.20	-2.20	77.21	3	Vertical	42	2.12	-	35.00	6.60	32.81
RMS	5.9246G	67.85	68.20	-0.35	59.06	3	Vertical	42	2.12	-	35.00	6.60	32.81
PK	5.9562G	115.39	Inf	-Inf	106.49	3	Vertical	42	2.12	-	35.12	6.60	32.82
RMS	5.9562G	106.41	Inf	-Inf	97.51	3	Vertical	42	2.12	-	35.12	6.60	32.82

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 17
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9238G	77.00	88.20	-11.20	68.21	3	Horizontal	57	1.84	-	35.00	6.60	32.81
RMS	5.925G	60.27	68.20	-7.93	51.48	3	Horizontal	57	1.84	-	35.00	6.60	32.81
PK	5.9502G	106.45	Inf	-Inf	97.57	3	Horizontal	57	1.84	-	35.10	6.60	32.82
RMS	5.9494G	98.22	Inf	-Inf	89.34	3	Horizontal	57	1.84	-	35.10	6.60	32.82

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 17
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.92832G	60.84	74.00	-13.16	44.93	3	Vertical	305	1.89	-	38.50	8.98	31.57
AV	11.92908G	48.55	54.00	-5.45	32.64	3	Vertical	305	1.89	-	38.50	8.98	31.57

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 17
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.93078G	61.58	74.00	-12.42	45.67	3	Horizontal	166	1.53	-	38.50	8.98	31.57
AV	11.9286G	48.55	54.00	-5.45	32.64	3	Horizontal	166	1.53	-	38.50	8.98	31.57

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.862G	64.46	88.20	-23.74	55.82	3	Vertical	318	1.80	-	34.82	6.60	32.78
RMS	5.9236G	52.94	68.20	-15.26	44.16	3	Vertical	318	1.80	-	34.99	6.60	32.81
PK	6.2078G	117.41	Inf	-Inf	107.92	3	Vertical	318	1.80	-	35.44	6.90	32.85
RMS	6.2078G	107.18	Inf	-Inf	97.69	3	Vertical	318	1.80	-	35.44	6.90	32.85

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.883G	63.18	88.20	-25.02	54.50	3	Horizontal	182	2.65	-	34.87	6.60	32.79
RMS	5.9222G	52.94	68.20	-15.26	44.16	3	Horizontal	182	2.65	-	34.99	6.60	32.81
PK	6.2036G	111.62	Inf	-Inf	102.10	3	Horizontal	182	2.65	-	35.47	6.90	32.85
RMS	6.2036G	100.37	Inf	-Inf	90.85	3	Horizontal	182	2.65	-	35.47	6.90	32.85

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.42056G	61.89	74.00	-12.11	45.62	3	Vertical	231	1.79	-	38.66	9.19	31.58
AV	12.40616G	48.68	54.00	-5.32	32.39	3	Vertical	231	1.79	-	38.69	9.18	31.58

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.41084G	64.47	74.00	-9.53	48.19	3	Horizontal	215	1.80	-	38.68	9.18	31.58
AV	12.4058G	50.92	54.00	-3.08	34.63	3	Horizontal	215	1.80	-	38.69	9.18	31.58

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.61329G	50.41	83.54	-33.13	47.70	1	Vertical	23	2.49	-	37.75	14.95	49.99
AV	18.61662G	37.05	63.54	-26.49	34.33	1	Vertical	23	2.49	-	37.75	14.95	49.98

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.61433G	50.25	83.54	-33.29	47.54	1	Horizontal	343	1.80	-	37.75	14.95	49.99
AV	18.61835G	36.16	63.54	-27.38	33.44	1	Horizontal	343	1.80	-	37.75	14.95	49.98

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9034G	64.03	88.20	-24.17	55.32	3	Vertical	325	1.74	-	34.91	6.60	32.80
RMS	5.9226G	53.00	68.20	-15.20	44.22	3	Vertical	325	1.74	-	34.99	6.60	32.81
PK	6.405G	116.83	Inf	-Inf	107.11	3	Vertical	325	1.74	-	35.58	7.00	32.86
RMS	6.4074G	105.63	Inf	-Inf	95.92	3	Vertical	325	1.74	-	35.57	7.00	32.86

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8986G	63.69	88.20	-24.51	54.99	3	Horizontal	144	1.76	-	34.90	6.60	32.80
RMS	5.9226G	52.94	68.20	-15.26	44.16	3	Horizontal	144	1.76	-	34.99	6.60	32.81
PK	6.4074G	109.55	Inf	-Inf	99.84	3	Horizontal	144	1.76	-	35.57	7.00	32.86
RMS	6.4074G	99.81	Inf	-Inf	90.10	3	Horizontal	144	1.76	-	35.57	7.00	32.86

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.80896G	61.13	88.20	-27.07	43.49	3	Vertical	237	1.06	-	39.21	9.36	30.93
RMS	12.80831G	47.58	68.20	-20.62	29.94	3	Vertical	237	1.06	-	39.21	9.36	30.93

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.81266G	61.18	88.20	-27.02	43.52	3	Horizontal	59	2.21	-	39.21	9.37	30.92
RMS	12.80856G	48.24	68.20	-19.96	30.60	3	Horizontal	59	2.21	-	39.21	9.36	30.93

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.21564G	49.93	83.54	-33.61	46.64	1	Vertical	325	2.76	-	37.74	15.19	49.64
AV	19.21786G	36.44	63.54	-27.10	33.15	1	Vertical	325	2.76	-	37.74	15.19	49.64

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2159G	50.62	83.54	-32.92	47.33	1	Horizontal	263	1.28	-	37.74	15.19	49.64
AV	19.21195G	37.06	63.54	-26.48	33.77	1	Horizontal	263	1.28	-	37.75	15.18	49.64

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9162G	83.06	88.20	-5.14	74.31	3	Vertical	41	2.32	-	34.96	6.60	32.81
RMS	5.925G	67.63	68.20	-0.57	58.84	3	Vertical	41	2.32	-	35.00	6.60	32.81
PK	5.9666G	112.41	Inf	-Inf	103.47	3	Vertical	41	2.32	-	35.17	6.60	32.83
RMS	5.9498G	102.61	Inf	-Inf	93.73	3	Vertical	41	2.32	-	35.10	6.60	32.82

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.913G	73.66	88.20	-14.54	64.92	3	Horizontal	56	1.80	-	34.95	6.60	32.81
RMS	5.9234G	60.59	68.20	-7.61	51.81	3	Horizontal	56	1.80	-	34.99	6.60	32.81
PK	5.9666G	102.34	Inf	-Inf	93.40	3	Horizontal	56	1.80	-	35.17	6.60	32.83
RMS	5.9498G	94.34	Inf	-Inf	85.46	3	Horizontal	56	1.80	-	35.10	6.60	32.82

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.974G	61.57	74.00	-12.43	45.63	3	Vertical	247	2.13	-	38.50	8.99	31.55
AV	11.96718G	51.55	54.00	-2.45	35.61	3	Vertical	247	2.13	-	38.50	8.99	31.55

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.97484G	61.15	74.00	-12.85	45.21	3	Horizontal	346	1.65	-	38.50	8.99	31.55
AV	11.97024G	51.47	54.00	-2.53	35.53	3	Horizontal	346	1.65	-	38.50	8.99	31.55

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8974G	63.36	88.20	-24.84	54.67	3	Vertical	321	1.80	-	34.89	6.60	32.80
RMS	5.925G	53.10	68.20	-15.10	44.31	3	Vertical	321	1.80	-	35.00	6.60	32.81
PK	6.2124G	114.89	Inf	-Inf	105.43	3	Vertical	321	1.80	-	35.40	6.91	32.85
RMS	6.2208G	104.34	Inf	-Inf	94.95	3	Vertical	321	1.80	-	35.33	6.91	32.85

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9002G	63.60	88.20	-24.60	54.90	3	Horizontal	142	1.74	-	34.90	6.60	32.80
RMS	5.925G	53.02	68.20	-15.18	44.23	3	Horizontal	142	1.74	-	35.00	6.60	32.81
PK	6.2292G	106.16	Inf	-Inf	96.83	3	Horizontal	142	1.74	-	35.27	6.91	32.85
RMS	6.2194G	96.61	Inf	-Inf	87.21	3	Horizontal	142	1.74	-	35.34	6.91	32.85

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.4661G	61.95	74.00	-12.05	45.76	3	Vertical	235	1.80	-	38.57	9.21	31.59
AV	12.43544G	50.91	54.00	-3.09	34.66	3	Vertical	235	1.80	-	38.63	9.20	31.58

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.46652G	63.07	74.00	-10.93	46.88	3	Horizontal	204	1.80	-	38.57	9.21	31.59
AV	12.45588G	51.98	54.00	-2.02	35.77	3	Horizontal	204	1.80	-	38.59	9.21	31.59

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.67283G	50.38	83.54	-33.16	47.61	1	Vertical	42	2.11	-	37.73	14.97	49.93
AV	18.67746G	39.50	63.54	-24.04	36.72	1	Vertical	42	2.11	-	37.73	14.97	49.92

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.67241G	49.86	83.54	-33.68	47.09	1	Horizontal	317	2.31	-	37.73	14.97	49.93
AV	18.67247G	39.79	63.54	-23.75	37.02	1	Horizontal	317	2.31	-	37.73	14.97	49.93

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.833G	63.55	88.20	-24.65	55.06	3	Vertical	326	1.80	-	34.66	6.60	32.77
RMS	5.9242G	53.01	68.20	-15.19	44.22	3	Vertical	326	1.80	-	35.00	6.60	32.81
PK	6.3874G	113.37	Inf	-Inf	103.72	3	Vertical	326	1.80	-	35.52	6.99	32.86
RMS	6.3874G	102.79	Inf	-Inf	93.14	3	Vertical	326	1.80	-	35.52	6.99	32.86

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8042G	64.72	88.20	-23.48	56.45	3	Horizontal	142	1.72	-	34.43	6.60	32.76
RMS	5.9242G	53.10	68.20	-15.10	44.31	3	Horizontal	142	1.72	-	35.00	6.60	32.81
PK	6.3802G	105.97	Inf	-Inf	96.36	3	Horizontal	142	1.72	-	35.48	6.99	32.86
RMS	6.3826G	96.35	Inf	-Inf	86.72	3	Horizontal	142	1.72	-	35.50	6.99	32.86

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.77153G	60.78	88.20	-27.42	43.30	3	Vertical	286	1.49	-	39.14	9.35	31.01
RMS	12.76842G	50.17	68.20	-18.03	32.70	3	Vertical	286	1.49	-	39.14	9.35	31.02

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.77028G	61.22	88.20	-26.98	43.74	3	Horizontal	2	1.02	-	39.14	9.35	31.01
RMS	12.77295G	50.11	68.20	-18.09	32.62	3	Horizontal	2	1.02	-	39.15	9.35	31.01

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.15801G	50.29	83.54	-33.25	46.95	1	Vertical	220	2.92	-	37.81	15.16	49.63
AV	19.15612G	39.86	63.54	-23.68	36.52	1	Vertical	220	2.92	-	37.81	15.16	49.63

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.15545G	49.91	83.54	-33.63	46.57	1	Horizontal	346	1.68	-	37.81	15.16	49.63
AV	19.15238G	39.93	63.54	-23.61	36.58	1	Horizontal	346	1.68	-	37.82	15.16	49.63

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.89G	82.76	88.20	-5.44	74.08	3	Vertical	58	2.28	-	34.88	6.60	32.80
RMS	5.916G	67.76	68.20	-0.44	59.01	3	Vertical	58	2.28	-	34.96	6.60	32.81
PK	6.03G	107.59	Inf	-Inf	98.55	3	Vertical	58	2.28	-	35.24	6.64	32.84
RMS	6.03G	99.70	Inf	-Inf	90.66	3	Vertical	58	2.28	-	35.24	6.64	32.84

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.89G	75.66	88.20	-12.54	66.98	3	Horizontal	59	1.95	-	34.88	6.60	32.80
RMS	5.9G	61.52	68.20	-6.68	52.82	3	Horizontal	59	1.95	-	34.90	6.60	32.80
PK	6.017G	98.16	Inf	-Inf	89.10	3	Horizontal	59	1.95	-	35.27	6.63	32.84
RMS	6.02G	91.12	Inf	-Inf	82.07	3	Horizontal	59	1.95	-	35.26	6.63	32.84

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.05058G	61.26	74.00	-12.74	45.24	3	Vertical	71	1.55	-	38.55	9.02	31.55
AV	12.04808G	51.64	54.00	-2.36	35.61	3	Vertical	71	1.55	-	38.55	9.02	31.54

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.0453G	61.17	74.00	-12.83	45.14	3	Horizontal	176	2.70	-	38.55	9.02	31.54
AV	12.0461G	51.36	54.00	-2.64	35.33	3	Horizontal	176	2.70	-	38.55	9.02	31.54

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.07278G	48.42	83.54	-35.12	46.32	1	Vertical	128	1.56	-	37.64	14.73	50.27
AV	18.07078G	38.01	63.54	-25.53	35.91	1	Vertical	128	1.56	-	37.64	14.73	50.27

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.07238G	47.13	83.54	-36.41	45.03	1	Horizontal	79	1.57	-	37.64	14.73	50.27
AV	18.07744G	37.80	63.54	-25.74	35.70	1	Horizontal	79	1.57	-	37.64	14.73	50.27

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.897G	65.98	88.20	-22.22	57.29	3	Vertical	229	1.76	-	34.89	6.60	32.80
RMS	5.9178G	53.64	68.20	-14.56	44.88	3	Vertical	229	1.76	-	34.97	6.60	32.81
PK	6.1802G	111.63	Inf	-Inf	102.19	3	Vertical	229	1.76	-	35.42	6.87	32.85
RMS	6.1818G	100.98	Inf	-Inf	91.53	3	Vertical	229	1.76	-	35.43	6.87	32.85

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9114G	66.86	88.20	-21.34	58.11	3	Horizontal	182	2.74	-	34.95	6.60	32.80
RMS	5.921G	53.86	68.20	-14.34	45.09	3	Horizontal	182	2.74	-	34.98	6.60	32.81
PK	6.1818G	106.54	Inf	-Inf	97.09	3	Horizontal	182	2.74	-	35.43	6.87	32.85
RMS	6.1818G	95.49	Inf	-Inf	86.04	3	Horizontal	182	2.74	-	35.43	6.87	32.85

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39156G	62.57	74.00	-11.43	46.29	3	Vertical	234	1.77	-	38.68	9.18	31.58
AV	12.39114G	51.50	54.00	-2.50	35.22	3	Vertical	234	1.77	-	38.68	9.18	31.58

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39128G	63.29	74.00	-10.71	47.01	3	Horizontal	145	1.76	-	38.68	9.18	31.58
AV	12.39128G	52.02	54.00	-1.98	35.74	3	Horizontal	145	1.76	-	38.68	9.18	31.58

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.55328G	49.55	83.54	-33.99	46.90	1	Vertical	27	1.79	-	37.78	14.92	50.05
AV	18.55584G	38.87	63.54	-24.67	36.21	1	Vertical	27	1.79	-	37.78	14.92	50.04

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.55289G	50.20	83.54	-33.34	47.55	1	Horizontal	58	3.00	-	37.78	14.92	50.05
AV	18.55529G	38.69	63.54	-24.85	36.03	1	Horizontal	58	3.00	-	37.78	14.92	50.04

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.881G	63.53	88.20	-24.67	54.86	3	Vertical	224	1.79	-	34.86	6.60	32.79
RMS	5.923G	53.16	68.20	-15.04	44.38	3	Vertical	224	1.79	-	34.99	6.60	32.81
PK	6.375G	110.55	Inf	-Inf	100.97	3	Vertical	224	1.79	-	35.45	6.99	32.86
RMS	6.353G	100.16	Inf	-Inf	90.71	3	Vertical	224	1.79	-	35.32	6.98	32.85

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.881G	63.92	88.20	-24.28	55.25	3	Horizontal	205	2.66	-	34.86	6.60	32.79
RMS	5.925G	53.15	68.20	-15.05	44.36	3	Horizontal	205	2.66	-	35.00	6.60	32.81
PK	6.349G	101.51	Inf	-Inf	92.09	3	Horizontal	205	2.66	-	35.30	6.97	32.85
RMS	6.349G	91.90	Inf	-Inf	82.48	3	Horizontal	205	2.66	-	35.30	6.97	32.85

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.6909G	60.75	74.00	-13.25	43.65	3	Vertical	128	1.09	-	38.97	9.31	31.18
AV	12.68755G	50.34	54.00	-3.66	33.26	3	Vertical	128	1.09	-	38.96	9.31	31.19

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.6883G	62.01	74.00	-11.99	44.93	3	Horizontal	243	1.54	-	38.96	9.31	31.19
AV	12.68817G	50.15	54.00	-3.85	33.07	3	Horizontal	243	1.54	-	38.96	9.31	31.19

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.03804G	50.03	83.54	-33.51	46.57	1	Vertical	330	1.30	-	37.95	15.12	49.61
AV	19.03289G	39.15	63.54	-24.39	35.69	1	Vertical	330	1.30	-	37.96	15.11	49.61

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom



EUT Y_2TX
Setting 16
01-C-K-3


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.03424G	49.73	83.54	-33.81	46.27	1	Horizontal	135	1.69	-	37.96	15.11	49.61
AV	19.03662G	39.28	63.54	-24.26	35.82	1	Horizontal	135	1.69	-	37.96	15.11	49.61

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW160-BF_Nss1,(MCS0)_2TX	Pass	RMS	5.901G	68.19	68.20	-0.01	3	Vertical	87	1.54	-

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.863G	66.13	88.20	-22.07	57.49	3	Vertical	90	1.54	-	34.83	6.60	32.79
RMS	5.925G	54.80	68.20	-13.40	46.01	3	Vertical	90	1.54	-	35.00	6.60	32.81
PK	5.9542G	120.06	Inf	-Inf	111.16	3	Vertical	90	1.54	-	35.12	6.60	32.82
RMS	5.9538G	107.59	Inf	-Inf	98.69	3	Vertical	90	1.54	-	35.12	6.60	32.82

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.91516G	61.29	74.00	-12.71	45.38	3	Vertical	230	1.77	-	38.50	8.98	31.57
AV	11.91276G	49.06	54.00	-4.94	33.15	3	Vertical	230	1.77	-	38.50	8.98	31.57

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.91606G	66.37	74.00	-7.63	50.46	3	Horizontal	200	1.80	-	38.50	8.98	31.57
AV	11.90868G	53.76	54.00	-0.24	37.86	3	Horizontal	200	1.80	-	38.50	8.98	31.58

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.865G	62.41	88.20	-25.79	56.09	3	Vertical	75	1.80	-	34.39	7.46	35.53
RMS	5.907G	51.33	68.20	-16.87	44.74	3	Vertical	75	1.80	-	34.63	7.51	35.55
PK	6.197G	123.18	Inf	-Inf	115.81	3	Vertical	75	1.80	-	35.19	7.70	35.52
RMS	6.193G	111.35	Inf	-Inf	104.00	3	Vertical	75	1.80	-	35.17	7.70	35.52

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38802G	62.18	74.00	-11.82	47.59	3	Vertical	224	1.90	-	38.89	11.11	35.41
AV	12.39036G	48.42	54.00	-5.58	33.83	3	Vertical	224	1.90	-	38.89	11.11	35.41

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3933G	66.77	74.00	-7.23	52.18	3	Horizontal	204	2.33	-	38.89	11.11	35.41
AV	12.3903G	53.23	54.00	-0.77	38.64	3	Horizontal	204	2.33	-	38.89	11.11	35.41

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58602G	49.17	83.54	-34.37	46.48	1	Vertical	38	1.76	-	37.77	14.93	50.01
AV	18.5988G	35.89	63.54	-27.65	33.19	1	Vertical	38	1.76	-	37.76	14.94	50.00

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59904G	50.10	83.54	-33.44	47.40	1	Horizontal	293	1.25	-	37.76	14.94	50.00
AV	18.57306G	36.03	63.54	-27.51	33.36	1	Horizontal	293	1.25	-	37.77	14.93	50.03

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8678G	62.25	88.20	-25.95	55.90	3	Vertical	71	1.80	-	34.41	7.47	35.53
RMS	5.919G	51.20	68.20	-17.00	44.56	3	Vertical	71	1.80	-	34.68	7.52	35.56
PK	6.415G	123.07	Inf	-Inf	115.93	3	Vertical	71	1.80	-	34.84	7.73	35.43
RMS	6.415G	112.30	Inf	-Inf	105.16	3	Vertical	71	1.80	-	34.84	7.73	35.43
PK	7.2086G	64.36	88.20	-23.84	55.23	3	Vertical	71	1.80	-	36.45	8.22	35.54
RMS	7.2118G	54.15	68.20	-14.05	45.01	3	Vertical	71	1.80	-	36.47	8.22	35.55

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83354G	65.87	88.20	-22.33	49.69	3	Vertical	204	2.33	-	39.33	11.47	34.62
RMS	12.82886G	51.36	68.20	-16.84	35.20	3	Vertical	204	2.33	-	39.33	11.46	34.63

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.83162G	66.09	88.20	-22.11	49.92	3	Horizontal	144	1.80	-	39.33	11.47	34.63
RMS	12.83138G	51.72	68.20	-16.48	35.55	3	Horizontal	144	1.80	-	39.33	11.47	34.63

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.23906G	51.00	83.54	-32.54	47.74	1	Vertical	72	1.89	-	37.71	15.20	49.65
AV	19.24356G	36.99	63.54	-26.55	33.73	1	Vertical	72	1.89	-	37.71	15.20	49.65

802.11ax HEW20-BF_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.25898G	51.40	83.54	-32.14	48.14	1	Horizontal	162	1.56	-	37.71	15.20	49.65
AV	19.23846G	37.08	63.54	-26.46	33.82	1	Horizontal	162	1.56	-	37.71	15.20	49.65

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9226G	86.47	88.20	-1.73	77.69	3	Vertical	86	1.55	-	34.99	6.60	32.81
RMS	5.9234G	67.84	68.20	-0.36	59.06	3	Vertical	86	1.55	-	34.99	6.60	32.81
PK	5.9678G	118.74	Inf	-Inf	109.80	3	Vertical	86	1.55	-	35.17	6.60	32.83
RMS	5.9738G	106.38	Inf	-Inf	97.41	3	Vertical	86	1.55	-	35.20	6.60	32.83

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.93516G	61.17	74.00	-12.83	45.26	3	Vertical	231	1.83	-	38.50	8.98	31.57
AV	11.94404G	48.67	54.00	-5.33	32.74	3	Vertical	231	1.83	-	38.50	8.99	31.56

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

5965MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9372G	66.19	74.00	-7.81	50.28	3	Horizontal	211	1.70	-	38.50	8.98	31.57
AV	11.9297G	53.62	54.00	-0.38	37.71	3	Horizontal	211	1.70	-	38.50	8.98	31.57

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.915G	62.03	88.20	-26.17	55.42	3	Vertical	71	1.77	-	34.66	7.51	35.56
RMS	5.925G	51.25	68.20	-16.95	44.58	3	Vertical	71	1.77	-	34.70	7.53	35.56
PK	6.205G	119.73	Inf	-Inf	112.37	3	Vertical	71	1.77	-	35.18	7.70	35.52
RMS	6.203G	109.99	Inf	-Inf	102.62	3	Vertical	71	1.77	-	35.19	7.70	35.52

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.39824G	60.62	74.00	-13.38	46.01	3	Vertical	224	1.66	-	38.90	11.12	35.41
AV	12.41048G	46.98	54.00	-7.02	32.37	3	Vertical	224	1.66	-	38.89	11.13	35.41

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.41072G	66.56	74.00	-7.44	51.95	3	Horizontal	207	2.28	-	38.89	11.13	35.41
AV	12.41522G	51.24	54.00	-2.76	36.64	3	Horizontal	207	2.28	-	38.88	11.13	35.41

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.60636G	49.90	83.54	-33.64	47.19	1	Vertical	293	1.11	-	37.76	14.94	49.99
AV	18.62622G	36.01	63.54	-27.53	33.28	1	Vertical	293	1.11	-	37.75	14.95	49.97

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6205MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.62088G	50.60	83.54	-32.94	47.88	1	Horizontal	162	1.37	-	37.75	14.95	49.98
AV	18.609G	36.04	63.54	-27.50	33.33	1	Horizontal	162	1.37	-	37.76	14.94	49.99

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	62.33	88.20	-25.87	55.66	3	Vertical	73	1.80	-	34.70	7.53	35.56
RMS	5.915G	51.22	68.20	-16.98	44.61	3	Vertical	73	1.80	-	34.66	7.51	35.56
PK	6.405G	121.37	Inf	-Inf	114.22	3	Vertical	73	1.80	-	34.88	7.71	35.44
RMS	6.4078G	110.45	Inf	-Inf	103.30	3	Vertical	73	1.80	-	34.87	7.72	35.44

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.81042G	60.56	88.20	-27.64	44.48	3	Vertical	252	2.42	-	39.31	11.45	34.68
RMS	12.81624G	47.10	68.20	-21.10	30.99	3	Vertical	252	2.42	-	39.32	11.45	34.66

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.81366G	63.52	88.20	-24.68	47.43	3	Horizontal	210	1.47	-	39.31	11.45	34.67
RMS	12.80598G	50.47	68.20	-17.73	34.41	3	Horizontal	210	1.47	-	39.31	11.44	34.69

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.21572G	50.30	83.54	-33.24	47.01	1	Vertical	279	1.45	-	37.74	15.19	49.64
AV	19.22976G	36.99	63.54	-26.55	33.73	1	Vertical	279	1.45	-	37.72	15.19	49.65

802.11ax HEW40-BF_Nss1,(MCS0)_2TX

6405MHz_TnomVnom




EUT Y_2TX
Setting 19.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2237G	51.38	83.54	-32.16	48.10	1	Horizontal	72	2.03	-	37.73	15.19	49.64
AV	19.2285G	36.97	63.54	-26.57	33.70	1	Horizontal	72	2.03	-	37.73	15.19	49.65

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 14
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9162G	77.47	88.20	-10.73	68.72	3	Vertical	67	1.57	-	34.96	6.60	32.81
RMS	5.9234G	61.00	68.20	-7.20	52.22	3	Vertical	67	1.57	-	34.99	6.60	32.81
PK	6.0098G	112.00	Inf	-Inf	102.95	3	Vertical	67	1.57	-	35.28	6.61	32.84
RMS	6.0186G	103.68	Inf	-Inf	94.63	3	Vertical	67	1.57	-	35.26	6.63	32.84

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 14
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.98422G	61.45	74.00	-12.55	45.50	3	Vertical	68	1.80	-	38.50	9.00	31.55
AV	11.98434G	51.58	54.00	-2.42	35.63	3	Vertical	68	1.80	-	38.50	9.00	31.55

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

5985MHz_TnomVnom




EUT Y_2TX
Setting 14
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.95968G	63.82	74.00	-10.18	47.89	3	Horizontal	199	1.80	-	38.50	8.99	31.56
AV	11.973G	53.84	54.00	-0.16	37.90	3	Horizontal	199	1.80	-	38.50	8.99	31.55

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.915G	63.12	88.20	-25.08	56.51	3	Vertical	72	1.82	-	34.66	7.51	35.56
RMS	5.925G	51.48	68.20	-16.72	44.81	3	Vertical	72	1.82	-	34.70	7.53	35.56
PK	6.229G	118.31	Inf	-Inf	111.04	3	Vertical	72	1.82	-	35.08	7.70	35.51
RMS	6.231G	107.06	Inf	-Inf	99.79	3	Vertical	72	1.82	-	35.08	7.70	35.51

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.43632G	59.37	74.00	-14.63	44.76	3	Vertical	223	1.80	-	38.86	11.15	35.40
AV	12.45792G	48.43	54.00	-5.57	33.82	3	Vertical	223	1.80	-	38.84	11.17	35.40

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.46224G	62.00	74.00	-12.00	47.39	3	Horizontal	205	2.61	-	38.84	11.17	35.40
AV	12.453G	51.86	54.00	-2.14	37.25	3	Horizontal	205	2.61	-	38.85	11.16	35.40

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.66126G	49.73	83.54	-33.81	46.97	1	Vertical	43	2.46	-	37.74	14.96	49.94
AV	18.66804G	39.40	63.54	-24.14	36.63	1	Vertical	43	2.46	-	37.73	14.97	49.93

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6225MHz_TnomVnom




EUT Y_2TX
Setting 20
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.68718G	49.62	83.54	-33.92	46.83	1	Horizontal	297	1.97	-	37.73	14.97	49.91
AV	18.67608G	39.42	63.54	-24.12	36.64	1	Horizontal	297	1.97	-	37.73	14.97	49.92

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7858G	61.36	88.20	-26.84	55.25	3	Vertical	72	1.80	-	34.20	7.40	35.49
RMS	5.925G	51.27	68.20	-16.93	44.61	3	Vertical	72	1.80	-	34.70	7.52	35.56
PK	6.399G	116.62	Inf	-Inf	109.46	3	Vertical	72	1.80	-	34.90	7.70	35.44
RMS	6.3878G	106.34	Inf	-Inf	99.18	3	Vertical	72	1.80	-	34.90	7.70	35.44

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.76724G	59.42	88.20	-28.78	43.56	3	Vertical	43	1.41	-	39.23	11.41	34.78
RMS	12.75638G	48.20	68.20	-20.00	32.38	3	Vertical	43	1.41	-	39.21	11.41	34.80

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.76436G	58.77	88.20	-29.43	42.91	3	Horizontal	192	2.23	-	39.23	11.41	34.78
RMS	12.76946G	48.40	68.20	-19.80	32.51	3	Horizontal	192	2.23	-	39.24	11.42	34.77

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.16382G	50.48	83.54	-33.06	47.14	1	Vertical	150	1.41	-	37.80	15.17	49.63
AV	19.15506G	40.01	63.54	-23.53	36.67	1	Vertical	150	1.41	-	37.81	15.16	49.63

802.11ax HEW80-BF_Nss1,(MCS0)_2TX

6385MHz_TnomVnom




EUT Y_2TX
Setting 18
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.1673G	50.54	83.54	-33.00	47.20	1	Horizontal	198	1.45	-	37.80	15.17	49.63
AV	19.16328G	40.15	63.54	-23.39	36.81	1	Horizontal	198	1.45	-	37.80	15.17	49.63

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 13.25
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.901G	86.18	88.20	-2.02	77.48	3	Vertical	87	1.54	-	34.90	6.60	32.80
RMS	5.901G	68.19	68.20	-0.01	59.49	3	Vertical	87	1.54	-	34.90	6.60	32.80
PK	6G	109.33	Inf	-Inf	100.27	3	Vertical	87	1.54	-	35.30	6.60	32.84
RMS	6.021G	99.93	Inf	-Inf	90.88	3	Vertical	87	1.54	-	35.26	6.63	32.84

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 13.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.04982G	61.31	74.00	-12.69	45.28	3	Vertical	0	2.78	-	38.55	9.02	31.54
AV	12.0545G	51.67	54.00	-2.33	35.65	3	Vertical	0	2.78	-	38.55	9.02	31.55

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 13.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.0458G	62.52	74.00	-11.48	46.49	3	Horizontal	218	1.45	-	38.55	9.02	31.54
AV	12.05864G	52.94	54.00	-1.06	36.90	3	Horizontal	218	1.45	-	38.56	9.03	31.55

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 13.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.07614G	47.87	83.54	-35.67	45.77	1	Vertical	259	2.58	-	37.64	14.73	50.27
AV	18.07668G	38.12	63.54	-25.42	36.02	1	Vertical	259	2.58	-	37.64	14.73	50.27

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6025MHz_TnomVnom




EUT Y_2TX
Setting 13.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.0696G	47.95	83.54	-35.59	45.85	1	Horizontal	157	1.62	-	37.64	14.73	50.27
AV	18.0855G	38.36	63.54	-25.18	36.27	1	Horizontal	157	1.62	-	37.63	14.73	50.27

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.907G	77.69	88.20	-10.51	71.10	3	Vertical	74	1.80	-	34.63	7.51	35.55
RMS	5.917G	59.69	68.20	-8.51	53.06	3	Vertical	74	1.80	-	34.67	7.52	35.56
PK	6.179G	114.70	Inf	-Inf	107.42	3	Vertical	74	1.80	-	35.12	7.69	35.53
RMS	6.181G	104.97	Inf	-Inf	97.69	3	Vertical	74	1.80	-	35.12	7.69	35.53

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3847G	60.14	74.00	-13.86	45.56	3	Vertical	211	1.80	-	38.88	11.11	35.41
AV	12.37024G	48.89	54.00	-5.11	34.34	3	Vertical	211	1.80	-	38.87	11.10	35.42

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.35674G	59.17	74.00	-14.83	44.64	3	Horizontal	65	2.36	-	38.86	11.09	35.42
AV	12.3811G	48.81	54.00	-5.19	34.24	3	Horizontal	65	2.36	-	38.88	11.10	35.41

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.54924G	50.16	83.54	-33.38	47.51	1	Vertical	225	1.28	-	37.78	14.92	50.05
AV	18.54318G	39.16	63.54	-24.38	36.52	1	Vertical	225	1.28	-	37.78	14.92	50.06

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6185MHz_TnomVnom




EUT Y_2TX
Setting 19.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5595G	49.64	83.54	-33.90	46.98	1	Horizontal	106	1.38	-	37.78	14.92	50.04
AV	18.54576G	39.26	63.54	-24.28	36.61	1	Horizontal	106	1.38	-	37.78	14.92	50.05

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.91G	64.03	88.20	-24.17	57.43	3	Vertical	72	1.73	-	34.64	7.51	35.55
RMS	5.916G	51.75	68.20	-16.45	45.13	3	Vertical	72	1.73	-	34.66	7.52	35.56
PK	6.357G	114.41	Inf	-Inf	107.27	3	Vertical	72	1.73	-	34.90	7.70	35.46
RMS	6.342G	103.01	Inf	-Inf	95.85	3	Vertical	72	1.73	-	34.92	7.70	35.46

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.69612G	59.42	74.00	-14.58	43.91	3	Vertical	352	1.63	-	39.09	11.36	34.94
AV	12.69398G	48.59	54.00	-5.41	33.09	3	Vertical	352	1.63	-	39.08	11.36	34.94

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.6978G	59.94	74.00	-14.06	44.43	3	Horizontal	83	2.74	-	39.09	11.36	34.94
AV	12.68034G	48.65	54.00	-5.35	33.25	3	Horizontal	83	2.74	-	39.04	11.34	34.98

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.04088G	51.36	83.54	-32.18	47.90	1	Vertical	215	2.47	-	37.95	15.12	49.61
AV	19.04076G	40.41	63.54	-23.13	36.95	1	Vertical	215	2.47	-	37.95	15.12	49.61

802.11ax HEW160-BF_Nss1,(MCS0)_2TX

6345MHz_TnomVnom



EUT Y_2TX
Setting 16
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.02168G	51.02	83.54	-32.52	47.54	1	Horizontal	323	1.22	-	37.97	15.11	49.60
AV	19.04052G	40.31	63.54	-23.23	36.85	1	Horizontal	323	1.22	-	37.95	15.12	49.61

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.89279G	53.68	54.00	-0.32	3	Horizontal	207	1.86	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 12.25
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8906G	62.62	88.20	-25.58	53.94	3	Vertical	44	1.24	-	34.88	6.60	32.80
RMS	5.9058G	51.13	68.20	-17.07	42.41	3	Vertical	44	1.24	-	34.92	6.60	32.80
PK	5.9466G	117.20	Inf	-Inf	108.33	3	Vertical	44	1.24	-	35.09	6.60	32.82
RMS	5.9466G	107.53	Inf	-Inf	98.66	3	Vertical	44	1.24	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 12.25
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8986G	62.20	88.20	-26.00	53.50	3	Horizontal	356	1.07	-	34.90	6.60	32.80
RMS	5.9062G	50.98	68.20	-17.22	42.26	3	Horizontal	356	1.07	-	34.92	6.60	32.80
PK	5.9462G	114.08	Inf	-Inf	105.22	3	Horizontal	356	1.07	-	35.08	6.60	32.82
RMS	5.9466G	104.86	Inf	-Inf	95.99	3	Horizontal	356	1.07	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 12.25
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89391G	58.78	74.00	-15.22	42.89	3	Vertical	241	1.76	-	38.50	8.97	31.58
AV	11.89291G	46.59	54.00	-7.41	30.70	3	Vertical	241	1.76	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 12.25
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89335G	69.32	74.00	-4.68	53.43	3	Horizontal	207	1.86	-	38.50	8.97	31.58
AV	11.89279G	53.68	54.00	-0.32	37.79	3	Horizontal	207	1.86	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15.25
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.5174G	59.31	88.20	-28.89	52.75	3	Vertical	236	1.12	-	34.60	7.32	35.36
RMS	5.6098G	47.40	68.20	-20.80	40.82	3	Vertical	236	1.12	-	34.58	7.40	35.40
PK	6.1866G	117.69	Inf	-Inf	110.38	3	Vertical	236	1.12	-	35.15	7.69	35.53
RMS	6.1866G	106.58	Inf	-Inf	99.27	3	Vertical	236	1.12	-	35.15	7.69	35.53

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15.25
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.6322G	59.14	88.20	-29.06	52.62	3	Horizontal	2	1.88	-	34.54	7.40	35.42
RMS	5.6154G	47.38	68.20	-20.82	40.82	3	Horizontal	2	1.88	-	34.57	7.40	35.41
PK	6.1866G	114.78	Inf	-Inf	107.47	3	Horizontal	2	1.88	-	35.15	7.69	35.53
RMS	6.1866G	103.31	Inf	-Inf	96.00	3	Horizontal	2	1.88	-	35.15	7.69	35.53

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3736G	56.45	74.00	-17.55	41.90	3	Vertical	255	1.80	-	38.87	11.10	35.42
AV	12.3734G	43.34	54.00	-10.66	28.79	3	Vertical	255	1.80	-	38.87	11.10	35.42

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3736G	68.10	74.00	-5.90	53.55	3	Horizontal	213	2.10	-	38.87	11.10	35.42
AV	12.373G	51.19	54.00	-2.81	36.64	3	Horizontal	213	2.10	-	38.87	11.10	35.42

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2236G	45.34	83.54	-38.20	42.06	1	Vertical	160	1.76	-	37.73	15.19	49.64
AV	19.2328G	32.18	63.54	-31.36	28.92	1	Vertical	160	1.76	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2526G	45.82	83.54	-37.72	42.57	1	Horizontal	67	1.08	-	37.70	15.20	49.65
AV	19.2288G	32.10	63.54	-31.44	28.83	1	Horizontal	67	1.08	-	37.73	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	59.16	88.20	-29.04	52.50	3	Vertical	285	2.06	-	34.70	7.52	35.56
RMS	5.925G	47.33	68.20	-20.87	40.67	3	Vertical	285	2.06	-	34.70	7.52	35.56
PK	6.4054G	114.82	Inf	-Inf	107.67	3	Vertical	285	2.06	-	34.88	7.71	35.44
RMS	6.4054G	101.77	Inf	-Inf	94.62	3	Vertical	285	2.06	-	34.88	7.71	35.44
PK	7.1254G	63.84	88.20	-24.36	55.21	3	Vertical	285	2.06	-	35.95	8.20	35.52
RMS	7.1574G	52.11	68.20	-16.09	43.30	3	Vertical	285	2.06	-	36.14	8.20	35.53

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	59.63	88.20	-28.57	52.97	3	Horizontal	3	1.79	-	34.70	7.52	35.56
RMS	5.925G	47.29	68.20	-20.91	40.63	3	Horizontal	3	1.79	-	34.70	7.52	35.56
PK	6.4054G	113.87	Inf	-Inf	106.72	3	Horizontal	3	1.79	-	34.88	7.71	35.44
RMS	6.4054G	100.11	Inf	-Inf	92.96	3	Horizontal	3	1.79	-	34.88	7.71	35.44
PK	7.1318G	63.39	88.20	-24.81	54.72	3	Horizontal	3	1.79	-	35.99	8.20	35.52
RMS	7.1606G	52.15	68.20	-16.05	43.32	3	Horizontal	3	1.79	-	36.16	8.20	35.53

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8136G	62.10	88.20	-26.10	46.01	3	Vertical	230	1.78	-	39.31	11.45	34.67
RMS	12.813G	46.72	68.20	-21.48	30.63	3	Vertical	230	1.78	-	39.31	11.45	34.67

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8136G	67.17	88.20	-21.03	51.08	3	Horizontal	213	1.80	-	39.31	11.45	34.67
RMS	12.8132G	51.89	68.20	-16.31	35.80	3	Horizontal	213	1.80	-	39.31	11.45	34.67

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2454G	45.74	83.54	-37.80	42.48	1	Vertical	338	1.58	-	37.71	15.20	49.65
AV	19.236G	32.12	63.54	-31.42	28.86	1	Vertical	338	1.58	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 15.5
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2082G	46.41	83.54	-37.13	43.12	1	Horizontal	126	2.99	-	37.75	15.18	49.64
AV	19.2378G	32.17	63.54	-31.37	28.91	1	Horizontal	126	2.99	-	37.71	15.20	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.89523G	53.88	54.00	-0.12	3	Horizontal	220	1.80	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.75
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9186G	64.29	88.20	-23.91	55.53	3	Vertical	44	1.25	-	34.97	6.60	32.81
RMS	5.9186G	51.76	68.20	-16.44	43.00	3	Vertical	44	1.25	-	34.97	6.60	32.81
PK	5.949G	117.41	Inf	-Inf	108.53	3	Vertical	44	1.25	-	35.10	6.60	32.82
RMS	5.9482G	107.28	Inf	-Inf	98.41	3	Vertical	44	1.25	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.75
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9126G	62.99	88.20	-25.21	54.25	3	Horizontal	360	2.41	-	34.95	6.60	32.81
RMS	5.9142G	51.06	68.20	-17.14	42.31	3	Horizontal	360	2.41	-	34.96	6.60	32.81
PK	5.949G	114.42	Inf	-Inf	105.54	3	Horizontal	360	2.41	-	35.10	6.60	32.82
RMS	5.9486G	104.37	Inf	-Inf	95.50	3	Horizontal	360	2.41	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89795G	60.52	74.00	-13.48	44.63	3	Vertical	3	1.77	-	38.50	8.97	31.58
AV	11.89519G	47.67	54.00	-6.33	31.78	3	Vertical	3	1.77	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89815G	65.95	74.00	-8.05	50.06	3	Horizontal	220	1.80	-	38.50	8.97	31.58
AV	11.89523G	53.88	54.00	-0.12	37.99	3	Horizontal	220	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9118G	57.96	88.20	-30.24	51.36	3	Vertical	235	1.12	-	34.65	7.51	35.56
RMS	5.9238G	47.09	68.20	-21.11	40.43	3	Vertical	235	1.12	-	34.70	7.52	35.56
PK	6.189G	117.44	Inf	-Inf	110.11	3	Vertical	235	1.12	-	35.16	7.69	35.52
RMS	6.189G	106.86	Inf	-Inf	99.53	3	Vertical	235	1.12	-	35.16	7.69	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9118G	57.65	88.20	-30.55	51.05	3	Horizontal	0	1.88	-	34.65	7.51	35.56
RMS	5.925G	47.04	68.20	-21.16	40.37	3	Horizontal	0	1.88	-	34.70	7.53	35.56
PK	6.189G	114.17	Inf	-Inf	106.84	3	Horizontal	0	1.88	-	35.16	7.69	35.52
RMS	6.189G	103.52	Inf	-Inf	96.19	3	Horizontal	0	1.88	-	35.16	7.69	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3756G	58.39	74.00	-15.61	43.82	3	Vertical	261	1.80	-	38.88	11.10	35.41
AV	12.376G	45.50	54.00	-8.50	30.93	3	Vertical	261	1.80	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3762G	64.45	74.00	-9.55	49.88	3	Horizontal	208	1.80	-	38.88	11.10	35.41
AV	12.3762G	50.66	54.00	-3.34	36.09	3	Horizontal	208	1.80	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6032G	45.20	83.54	-38.34	42.50	1	Vertical	129	1.26	-	37.76	14.94	50.00
AV	18.5358G	31.25	63.54	-32.29	28.61	1	Vertical	129	1.26	-	37.79	14.91	50.06

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5786G	44.56	83.54	-38.98	41.88	1	Horizontal	179	2.19	-	37.77	14.93	50.02
AV	18.5376G	31.25	63.54	-32.29	28.61	1	Horizontal	179	2.19	-	37.78	14.92	50.06

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8654G	57.58	88.20	-30.62	51.25	3	Vertical	332	1.64	-	34.39	7.47	35.53
RMS	5.9206G	47.00	68.20	-21.20	40.36	3	Vertical	332	1.64	-	34.68	7.52	35.56
PK	6.4102G	114.05	Inf	-Inf	106.91	3	Vertical	332	1.64	-	34.86	7.72	35.44
RMS	6.4078G	103.50	Inf	-Inf	96.35	3	Vertical	332	1.64	-	34.87	7.72	35.44

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9182G	57.90	88.20	-30.30	51.27	3	Horizontal	355	1.87	-	34.67	7.52	35.56
RMS	5.9182G	46.98	68.20	-21.22	40.35	3	Horizontal	355	1.87	-	34.67	7.52	35.56
PK	6.4102G	113.72	Inf	-Inf	106.58	3	Horizontal	355	1.87	-	34.86	7.72	35.44
RMS	6.4078G	102.92	Inf	-Inf	95.77	3	Horizontal	355	1.87	-	34.87	7.72	35.44

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8184G	59.76	88.20	-28.44	43.65	3	Vertical	215	1.80	-	39.32	11.45	34.66
RMS	12.816G	46.19	68.20	-22.01	30.08	3	Vertical	215	1.80	-	39.32	11.45	34.66

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8164G	65.45	88.20	-22.75	49.34	3	Horizontal	206	1.80	-	39.32	11.45	34.66
RMS	12.8162G	52.02	68.20	-16.18	35.91	3	Horizontal	206	1.80	-	39.32	11.45	34.66

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2296G	46.10	83.54	-37.44	42.84	1	Vertical	340	1.04	-	37.72	15.19	49.65
AV	19.233G	32.16	63.54	-31.38	28.90	1	Vertical	340	1.04	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 18.25
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2846G	46.27	83.54	-37.27	42.99	1	Horizontal	271	1.93	-	37.73	15.21	49.66
AV	19.2278G	32.08	63.54	-31.46	28.81	1	Horizontal	271	1.93	-	37.73	15.19	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.90111G	53.74	54.00	-0.26	3	Vertical	296	2.24	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.75
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9222G	67.03	88.20	-21.17	58.25	3	Vertical	42	1.14	-	34.99	6.60	32.81
RMS	5.925G	51.84	68.20	-16.36	43.05	3	Vertical	42	1.14	-	35.00	6.60	32.81
PK	5.9518G	113.81	Inf	-Inf	104.92	3	Vertical	42	1.14	-	35.11	6.60	32.82
RMS	5.9522G	105.25	Inf	-Inf	96.36	3	Vertical	42	1.14	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.75
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9198G	66.64	88.20	-21.56	57.87	3	Horizontal	360	1.70	-	34.98	6.60	32.81
RMS	5.9238G	51.33	68.20	-16.87	42.54	3	Horizontal	360	1.70	-	35.00	6.60	32.81
PK	5.9522G	111.12	Inf	-Inf	102.23	3	Horizontal	360	1.70	-	35.11	6.60	32.82
RMS	5.9522G	102.40	Inf	-Inf	93.51	3	Horizontal	360	1.70	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.90141G	65.67	74.00	-8.33	49.77	3	Vertical	296	2.24	-	38.50	8.98	31.58
AV	11.90111G	53.74	54.00	-0.26	37.84	3	Vertical	296	2.24	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.75
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89711G	65.88	74.00	-8.12	49.99	3	Horizontal	209	1.50	-	38.50	8.97	31.58
AV	11.90101G	53.52	54.00	-0.48	37.62	3	Horizontal	209	1.50	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	58.48	88.20	-29.72	51.81	3	Vertical	223	1.94	-	34.70	7.53	35.56
RMS	5.9238G	46.94	68.20	-21.26	40.28	3	Vertical	223	1.94	-	34.70	7.52	35.56
PK	6.1926G	112.47	Inf	-Inf	105.12	3	Vertical	223	1.94	-	35.17	7.70	35.52
RMS	6.1926G	104.65	Inf	-Inf	97.30	3	Vertical	223	1.94	-	35.17	7.70	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.919G	58.56	88.20	-29.64	51.92	3	Horizontal	198	1.80	-	34.68	7.52	35.56
RMS	5.925G	46.92	68.20	-21.28	40.25	3	Horizontal	198	1.80	-	34.70	7.53	35.56
PK	6.1926G	111.11	Inf	-Inf	103.76	3	Horizontal	198	1.80	-	35.17	7.70	35.52
RMS	6.1926G	103.17	Inf	-Inf	95.82	3	Horizontal	198	1.80	-	35.17	7.70	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3828G	58.72	74.00	-15.28	44.14	3	Vertical	263	1.79	-	38.88	11.11	35.41
AV	12.38124G	45.46	54.00	-8.54	30.89	3	Vertical	263	1.79	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38262G	63.44	74.00	-10.56	48.86	3	Horizontal	209	1.80	-	38.88	11.11	35.41
AV	12.3813G	51.21	54.00	-2.79	36.63	3	Horizontal	209	1.80	-	38.88	11.11	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58584G	44.93	83.54	-38.61	42.24	1	Vertical	1	1.84	-	37.77	14.93	50.01
AV	18.57096G	30.79	63.54	-32.75	28.12	1	Vertical	1	1.84	-	37.77	14.93	50.03

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59226G	44.63	83.54	-38.91	41.94	1	Horizontal	298	2.24	-	37.76	14.94	50.01
AV	18.57114G	30.77	63.54	-32.77	28.10	1	Horizontal	298	2.24	-	37.77	14.93	50.03

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21.25
03-D-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9158G	57.90	88.20	-30.30	51.28	3	Vertical	329	1.80	-	34.66	7.52	35.56
RMS	5.925G	46.99	68.20	-21.21	40.33	3	Vertical	329	1.80	-	34.70	7.52	35.56
PK	6.4126G	112.19	Inf	-Inf	105.04	3	Vertical	329	1.80	-	34.85	7.73	35.43
RMS	6.4126G	104.13	Inf	-Inf	96.98	3	Vertical	329	1.80	-	34.85	7.73	35.43

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21.25
03-D-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8342G	57.31	88.20	-30.89	51.13	3	Horizontal	0	1.85	-	34.27	7.43	35.52
RMS	5.923G	46.92	68.20	-21.28	40.27	3	Horizontal	0	1.85	-	34.69	7.52	35.56
PK	6.4126G	111.50	Inf	-Inf	104.35	3	Horizontal	0	1.85	-	34.85	7.73	35.43
RMS	6.4126G	103.37	Inf	-Inf	96.22	3	Horizontal	0	1.85	-	34.85	7.73	35.43

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.82106G	59.36	88.20	-28.84	43.23	3	Vertical	265	1.80	-	39.32	11.46	34.65
RMS	12.82124G	45.43	68.20	-22.77	29.30	3	Vertical	265	1.80	-	39.32	11.46	34.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.82058G	64.99	88.20	-23.21	48.86	3	Horizontal	207	1.71	-	39.32	11.46	34.65
RMS	12.82124G	52.77	68.20	-15.43	36.64	3	Horizontal	207	1.71	-	39.32	11.46	34.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2303G	45.41	83.54	-38.13	42.15	1	Vertical	170	2.46	-	37.72	15.19	49.65
AV	19.23318G	31.59	63.54	-31.95	28.33	1	Vertical	170	2.46	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 21.25
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.25886G	45.66	83.54	-37.88	42.40	1	Horizontal	111	1.04	-	37.71	15.20	49.65
AV	19.23348G	31.55	63.54	-31.99	28.29	1	Horizontal	111	1.04	-	37.72	15.19	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.89287G	53.88	54.00	-0.12	3	Horizontal	199	2.27	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 12.5
01-C-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9082G	63.38	88.20	-24.82	54.65	3	Vertical	19	2.26	-	34.93	6.60	32.80
RMS	5.9094G	50.93	68.20	-17.27	42.19	3	Vertical	19	2.26	-	34.94	6.60	32.80
PK	5.9466G	103.51	Inf	-Inf	94.64	3	Vertical	19	2.26	-	35.09	6.60	32.82
RMS	5.9466G	93.80	Inf	-Inf	84.93	3	Vertical	19	2.26	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 12.5
01-C-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.879G	63.26	88.20	-24.94	54.59	3	Horizontal	346	2.87	-	34.86	6.60	32.79
RMS	5.9174G	50.88	68.20	-17.32	42.12	3	Horizontal	346	2.87	-	34.97	6.60	32.81
PK	5.9466G	108.85	Inf	-Inf	99.98	3	Horizontal	346	2.87	-	35.09	6.60	32.82
RMS	5.9466G	99.94	Inf	-Inf	91.07	3	Horizontal	346	2.87	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 12.5
01-C-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89339G	65.21	74.00	-8.79	49.32	3	Vertical	231	1.79	-	38.50	8.97	31.58
AV	11.89275G	51.71	54.00	-2.29	35.82	3	Vertical	231	1.79	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 12.5
01-C-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89295G	68.91	74.00	-5.09	53.02	3	Horizontal	199	2.27	-	38.50	8.97	31.58
AV	11.89287G	53.88	54.00	-0.12	37.99	3	Horizontal	199	2.27	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8974G	61.70	88.20	-26.50	53.01	3	Vertical	230	1.77	-	34.89	6.60	32.80
RMS	5.9238G	50.11	68.20	-18.09	41.32	3	Vertical	230	1.77	-	35.00	6.60	32.81
PK	6.1866G	121.45	Inf	-Inf	111.97	3	Vertical	230	1.77	-	35.45	6.88	32.85
RMS	6.1866G	109.57	Inf	-Inf	100.09	3	Vertical	230	1.77	-	35.45	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9226G	61.56	88.20	-26.64	52.78	3	Horizontal	182	2.69	-	34.99	6.60	32.81
RMS	5.925G	50.10	68.20	-18.10	41.31	3	Horizontal	182	2.69	-	35.00	6.60	32.81
PK	6.1866G	114.92	Inf	-Inf	105.44	3	Horizontal	182	2.69	-	35.45	6.88	32.85
RMS	6.1866G	103.69	Inf	-Inf	94.21	3	Horizontal	182	2.69	-	35.45	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3726G	63.31	74.00	-10.69	47.07	3	Vertical	232	1.72	-	38.65	9.17	31.58
AV	12.3732G	48.68	54.00	-5.32	32.44	3	Vertical	232	1.72	-	38.65	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.37212G	67.43	74.00	-6.57	51.20	3	Horizontal	203	1.80	-	38.64	9.17	31.58
AV	12.37272G	51.38	54.00	-2.62	35.14	3	Horizontal	203	1.80	-	38.65	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5856G	47.54	83.54	-36.00	44.85	1	Vertical	181	1.55	-	37.77	14.93	50.01
AV	18.61308G	33.70	63.54	-29.84	30.99	1	Vertical	181	1.55	-	37.75	14.95	49.99

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59016G	47.79	83.54	-35.75	45.10	1	Horizontal	283	2.71	-	37.76	14.94	50.01
AV	18.609G	33.78	63.54	-29.76	31.07	1	Horizontal	283	2.71	-	37.76	14.94	49.99

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.911G	61.56	88.20	-26.64	52.82	3	Vertical	222	1.80	-	34.94	6.60	32.80
RMS	5.925G	50.04	68.20	-18.16	41.25	3	Vertical	222	1.80	-	35.00	6.60	32.81
PK	6.4078G	121.96	Inf	-Inf	112.25	3	Vertical	222	1.80	-	35.57	7.00	32.86
RMS	6.4078G	107.73	Inf	-Inf	98.02	3	Vertical	222	1.80	-	35.57	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8942G	61.44	88.20	-26.76	52.75	3	Horizontal	322	1.72	-	34.89	6.60	32.80
RMS	5.923G	50.02	68.20	-18.18	41.24	3	Horizontal	322	1.72	-	34.99	6.60	32.81
PK	6.4078G	115.06	Inf	-Inf	105.35	3	Horizontal	322	1.72	-	35.57	7.00	32.86
RMS	6.4078G	101.97	Inf	-Inf	92.26	3	Horizontal	322	1.72	-	35.57	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.81392G	64.84	88.20	-23.36	47.18	3	Vertical	262	1.80	-	39.21	9.37	30.92
RMS	12.81344G	49.97	68.20	-18.23	32.31	3	Vertical	262	1.80	-	39.21	9.37	30.92

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.81368G	69.32	88.20	-18.88	51.66	3	Horizontal	206	2.15	-	39.21	9.37	30.92
RMS	12.81308G	54.90	68.20	-13.30	37.24	3	Horizontal	206	2.15	-	39.21	9.37	30.92

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.22328G	47.34	83.54	-36.20	44.06	1	Vertical	235	1.73	-	37.73	15.19	49.64
AV	19.21728G	34.13	63.54	-29.41	30.84	1	Vertical	235	1.73	-	37.74	15.19	49.64

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 15.5
01-C-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.257G	48.05	83.54	-35.49	44.79	1	Horizontal	195	2.06	-	37.71	15.20	49.65
AV	19.21788G	34.13	63.54	-29.41	30.84	1	Horizontal	195	2.06	-	37.74	15.19	49.64

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.8952G	53.83	54.00	-0.17	3	Horizontal	211	1.80	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 14.75
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9192G	62.20	88.20	-26.00	53.43	3	Vertical	41	2.28	-	34.98	6.60	32.81
RMS	5.9056G	51.09	68.20	-17.11	42.37	3	Vertical	41	2.28	-	34.92	6.60	32.80
PK	5.9492G	117.30	Inf	-Inf	108.42	3	Vertical	41	2.28	-	35.10	6.60	32.82
RMS	5.9486G	107.43	Inf	-Inf	98.56	3	Vertical	41	2.28	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 14.75
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.911G	62.40	88.20	-25.80	53.66	3	Horizontal	345	2.86	-	34.94	6.60	32.80
RMS	5.9162G	50.92	68.20	-17.28	42.17	3	Horizontal	345	2.86	-	34.96	6.60	32.81
PK	5.9492G	108.35	Inf	-Inf	99.47	3	Horizontal	345	2.86	-	35.10	6.60	32.82
RMS	5.9486G	98.46	Inf	-Inf	89.59	3	Horizontal	345	2.86	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 14.75
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8936G	59.82	74.00	-14.18	43.93	3	Vertical	22	1.80	-	38.50	8.97	31.58
AV	11.8955G	47.30	54.00	-6.70	31.41	3	Vertical	22	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 14.75
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8941G	66.13	74.00	-7.87	50.24	3	Horizontal	211	1.80	-	38.50	8.97	31.58
AV	11.8952G	53.83	54.00	-0.17	37.94	3	Horizontal	211	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.873G	61.34	88.20	-26.86	52.68	3	Vertical	232	1.78	-	34.85	6.60	32.79
RMS	5.919G	50.12	68.20	-18.08	41.35	3	Vertical	232	1.78	-	34.98	6.60	32.81
PK	6.189G	119.45	Inf	-Inf	109.96	3	Vertical	232	1.78	-	35.46	6.88	32.85
RMS	6.189G	108.57	Inf	-Inf	99.08	3	Vertical	232	1.78	-	35.46	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.749G	60.78	88.20	-27.42	52.53	3	Horizontal	189	2.90	-	34.39	6.60	32.74
RMS	5.925G	50.06	68.20	-18.14	41.27	3	Horizontal	189	2.90	-	35.00	6.60	32.81
PK	6.189G	110.83	Inf	-Inf	101.34	3	Horizontal	189	2.90	-	35.46	6.88	32.85
RMS	6.189G	100.59	Inf	-Inf	91.10	3	Horizontal	189	2.90	-	35.46	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3782G	63.01	74.00	-10.99	46.76	3	Vertical	235	1.80	-	38.66	9.17	31.58
AV	12.3761G	49.12	54.00	-4.88	32.88	3	Vertical	235	1.80	-	38.65	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3784G	67.04	74.00	-6.96	50.79	3	Horizontal	203	1.80	-	38.66	9.17	31.58
AV	12.3761G	53.08	54.00	-0.92	36.84	3	Horizontal	203	1.80	-	38.65	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5885G	46.93	83.54	-36.61	44.24	1	Vertical	7	1.54	-	37.76	14.94	50.01
AV	18.5887G	33.39	63.54	-30.15	30.70	1	Vertical	7	1.54	-	37.76	14.94	50.01

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.604G	47.11	83.54	-36.43	44.41	1	Horizontal	268	2.98	-	37.76	14.94	50.00
AV	18.6063G	33.44	63.54	-30.10	30.73	1	Horizontal	268	2.98	-	37.76	14.94	49.99

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9222G	61.04	88.20	-27.16	52.26	3	Vertical	223	1.80	-	34.99	6.60	32.81
RMS	5.925G	49.99	68.20	-18.21	41.20	3	Vertical	223	1.80	-	35.00	6.60	32.81
PK	6.4094G	119.52	Inf	-Inf	109.82	3	Vertical	223	1.80	-	35.56	7.00	32.86
RMS	6.4094G	107.44	Inf	-Inf	97.74	3	Vertical	223	1.80	-	35.56	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.813G	60.30	88.20	-27.90	51.97	3	Horizontal	322	1.72	-	34.50	6.60	32.77
RMS	5.925G	50.04	68.20	-18.16	41.25	3	Horizontal	322	1.72	-	35.00	6.60	32.81
PK	6.4094G	112.18	Inf	-Inf	102.48	3	Horizontal	322	1.72	-	35.56	7.00	32.86
RMS	6.4094G	100.22	Inf	-Inf	90.52	3	Horizontal	322	1.72	-	35.56	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8162G	64.38	88.20	-23.82	46.70	3	Vertical	259	1.80	-	39.22	9.37	30.91
RMS	12.816G	51.13	68.20	-17.07	33.45	3	Vertical	259	1.80	-	39.22	9.37	30.91

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8162G	67.89	88.20	-20.31	50.21	3	Horizontal	202	1.87	-	39.22	9.37	30.91
RMS	12.8162G	54.53	68.20	-13.67	36.85	3	Horizontal	202	1.87	-	39.22	9.37	30.91

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2398G	47.16	83.54	-36.38	43.90	1	Vertical	101	2.74	-	37.71	15.20	49.65
AV	19.2287G	33.98	63.54	-29.56	30.71	1	Vertical	101	2.74	-	37.73	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 18.25
01-C-K-4


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.231G	47.05	83.54	-36.49	43.79	1	Horizontal	73	2.08	-	37.72	15.19	49.65
AV	19.2321G	33.95	63.54	-29.59	30.69	1	Horizontal	73	2.08	-	37.72	15.19	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	12.3812G	53.73	54.00	-0.27	3	Horizontal	203	1.80	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.75
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9238G	62.30	88.20	-25.90	53.51	3	Vertical	41	2.30	-	35.00	6.60	32.81
RMS	5.9234G	51.14	68.20	-17.06	42.36	3	Vertical	41	2.30	-	34.99	6.60	32.81
PK	5.9518G	114.00	Inf	-Inf	105.11	3	Vertical	41	2.30	-	35.11	6.60	32.82
RMS	5.9524G	105.54	Inf	-Inf	96.65	3	Vertical	41	2.30	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.75
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9158G	62.30	88.20	-25.90	53.55	3	Horizontal	344	2.86	-	34.96	6.60	32.81
RMS	5.9102G	50.90	68.20	-17.30	42.16	3	Horizontal	344	2.86	-	34.94	6.60	32.80
PK	5.952G	105.38	Inf	-Inf	96.49	3	Horizontal	344	2.86	-	35.11	6.60	32.82
RMS	5.9524G	96.97	Inf	-Inf	88.08	3	Horizontal	344	2.86	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.75
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8966G	59.73	74.00	-14.27	43.84	3	Vertical	18	1.78	-	38.50	8.97	31.58
AV	11.9002G	47.10	54.00	-6.90	31.20	3	Vertical	18	1.78	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.75
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9012G	65.03	74.00	-8.97	49.13	3	Horizontal	199	1.80	-	38.50	8.98	31.58
AV	11.901G	53.61	54.00	-0.39	37.71	3	Horizontal	199	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
01-C-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9058G	60.57	88.20	-27.63	51.85	3	Vertical	233	1.79	-	34.92	6.60	32.80
RMS	5.925G	50.11	68.20	-18.09	41.32	3	Vertical	233	1.79	-	35.00	6.60	32.81
PK	6.1914G	117.30	Inf	-Inf	107.79	3	Vertical	233	1.79	-	35.47	6.89	32.85
RMS	6.1926G	109.43	Inf	-Inf	99.92	3	Vertical	233	1.79	-	35.47	6.89	32.85

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
01-C-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	61.10	88.20	-27.10	52.31	3	Horizontal	183	2.68	-	35.00	6.60	32.81
RMS	5.9214G	50.07	68.20	-18.13	41.29	3	Horizontal	183	2.68	-	34.99	6.60	32.81
PK	6.1938G	110.32	Inf	-Inf	100.80	3	Horizontal	183	2.68	-	35.48	6.89	32.85
RMS	6.1926G	102.37	Inf	-Inf	92.86	3	Horizontal	183	2.68	-	35.47	6.89	32.85

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3824G	62.24	74.00	-11.76	45.99	3	Vertical	235	1.80	-	38.66	9.17	31.58
AV	12.3812G	49.29	54.00	-4.71	33.04	3	Vertical	235	1.80	-	38.66	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.383G	66.53	74.00	-7.47	50.27	3	Horizontal	203	1.80	-	38.67	9.17	31.58
AV	12.3812G	53.73	54.00	-0.27	37.48	3	Horizontal	203	1.80	-	38.66	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6058G	47.22	83.54	-36.32	44.51	1	Vertical	254	2.35	-	37.76	14.94	49.99
AV	18.6041G	33.33	63.54	-30.21	30.63	1	Vertical	254	2.35	-	37.76	14.94	50.00

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58G	46.74	83.54	-36.80	44.06	1	Horizontal	55	1.38	-	37.77	14.93	50.02
AV	18.6098G	33.37	63.54	-30.17	30.66	1	Horizontal	55	1.38	-	37.76	14.94	49.99

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
01-C-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	60.43	88.20	-27.77	51.65	3	Vertical	223	1.80	-	34.99	6.60	32.81
RMS	5.923G	50.00	68.20	-18.20	41.22	3	Vertical	223	1.80	-	34.99	6.60	32.81
PK	6.4126G	116.86	Inf	-Inf	107.17	3	Vertical	223	1.80	-	35.55	7.00	32.86
RMS	6.4126G	108.95	Inf	-Inf	99.26	3	Vertical	223	1.80	-	35.55	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
01-C-K-4-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8774G	61.11	88.20	-27.09	52.45	3	Horizontal	319	1.67	-	34.85	6.60	32.79
RMS	5.925G	50.03	68.20	-18.17	41.24	3	Horizontal	319	1.67	-	35.00	6.60	32.81
PK	6.4126G	109.24	Inf	-Inf	99.55	3	Horizontal	319	1.67	-	35.55	7.00	32.86
RMS	6.4126G	101.61	Inf	-Inf	91.92	3	Horizontal	319	1.67	-	35.55	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8214G	62.80	88.20	-25.40	45.11	3	Vertical	261	1.80	-	39.22	9.37	30.90
RMS	12.8212G	50.58	68.20	-17.62	32.89	3	Vertical	261	1.80	-	39.22	9.37	30.90

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8226G	66.69	88.20	-21.51	49.00	3	Horizontal	206	1.80	-	39.22	9.37	30.90
RMS	12.8212G	54.56	68.20	-13.64	36.87	3	Horizontal	206	1.80	-	39.22	9.37	30.90

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
01-C-K-4

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2444G	47.54	83.54	-36.00	44.28	1	Vertical	238	2.88	-	37.71	15.20	49.65
AV	19.2298G	33.81	63.54	-29.73	30.55	1	Vertical	238	2.88	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 21
01-C-K-4


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2228G	47.61	83.54	-35.93	44.33	1	Horizontal	291	2.97	-	37.73	15.19	49.64
AV	19.2222G	33.65	63.54	-29.89	30.37	1	Horizontal	291	2.97	-	37.73	15.19	49.64

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.8928G	53.78	54.00	-0.22	3	Horizontal	213	1.80	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.25
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.867G	63.25	88.20	-24.95	54.61	3	Vertical	89	1.72	-	34.83	6.60	32.79
RMS	5.9058G	51.63	68.20	-16.57	42.91	3	Vertical	89	1.72	-	34.92	6.60	32.80
PK	5.9466G	120.04	Inf	-Inf	111.17	3	Vertical	89	1.72	-	35.09	6.60	32.82
RMS	5.9466G	110.32	Inf	-Inf	101.45	3	Vertical	89	1.72	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8936G	58.66	74.00	-15.34	42.77	3	Vertical	19	1.80	-	38.50	8.97	31.58
AV	11.8928G	47.07	54.00	-6.93	31.18	3	Vertical	19	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8932G	68.67	74.00	-5.33	52.78	3	Horizontal	213	1.80	-	38.50	8.97	31.58
AV	11.8928G	53.78	54.00	-0.22	37.89	3	Horizontal	213	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7414G	59.52	88.20	-28.68	53.37	3	Vertical	68	1.79	-	34.22	7.40	35.47
RMS	5.925G	47.48	68.20	-20.72	40.82	3	Vertical	68	1.79	-	34.70	7.52	35.56
PK	6.1866G	120.72	Inf	-Inf	113.41	3	Vertical	68	1.79	-	35.15	7.69	35.53
RMS	6.1866G	110.64	Inf	-Inf	103.33	3	Vertical	68	1.79	-	35.15	7.69	35.53

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3726G	60.15	74.00	-13.85	45.60	3	Vertical	228	1.69	-	38.87	11.10	35.42
AV	12.373G	46.51	54.00	-7.49	31.96	3	Vertical	228	1.69	-	38.87	11.10	35.42

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3728G	67.89	74.00	-6.11	53.34	3	Horizontal	205	2.30	-	38.87	11.10	35.42
AV	12.3732G	53.23	54.00	-0.77	38.68	3	Horizontal	205	2.30	-	38.87	11.10	35.42

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5526G	45.38	83.54	-38.16	42.73	1	Vertical	65	1.38	-	37.78	14.92	50.05
AV	18.5468G	32.07	63.54	-31.47	29.42	1	Vertical	65	1.38	-	37.78	14.92	50.05

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 15
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5956G	44.98	83.54	-38.56	42.28	1	Horizontal	106	1.81	-	37.76	14.94	50.00
AV	18.5466G	32.11	63.54	-31.43	29.46	1	Horizontal	106	1.81	-	37.78	14.92	50.05

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7142G	59.49	88.20	-28.71	53.28	3	Vertical	71	1.80	-	34.27	7.40	35.46
RMS	5.919G	47.50	68.20	-20.70	40.86	3	Vertical	71	1.80	-	34.68	7.52	35.56
PK	6.4086G	120.47	Inf	-Inf	113.32	3	Vertical	71	1.80	-	34.87	7.72	35.44
RMS	6.4086G	107.04	Inf	-Inf	99.89	3	Vertical	71	1.80	-	34.87	7.72	35.44
PK	7.199G	61.47	88.20	-26.73	52.42	3	Vertical	71	1.80	-	36.39	8.20	35.54
RMS	7.199G	50.21	68.20	-17.99	41.16	3	Vertical	71	1.80	-	36.39	8.20	35.54

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8122G	59.37	88.20	-28.83	43.28	3	Vertical	227	1.80	-	39.31	11.45	34.67
RMS	12.813G	46.29	68.20	-21.91	30.20	3	Vertical	227	1.80	-	39.31	11.45	34.67

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8136G	68.31	88.20	-19.89	52.22	3	Horizontal	203	2.18	-	39.31	11.45	34.67
RMS	12.813G	52.81	68.20	-15.39	36.72	3	Horizontal	203	2.18	-	39.31	11.45	34.67

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 15.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2096G	46.06	83.54	-37.48	42.77	1	Vertical	184	1.36	-	37.75	15.18	49.64
AV	19.2136G	32.92	63.54	-30.62	29.63	1	Vertical	184	1.36	-	37.74	15.19	49.64

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 15.5
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2434G	46.18	83.54	-37.36	42.92	1	Horizontal	143	1.48	-	37.71	15.20	49.65
AV	19.2138G	32.83	63.54	-30.71	29.54	1	Horizontal	143	1.48	-	37.74	15.19	49.64

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.8952G	53.88	54.00	-0.12	3	Horizontal	213	1.38	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.75
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9178G	67.09	88.20	-21.11	58.33	3	Vertical	70	1.42	-	34.97	6.60	32.81
RMS	5.9182G	51.76	68.20	-16.44	43.00	3	Vertical	70	1.42	-	34.97	6.60	32.81
PK	5.949G	119.39	Inf	-Inf	110.51	3	Vertical	70	1.42	-	35.10	6.60	32.82
RMS	5.9486G	108.73	Inf	-Inf	99.86	3	Vertical	70	1.42	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.75
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9476G	58.95	74.00	-15.05	43.02	3	Vertical	242	1.80	-	38.50	8.99	31.56
AV	11.8952G	46.18	54.00	-7.82	30.29	3	Vertical	242	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 13.75
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8948G	66.75	74.00	-7.25	50.86	3	Horizontal	213	1.38	-	38.50	8.97	31.58
AV	11.8952G	53.88	54.00	-0.12	37.99	3	Horizontal	213	1.38	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.877G	59.04	88.20	-29.16	52.64	3	Vertical	67	1.76	-	34.46	7.48	35.54
RMS	5.919G	48.01	68.20	-20.19	41.37	3	Vertical	67	1.76	-	34.68	7.52	35.56
PK	6.189G	121.29	Inf	-Inf	113.96	3	Vertical	67	1.76	-	35.16	7.69	35.52
RMS	6.189G	112.04	Inf	-Inf	104.71	3	Vertical	67	1.76	-	35.16	7.69	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3762G	58.65	74.00	-15.35	44.08	3	Vertical	282	1.73	-	38.88	11.10	35.41
AV	12.376G	45.70	54.00	-8.30	31.13	3	Vertical	282	1.73	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3782G	66.87	74.00	-7.13	52.30	3	Horizontal	203	2.16	-	38.88	11.10	35.41
AV	12.376G	52.89	54.00	-1.11	38.32	3	Horizontal	203	2.16	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6338G	46.10	83.54	-37.44	43.37	1	Vertical	15	1.88	-	37.75	14.95	49.97
AV	18.535G	32.15	63.54	-31.39	29.51	1	Vertical	15	1.88	-	37.79	14.91	50.06

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 17.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6028G	45.44	83.54	-38.10	42.74	1	Horizontal	184	2.23	-	37.76	14.94	50.00
AV	18.535G	32.16	63.54	-31.38	29.52	1	Horizontal	184	2.23	-	37.79	14.91	50.06

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.919G	59.20	88.20	-29.00	52.56	3	Vertical	67	1.67	-	34.68	7.52	35.56
RMS	5.925G	47.90	68.20	-20.30	41.24	3	Vertical	67	1.67	-	34.70	7.52	35.56
PK	6.4086G	119.86	Inf	-Inf	112.71	3	Vertical	67	1.67	-	34.87	7.72	35.44
RMS	6.4086G	110.98	Inf	-Inf	103.83	3	Vertical	67	1.67	-	34.87	7.72	35.44
PK	7.167G	61.58	88.20	-26.62	52.71	3	Vertical	67	1.67	-	36.20	8.20	35.53
RMS	7.2054G	50.67	68.20	-17.53	41.57	3	Vertical	67	1.67	-	36.43	8.21	35.54

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8184G	59.73	88.20	-28.47	43.62	3	Vertical	255	1.56	-	39.32	11.45	34.66
RMS	12.8162G	46.59	68.20	-21.61	30.48	3	Vertical	255	1.56	-	39.32	11.45	34.66

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8182G	66.19	88.20	-22.01	50.08	3	Horizontal	202	2.09	-	39.32	11.45	34.66
RMS	12.8162G	52.66	68.20	-15.54	36.55	3	Horizontal	202	2.09	-	39.32	11.45	34.66

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 18.25
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2288G	46.34	83.54	-37.20	43.07	1	Vertical	350	1.62	-	37.73	15.19	49.65
AV	19.2222G	33.06	63.54	-30.48	29.78	1	Vertical	350	1.62	-	37.73	15.19	49.64

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 18.25
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.1954G	46.22	83.54	-37.32	42.91	1	Horizontal	113	1.06	-	37.77	15.18	49.64
AV	19.2166G	32.94	63.54	-30.60	29.65	1	Horizontal	113	1.06	-	37.74	15.19	49.64

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_1TX	Pass	AV	11.901G	53.76	54.00	-0.24	3	Horizontal	201	1.92	-

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9234G	81.39	88.20	-6.81	72.61	3	Vertical	92	1.80	-	34.99	6.60	32.81
RMS	5.9218G	53.07	68.20	-15.13	44.29	3	Vertical	92	1.80	-	34.99	6.60	32.81
PK	5.9518G	115.01	Inf	-Inf	106.12	3	Vertical	92	1.80	-	35.11	6.60	32.82
RMS	5.9522G	105.99	Inf	-Inf	97.10	3	Vertical	92	1.80	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8886G	58.45	74.00	-15.55	42.56	3	Vertical	57	1.80	-	38.50	8.97	31.58
AV	11.9024G	45.83	54.00	-8.17	29.93	3	Vertical	57	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

5955MHz_TnomVnom




EUT Y_1TX
Setting 15.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9014G	65.63	74.00	-8.37	49.73	3	Horizontal	201	1.92	-	38.50	8.98	31.58
AV	11.901G	53.76	54.00	-0.24	37.86	3	Horizontal	201	1.92	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.875G	59.60	88.20	-28.60	53.22	3	Vertical	69	1.70	-	34.45	7.47	35.54
RMS	5.923G	47.88	68.20	-20.32	41.23	3	Vertical	69	1.70	-	34.69	7.52	35.56
PK	6.193G	119.70	Inf	-Inf	112.35	3	Vertical	69	1.70	-	35.17	7.70	35.52
RMS	6.193G	111.62	Inf	-Inf	104.27	3	Vertical	69	1.70	-	35.17	7.70	35.52

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3826G	59.96	74.00	-14.04	45.38	3	Vertical	233	1.71	-	38.88	11.11	35.41
AV	12.3814G	47.40	54.00	-6.60	32.82	3	Vertical	233	1.71	-	38.88	11.11	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3826G	65.00	74.00	-9.00	50.42	3	Horizontal	208	2.46	-	38.88	11.11	35.41
AV	12.3812G	52.97	54.00	-1.03	38.40	3	Horizontal	208	2.46	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6236G	46.92	83.54	-36.62	44.20	1	Vertical	339	1.28	-	37.75	14.95	49.98
AV	18.6296G	32.89	63.54	-30.65	30.16	1	Vertical	339	1.28	-	37.75	14.95	49.97

802.11ax HEW20_Nss1,(MCS0)_1TX

6195MHz_TnomVnom




EUT Y_1TX
Setting 20.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5756G	46.89	83.54	-36.65	44.21	1	Horizontal	84	1.52	-	37.77	14.93	50.02
AV	18.6196G	33.02	63.54	-30.52	30.30	1	Horizontal	84	1.52	-	37.75	14.95	49.98

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.89G	58.52	88.20	-29.68	52.04	3	Vertical	68	1.80	-	34.54	7.49	35.55
RMS	5.908G	47.81	68.20	-20.39	41.22	3	Vertical	68	1.80	-	34.63	7.51	35.55
PK	6.412G	119.68	Inf	-Inf	112.55	3	Vertical	68	1.80	-	34.85	7.72	35.44
RMS	6.412G	111.26	Inf	-Inf	104.13	3	Vertical	68	1.80	-	34.85	7.72	35.44
PK	7.132G	61.26	88.20	-26.94	52.59	3	Vertical	68	1.80	-	35.99	8.20	35.52
RMS	7.147G	50.34	68.20	-17.86	41.59	3	Vertical	68	1.80	-	36.08	8.20	35.53

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8216G	58.98	88.20	-29.22	42.85	3	Vertical	218	1.80	-	39.32	11.46	34.65
RMS	12.8212G	45.78	68.20	-22.42	29.65	3	Vertical	218	1.80	-	39.32	11.46	34.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8228G	65.08	88.20	-23.12	48.95	3	Horizontal	209	2.17	-	39.32	11.46	34.65
RMS	12.8212G	52.74	68.20	-15.46	36.61	3	Horizontal	209	2.17	-	39.32	11.46	34.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom




EUT Y_1TX
Setting 21
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2614G	47.28	83.54	-36.26	44.02	1	Vertical	78	1.39	-	37.71	15.20	49.65
AV	19.2368G	34.01	63.54	-29.53	30.75	1	Vertical	78	1.39	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX

6415MHz_TnomVnom



EUT Y_1TX
Setting 21
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2666G	47.60	83.54	-35.94	44.33	1	Horizontal	148	2.93	-	37.71	15.21	49.65
AV	19.225G	34.04	63.54	-29.50	30.77	1	Horizontal	148	2.93	-	37.73	15.19	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.8929G	53.94	54.00	-0.06	3	Horizontal	209	1.80	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 12.75
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.92G	62.11	88.20	-26.09	53.34	3	Vertical	47	1.23	-	34.98	6.60	32.81
RMS	5.906G	50.67	68.20	-17.53	41.95	3	Vertical	47	1.23	-	34.92	6.60	32.80
PK	5.947G	118.35	Inf	-Inf	109.48	3	Vertical	47	1.23	-	35.09	6.60	32.82
RMS	5.9466G	103.66	Inf	-Inf	94.79	3	Vertical	47	1.23	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 12.75
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9086G	62.52	88.20	-25.68	53.79	3	Horizontal	45	2.31	-	34.93	6.60	32.80
RMS	5.9058G	50.69	68.20	-17.51	41.97	3	Horizontal	45	2.31	-	34.92	6.60	32.80
PK	5.9468G	117.47	Inf	-Inf	108.60	3	Horizontal	45	2.31	-	35.09	6.60	32.82
RMS	5.9468G	107.83	Inf	-Inf	98.96	3	Horizontal	45	2.31	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 12.75
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8931G	60.61	74.00	-13.39	44.72	3	Vertical	253	1.80	-	38.50	8.97	31.58
AV	11.893G	46.94	54.00	-7.06	31.05	3	Vertical	253	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 12.75
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8931G	68.60	74.00	-5.40	52.71	3	Horizontal	209	1.80	-	38.50	8.97	31.58
AV	11.8929G	53.94	54.00	-0.06	38.05	3	Horizontal	209	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.809G	61.62	88.20	-26.58	53.31	3	Vertical	222	1.56	-	34.47	6.60	32.76
RMS	5.925G	50.17	68.20	-18.03	41.38	3	Vertical	222	1.56	-	35.00	6.60	32.81
PK	6.187G	113.97	Inf	-Inf	104.49	3	Vertical	222	1.56	-	35.45	6.88	32.85
RMS	6.187G	103.09	Inf	-Inf	93.61	3	Vertical	222	1.56	-	35.45	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.897G	61.64	88.20	-26.56	52.95	3	Horizontal	338	1.73	-	34.89	6.60	32.80
RMS	5.919G	50.18	68.20	-18.02	41.41	3	Horizontal	338	1.73	-	34.98	6.60	32.81
PK	6.187G	116.31	Inf	-Inf	106.83	3	Horizontal	338	1.73	-	35.45	6.88	32.85
RMS	6.187G	104.47	Inf	-Inf	94.99	3	Horizontal	338	1.73	-	35.45	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3756G	57.90	74.00	-16.10	41.66	3	Vertical	78	1.80	-	38.65	9.17	31.58
AV	12.4192G	44.23	54.00	-9.77	27.96	3	Vertical	78	1.80	-	38.66	9.19	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3728G	58.82	74.00	-15.18	42.58	3	Horizontal	212	1.80	-	38.65	9.17	31.58
AV	12.3726G	45.29	54.00	-8.71	29.05	3	Horizontal	212	1.80	-	38.65	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6228G	46.88	83.54	-36.66	44.16	1	Vertical	211	1.86	-	37.75	14.95	49.98
AV	18.6316G	33.55	63.54	-29.99	30.82	1	Vertical	211	1.86	-	37.75	14.95	49.97

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6154G	47.11	83.54	-36.43	44.39	1	Horizontal	113	2.57	-	37.75	14.95	49.98
AV	18.6346G	33.54	63.54	-30.00	30.81	1	Horizontal	113	2.57	-	37.75	14.95	49.97

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9194G	61.00	88.20	-27.20	52.23	3	Vertical	217	1.80	-	34.98	6.60	32.81
RMS	5.9194G	50.17	68.20	-18.03	41.40	3	Vertical	217	1.80	-	34.98	6.60	32.81
PK	6.4066G	113.77	Inf	-Inf	104.06	3	Vertical	217	1.80	-	35.57	7.00	32.86
RMS	6.4066G	101.60	Inf	-Inf	91.89	3	Vertical	217	1.80	-	35.57	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8858G	61.27	88.20	-26.93	52.59	3	Horizontal	335	1.80	-	34.87	6.60	32.79
RMS	5.925G	50.18	68.20	-18.02	41.39	3	Horizontal	335	1.80	-	35.00	6.60	32.81
PK	6.4066G	114.75	Inf	-Inf	105.04	3	Horizontal	335	1.80	-	35.57	7.00	32.86
RMS	6.4066G	102.72	Inf	-Inf	93.01	3	Horizontal	335	1.80	-	35.57	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8732G	60.30	88.20	-27.90	42.43	3	Vertical	313	1.80	-	39.27	9.39	30.79
RMS	12.8722G	45.29	68.20	-22.91	27.42	3	Vertical	313	1.80	-	39.27	9.39	30.79

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8136G	59.96	88.20	-28.24	42.30	3	Horizontal	215	1.80	-	39.21	9.37	30.92
RMS	12.813G	46.14	68.20	-22.06	28.48	3	Horizontal	215	1.80	-	39.21	9.37	30.92

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 11
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.1992G	47.49	83.54	-36.05	44.19	1	Vertical	275	2.08	-	37.76	15.18	49.64
AV	19.2182G	33.88	63.54	-29.66	30.59	1	Vertical	275	2.08	-	37.74	15.19	49.64

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 11
01-C-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.1972G	47.34	83.54	-36.20	44.04	1	Horizontal	318	2.76	-	37.76	15.18	49.64
AV	19.2028G	33.86	63.54	-29.68	30.56	1	Horizontal	318	2.76	-	37.76	15.18	49.64

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.8952G	53.68	54.00	-0.32	3	Horizontal	208	1.80	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9094G	66.49	88.20	-21.71	57.75	3	Vertical	73	1.80	-	34.94	6.60	32.80
RMS	5.925G	50.56	68.20	-17.64	41.77	3	Vertical	73	1.80	-	35.00	6.60	32.81
PK	5.9492G	116.49	Inf	-Inf	107.61	3	Vertical	73	1.80	-	35.10	6.60	32.82
RMS	5.9486G	104.88	Inf	-Inf	96.01	3	Vertical	73	1.80	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9164G	62.34	88.20	-25.86	53.58	3	Horizontal	358	1.79	-	34.97	6.60	32.81
RMS	5.9066G	50.51	68.20	-17.69	41.78	3	Horizontal	358	1.79	-	34.93	6.60	32.80
PK	5.9492G	116.18	Inf	-Inf	107.30	3	Horizontal	358	1.79	-	35.10	6.60	32.82
RMS	5.9486G	103.92	Inf	-Inf	95.05	3	Horizontal	358	1.79	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8964G	59.60	74.00	-14.40	43.71	3	Vertical	5	1.80	-	38.50	8.97	31.58
AV	11.8943G	47.38	54.00	-6.62	31.49	3	Vertical	5	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8947G	66.89	74.00	-7.11	51.00	3	Horizontal	208	1.80	-	38.50	8.97	31.58
AV	11.8952G	53.68	54.00	-0.32	37.79	3	Horizontal	208	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 15.25
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.717G	61.17	88.20	-27.03	53.16	3	Vertical	210	1.09	-	34.14	6.60	32.73
RMS	5.925G	50.12	68.20	-18.08	41.33	3	Vertical	210	1.09	-	35.00	6.60	32.81
PK	6.189G	118.00	Inf	-Inf	108.51	3	Vertical	210	1.09	-	35.46	6.88	32.85
RMS	6.189G	104.70	Inf	-Inf	95.21	3	Vertical	210	1.09	-	35.46	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 15.25
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.885G	61.21	88.20	-26.99	52.53	3	Horizontal	330	1.80	-	34.87	6.60	32.79
RMS	5.923G	50.18	68.20	-18.02	41.40	3	Horizontal	330	1.80	-	34.99	6.60	32.81
PK	6.189G	118.41	Inf	-Inf	108.92	3	Horizontal	330	1.80	-	35.46	6.88	32.85
RMS	6.189G	104.93	Inf	-Inf	95.44	3	Horizontal	330	1.80	-	35.46	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 15.25
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.4041G	59.46	74.00	-14.54	43.17	3	Vertical	226	1.80	-	38.69	9.18	31.58
AV	12.405G	45.26	54.00	-8.74	28.97	3	Vertical	226	1.80	-	38.69	9.18	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 15.25
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.4045G	62.49	74.00	-11.51	46.20	3	Horizontal	205	1.79	-	38.69	9.18	31.58
AV	12.4046G	47.67	54.00	-6.33	31.38	3	Horizontal	205	1.79	-	38.69	9.18	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 15.25
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59604G	46.88	83.54	-36.66	44.18	1	Vertical	320	1.01	-	37.76	14.94	50.00
AV	18.59646G	33.22	63.54	-30.32	30.52	1	Vertical	320	1.01	-	37.76	14.94	50.00

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 15.25
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59964G	47.55	83.54	-35.99	44.85	1	Horizontal	116	2.03	-	37.76	14.94	50.00
AV	18.59964G	33.22	63.54	-30.32	30.52	1	Horizontal	116	2.03	-	37.76	14.94	50.00

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.919G	61.22	88.20	-26.98	52.45	3	Vertical	216	1.75	-	34.98	6.60	32.81
RMS	5.919G	50.07	68.20	-18.13	41.30	3	Vertical	216	1.75	-	34.98	6.60	32.81
PK	6.4086G	114.18	Inf	-Inf	104.47	3	Vertical	216	1.75	-	35.57	7.00	32.86
RMS	6.4086G	103.57	Inf	-Inf	93.86	3	Vertical	216	1.75	-	35.57	7.00	32.86
PK	7.151G	63.50	88.20	-24.70	52.48	3	Vertical	216	1.75	-	36.90	7.22	33.10
RMS	7.199G	53.28	68.20	-14.92	42.10	3	Vertical	216	1.75	-	37.10	7.20	33.12

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.6406G	60.70	88.20	-27.50	52.76	3	Horizontal	345	1.80	-	34.04	6.60	32.70
RMS	5.9222G	50.10	68.20	-18.10	41.32	3	Horizontal	345	1.80	-	34.99	6.60	32.81
PK	6.4086G	115.33	Inf	-Inf	105.62	3	Horizontal	345	1.80	-	35.57	7.00	32.86
RMS	6.4086G	104.31	Inf	-Inf	94.60	3	Horizontal	345	1.80	-	35.57	7.00	32.86
PK	7.1606G	64.19	88.20	-24.01	53.13	3	Horizontal	345	1.80	-	36.94	7.22	33.10
RMS	7.215G	53.32	68.20	-14.88	42.13	3	Horizontal	345	1.80	-	37.10	7.22	33.13

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.84356G	60.88	88.20	-27.32	43.11	3	Vertical	301	1.80	-	39.24	9.38	30.85
RMS	12.8438G	46.36	68.20	-21.84	28.59	3	Vertical	301	1.80	-	39.24	9.38	30.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8435G	64.85	88.20	-23.35	47.08	3	Horizontal	201	1.82	-	39.24	9.38	30.85
RMS	12.84392G	49.73	68.20	-18.47	31.96	3	Horizontal	201	1.82	-	39.24	9.38	30.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2423G	48.86	83.54	-34.68	45.60	1	Vertical	286	2.56	-	37.71	15.20	49.65
AV	19.23066G	33.70	63.54	-29.84	30.44	1	Vertical	286	2.56	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 13.75
01-C-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.25268G	46.97	83.54	-36.57	43.72	1	Horizontal	267	1.24	-	37.70	15.20	49.65
AV	19.23024G	33.70	63.54	-29.84	30.44	1	Horizontal	267	1.24	-	37.72	15.19	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.9013G	53.63	54.00	-0.37	3	Horizontal	220	1.77	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 16
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	71.43	88.20	-16.77	62.64	3	Vertical	47	1.23	-	35.00	6.60	32.81
RMS	5.925G	52.83	68.20	-15.37	44.04	3	Vertical	47	1.23	-	35.00	6.60	32.81
PK	5.952G	116.02	Inf	-Inf	107.13	3	Vertical	47	1.23	-	35.11	6.60	32.82
RMS	5.9524G	105.32	Inf	-Inf	96.43	3	Vertical	47	1.23	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 16
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9248G	67.57	88.20	-20.63	58.78	3	Horizontal	44	2.32	-	35.00	6.60	32.81
RMS	5.9244G	50.94	68.20	-17.26	42.15	3	Horizontal	44	2.32	-	35.00	6.60	32.81
PK	5.952G	114.33	Inf	-Inf	105.44	3	Horizontal	44	2.32	-	35.11	6.60	32.82
RMS	5.9498G	104.29	Inf	-Inf	95.41	3	Horizontal	44	2.32	-	35.10	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 16
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9028G	60.01	74.00	-13.99	44.11	3	Vertical	265	1.80	-	38.50	8.98	31.58
AV	11.9013G	45.97	54.00	-8.03	30.07	3	Vertical	265	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 16
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9027G	67.32	74.00	-6.68	51.42	3	Horizontal	220	1.77	-	38.50	8.98	31.58
AV	11.9013G	53.63	54.00	-0.37	37.73	3	Horizontal	220	1.77	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7862G	60.86	88.20	-27.34	52.61	3	Vertical	213	1.37	-	34.40	6.60	32.75
RMS	5.9178G	50.15	68.20	-18.05	41.39	3	Vertical	213	1.37	-	34.97	6.60	32.81
PK	6.1922G	115.26	Inf	-Inf	105.75	3	Vertical	213	1.37	-	35.47	6.89	32.85
RMS	6.1922G	104.55	Inf	-Inf	95.04	3	Vertical	213	1.37	-	35.47	6.89	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8366G	61.40	88.20	-26.80	52.88	3	Horizontal	339	1.80	-	34.69	6.60	32.77
RMS	5.925G	50.13	68.20	-18.07	41.34	3	Horizontal	339	1.80	-	35.00	6.60	32.81
PK	6.1922G	115.58	Inf	-Inf	106.07	3	Horizontal	339	1.80	-	35.47	6.89	32.85
RMS	6.1922G	104.63	Inf	-Inf	95.12	3	Horizontal	339	1.80	-	35.47	6.89	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3805G	59.03	74.00	-14.97	42.78	3	Vertical	228	1.80	-	38.66	9.17	31.58
AV	12.3804G	44.80	54.00	-9.20	28.55	3	Vertical	228	1.80	-	38.66	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3825G	62.75	74.00	-11.25	46.50	3	Horizontal	204	1.80	-	38.66	9.17	31.58
AV	12.3844G	47.63	54.00	-6.37	31.37	3	Horizontal	204	1.80	-	38.67	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5778G	46.74	83.54	-36.80	44.06	1	Vertical	233	2.37	-	37.77	14.93	50.02
AV	18.6061G	33.37	63.54	-30.17	30.66	1	Vertical	233	2.37	-	37.76	14.94	49.99

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5826G	47.23	83.54	-36.31	44.55	1	Horizontal	51	1.73	-	37.77	14.93	50.02
AV	18.6062G	33.39	63.54	-30.15	30.68	1	Horizontal	51	1.73	-	37.76	14.94	49.99

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16.25
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	61.09	88.20	-27.11	52.30	3	Vertical	210	1.14	-	35.00	6.60	32.81
RMS	5.9222G	50.13	68.20	-18.07	41.35	3	Vertical	210	1.14	-	34.99	6.60	32.81
PK	6.4122G	116.00	Inf	-Inf	106.31	3	Vertical	210	1.14	-	35.55	7.00	32.86
RMS	6.4122G	105.30	Inf	-Inf	95.61	3	Vertical	210	1.14	-	35.55	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16.25
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8242G	60.38	88.20	-27.82	51.96	3	Horizontal	340	1.80	-	34.59	6.60	32.77
RMS	5.9222G	50.09	68.20	-18.11	41.31	3	Horizontal	340	1.80	-	34.99	6.60	32.81
PK	6.4122G	115.07	Inf	-Inf	105.38	3	Horizontal	340	1.80	-	35.55	7.00	32.86
RMS	6.4122G	105.95	Inf	-Inf	96.26	3	Horizontal	340	1.80	-	35.55	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16.25
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8215G	61.33	88.20	-26.87	43.64	3	Vertical	303	1.14	-	39.22	9.37	30.90
RMS	12.8213G	47.50	68.20	-20.70	29.81	3	Vertical	303	1.14	-	39.22	9.37	30.90

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16.25
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8238G	64.71	88.20	-23.49	47.02	3	Horizontal	202	1.80	-	39.22	9.37	30.90
RMS	12.8213G	50.73	68.20	-17.47	33.04	3	Horizontal	202	1.80	-	39.22	9.37	30.90

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16.25
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2204G	47.95	83.54	-35.59	44.66	1	Vertical	314	2.77	-	37.74	15.19	49.64
AV	19.2243G	33.81	63.54	-29.73	30.53	1	Vertical	314	2.77	-	37.73	15.19	49.64

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 16.25
01-C-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2436G	47.45	83.54	-36.09	44.19	1	Horizontal	277	2.60	-	37.71	15.20	49.65
AV	19.2235G	33.81	63.54	-29.73	30.53	1	Horizontal	277	2.60	-	37.73	15.19	49.64

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.89288G	53.67	54.00	-0.33	3	Horizontal	211	1.80	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9062G	63.42	88.20	-24.78	54.70	3	Vertical	60	1.80	-	34.92	6.60	32.80
RMS	5.9244G	50.85	68.20	-17.35	42.06	3	Vertical	60	1.80	-	35.00	6.60	32.81
PK	5.9466G	112.98	Inf	-Inf	104.11	3	Vertical	60	1.80	-	35.09	6.60	32.82
RMS	5.9468G	98.50	Inf	-Inf	89.63	3	Vertical	60	1.80	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9154G	62.35	88.20	-25.85	53.60	3	Horizontal	60	1.78	-	34.96	6.60	32.81
AV	5.9162G	50.85	68.20	-17.35	42.10	3	Horizontal	60	1.78	-	34.96	6.60	32.81
PK	5.9468G	113.64	Inf	-Inf	104.77	3	Horizontal	60	1.78	-	35.09	6.60	32.82
AV	5.9462G	97.99	Inf	-Inf	89.13	3	Horizontal	60	1.78	-	35.08	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89352G	60.05	74.00	-13.95	44.16	3	Vertical	24	1.74	-	38.50	8.97	31.58
AV	11.8928G	47.29	54.00	-6.71	31.40	3	Vertical	24	1.74	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89296G	67.31	74.00	-6.69	51.42	3	Horizontal	211	1.80	-	38.50	8.97	31.58
AV	11.89288G	53.67	54.00	-0.33	37.78	3	Horizontal	211	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	61.12	88.20	-27.08	52.33	3	Vertical	27	1.80	-	35.00	6.60	32.81
RMS	5.925G	49.99	68.20	-18.21	41.20	3	Vertical	27	1.80	-	35.00	6.60	32.81
PK	6.1866G	115.46	Inf	-Inf	105.98	3	Vertical	27	1.80	-	35.45	6.88	32.85
RMS	6.1866G	103.23	Inf	-Inf	93.75	3	Vertical	27	1.80	-	35.45	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9046G	62.13	88.20	-26.07	53.41	3	Horizontal	144	1.80	-	34.92	6.60	32.80
RMS	5.9238G	50.00	68.20	-18.20	41.21	3	Horizontal	144	1.80	-	35.00	6.60	32.81
PK	6.1866G	107.79	Inf	-Inf	98.31	3	Horizontal	144	1.80	-	35.45	6.88	32.85
RMS	6.1866G	97.31	Inf	-Inf	87.83	3	Horizontal	144	1.80	-	35.45	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38982G	58.31	74.00	-15.69	42.03	3	Vertical	205	2.31	-	38.68	9.18	31.58
AV	12.39018G	44.52	54.00	-9.48	28.24	3	Vertical	205	2.31	-	38.68	9.18	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38938G	57.52	74.00	-16.48	41.24	3	Horizontal	24	2.36	-	38.68	9.18	31.58
AV	12.38968G	43.83	54.00	-10.17	27.55	3	Horizontal	24	2.36	-	38.68	9.18	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58366G	46.95	83.54	-36.59	44.27	1	Vertical	254	2.29	-	37.77	14.93	50.02
AV	18.58421G	33.78	63.54	-29.76	31.10	1	Vertical	254	2.29	-	37.77	14.93	50.02

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58675G	46.81	83.54	-36.73	44.12	1	Horizontal	282	1.95	-	37.77	14.93	50.01
AV	18.58554G	33.83	63.54	-29.71	31.14	1	Horizontal	282	1.95	-	37.77	14.93	50.01

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8558G	61.59	88.20	-26.61	52.96	3	Vertical	1	1.80	-	34.81	6.60	32.78
RMS	5.923G	49.90	68.20	-18.30	41.12	3	Vertical	1	1.80	-	34.99	6.60	32.81
PK	6.4078G	116.36	Inf	-Inf	106.65	3	Vertical	1	1.80	-	35.57	7.00	32.86
RMS	6.4078G	102.82	Inf	-Inf	93.11	3	Vertical	1	1.80	-	35.57	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.923G	60.93	88.20	-27.27	52.15	3	Horizontal	140	1.75	-	34.99	6.60	32.81
RMS	5.925G	49.88	68.20	-18.32	41.09	3	Horizontal	140	1.75	-	35.00	6.60	32.81
PK	6.4078G	109.38	Inf	-Inf	99.67	3	Horizontal	140	1.75	-	35.57	7.00	32.86
RMS	6.4078G	95.37	Inf	-Inf	85.66	3	Horizontal	140	1.75	-	35.57	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8307G	58.46	88.20	-29.74	40.74	3	Vertical	109	1.81	-	39.23	9.37	30.88
RMS	12.82832G	44.37	68.20	-23.83	26.66	3	Vertical	109	1.81	-	39.23	9.37	30.89

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.82955G	58.18	88.20	-30.02	40.46	3	Horizontal	164	2.32	-	39.23	9.37	30.88
RMS	12.83051G	44.38	68.20	-23.82	26.66	3	Horizontal	164	2.32	-	39.23	9.37	30.88

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
01-C-K-3

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.24598G	46.67	83.54	-36.87	43.42	1	Vertical	173	1.82	-	37.70	15.20	49.65
AV	19.24492G	33.27	63.54	-30.27	30.01	1	Vertical	173	1.82	-	37.71	15.20	49.65

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 10.75
01-C-K-3


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.24458G	46.91	83.54	-36.63	43.65	1	Horizontal	116	2.07	-	37.71	15.20	49.65
AV	19.243G	33.25	63.54	-30.29	29.99	1	Horizontal	116	2.07	-	37.71	15.20	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.89528G	53.54	54.00	-0.46	3	Horizontal	211	1.80	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9174G	67.28	88.20	-20.92	58.52	3	Vertical	41	2.29	-	34.97	6.60	32.81
RMS	5.9186G	51.63	68.20	-16.57	42.87	3	Vertical	41	2.29	-	34.97	6.60	32.81
PK	5.9492G	122.64	Inf	-Inf	113.76	3	Vertical	41	2.29	-	35.10	6.60	32.82
RMS	5.9472G	110.52	Inf	-Inf	101.65	3	Vertical	41	2.29	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-M-G-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9168G	63.63	88.20	-24.57	54.87	3	Horizontal	59	1.85	-	34.97	6.60	32.81
AV	5.9164G	50.92	68.20	-17.28	42.16	3	Horizontal	59	1.85	-	34.97	6.60	32.81
PK	5.9492G	113.09	Inf	-Inf	104.21	3	Horizontal	59	1.85	-	35.10	6.60	32.82
AV	5.9474G	100.67	Inf	-Inf	91.80	3	Horizontal	59	1.85	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89416G	60.90	74.00	-13.10	45.01	3	Vertical	24	1.71	-	38.50	8.97	31.58
AV	11.89528G	47.45	54.00	-6.55	31.56	3	Vertical	24	1.71	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-M-G-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.89408G	65.44	74.00	-8.56	49.55	3	Horizontal	211	1.80	-	38.50	8.97	31.58
AV	11.89528G	53.54	54.00	-0.46	37.65	3	Horizontal	211	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.847G	60.73	88.20	-27.47	52.13	3	Vertical	237	1.79	-	34.78	6.60	32.78
RMS	5.925G	50.15	68.20	-18.05	41.36	3	Vertical	237	1.79	-	35.00	6.60	32.81
PK	6.189G	114.71	Inf	-Inf	105.22	3	Vertical	237	1.79	-	35.46	6.88	32.85
RMS	6.189G	104.65	Inf	-Inf	95.16	3	Vertical	237	1.79	-	35.46	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.867G	61.40	88.20	-26.80	52.76	3	Horizontal	61	1.78	-	34.83	6.60	32.79
RMS	5.923G	50.19	68.20	-18.01	41.41	3	Horizontal	61	1.78	-	34.99	6.60	32.81
PK	6.189G	109.86	Inf	-Inf	100.37	3	Horizontal	61	1.78	-	35.46	6.88	32.85
RMS	6.189G	97.57	Inf	-Inf	88.08	3	Horizontal	61	1.78	-	35.46	6.88	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3949G	58.22	74.00	-15.78	41.93	3	Vertical	230	1.80	-	38.69	9.18	31.58
AV	12.3754G	44.58	54.00	-9.42	28.34	3	Vertical	230	1.80	-	38.65	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3766G	57.82	74.00	-16.18	41.58	3	Horizontal	160	1.71	-	38.65	9.17	31.58
AV	12.3755G	44.58	54.00	-9.42	28.34	3	Horizontal	160	1.71	-	38.65	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5873G	47.26	83.54	-36.28	44.57	1	Vertical	245	1.05	-	37.77	14.93	50.01
AV	18.6054G	33.42	63.54	-30.12	30.71	1	Vertical	245	1.05	-	37.76	14.94	49.99

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6058G	47.24	83.54	-36.30	44.53	1	Horizontal	63	1.67	-	37.76	14.94	49.99
AV	18.608G	33.39	63.54	-30.15	30.68	1	Horizontal	63	1.67	-	37.76	14.94	49.99

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9138G	61.18	88.20	-27.02	52.43	3	Vertical	71	1.52	-	34.96	6.60	32.81
RMS	5.925G	50.19	68.20	-18.01	41.40	3	Vertical	71	1.52	-	35.00	6.60	32.81
PK	6.4094G	115.54	Inf	-Inf	105.84	3	Vertical	71	1.52	-	35.56	7.00	32.86
RMS	6.4094G	105.41	Inf	-Inf	95.71	3	Vertical	71	1.52	-	35.56	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8214G	61.49	88.20	-26.71	53.09	3	Horizontal	62	1.68	-	34.57	6.60	32.77
RMS	5.9222G	50.15	68.20	-18.05	41.37	3	Horizontal	62	1.68	-	34.99	6.60	32.81
PK	6.4094G	110.44	Inf	-Inf	100.74	3	Horizontal	62	1.68	-	35.56	7.00	32.86
RMS	6.4094G	96.10	Inf	-Inf	86.40	3	Horizontal	62	1.68	-	35.56	7.00	32.86

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8181G	60.08	88.20	-28.12	42.40	3	Vertical	274	1.80	-	39.22	9.37	30.91
RMS	12.8163G	45.98	68.20	-22.22	28.30	3	Vertical	274	1.80	-	39.22	9.37	30.91

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8149G	62.75	88.20	-25.45	45.09	3	Horizontal	209	1.80	-	39.21	9.37	30.92
RMS	12.8155G	48.29	68.20	-19.91	30.61	3	Horizontal	209	1.80	-	39.22	9.37	30.91

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2483G	47.36	83.54	-36.18	44.11	1	Vertical	356	2.42	-	37.70	15.20	49.65
AV	19.2237G	33.73	63.54	-29.81	30.45	1	Vertical	356	2.42	-	37.73	15.19	49.64

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 13.75
01-C-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2229G	47.28	83.54	-36.26	44.00	1	Horizontal	24	2.26	-	37.73	15.19	49.64
AV	19.2216G	33.72	63.54	-29.82	30.44	1	Horizontal	24	2.26	-	37.73	15.19	49.64

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.90104G	53.52	54.00	-0.48	3	Horizontal	200	1.80	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9242G	67.23	88.20	-20.97	58.44	3	Vertical	41	2.30	-	35.00	6.60	32.81
RMS	5.925G	52.34	68.20	-15.86	43.55	3	Vertical	41	2.30	-	35.00	6.60	32.81
PK	5.9518G	119.73	Inf	-Inf	110.84	3	Vertical	41	2.30	-	35.11	6.60	32.82
RMS	5.9522G	110.19	Inf	-Inf	101.30	3	Vertical	41	2.30	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-S-8-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.925G	63.54	88.20	-24.66	54.75	3	Horizontal	60	1.86	-	35.00	6.60	32.81
RMS	5.9218G	50.99	68.20	-17.21	42.21	3	Horizontal	60	1.86	-	34.99	6.60	32.81
PK	5.9522G	109.63	Inf	-Inf	100.74	3	Horizontal	60	1.86	-	35.11	6.60	32.82
RMS	5.9522G	97.84	Inf	-Inf	88.95	3	Horizontal	60	1.86	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.90136G	61.03	74.00	-12.97	45.13	3	Vertical	24	1.78	-	38.50	8.98	31.58
AV	11.90112G	48.63	54.00	-5.37	32.73	3	Vertical	24	1.78	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 16.5
01-M-S-8

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.90164G	65.59	74.00	-8.41	49.69	3	Horizontal	200	1.80	-	38.50	8.98	31.58
AV	11.90104G	53.52	54.00	-0.48	37.62	3	Horizontal	200	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.85G	60.50	88.20	-27.70	51.88	3	Vertical	236	1.80	-	34.80	6.60	32.78
RMS	5.9234G	50.28	68.20	-17.92	41.50	3	Vertical	236	1.80	-	34.99	6.60	32.81
PK	6.1922G	115.05	Inf	-Inf	105.54	3	Vertical	236	1.80	-	35.47	6.89	32.85
RMS	6.1922G	104.18	Inf	-Inf	94.67	3	Vertical	236	1.80	-	35.47	6.89	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.859G	61.27	88.20	-26.93	52.63	3	Horizontal	61	1.78	-	34.82	6.60	32.78
RMS	5.9206G	50.23	68.20	-17.97	41.46	3	Horizontal	61	1.78	-	34.98	6.60	32.81
PK	6.1922G	109.09	Inf	-Inf	99.58	3	Horizontal	61	1.78	-	35.47	6.89	32.85
RMS	6.1922G	99.35	Inf	-Inf	89.84	3	Horizontal	61	1.78	-	35.47	6.89	32.85

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.38298G	58.77	74.00	-15.23	42.51	3	Vertical	239	1.78	-	38.67	9.17	31.58
AV	12.38016G	44.85	54.00	-9.15	28.60	3	Vertical	239	1.78	-	38.66	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3825G	63.39	74.00	-10.61	47.14	3	Horizontal	206	1.80	-	38.66	9.17	31.58
AV	12.38448G	47.76	54.00	-6.24	31.50	3	Horizontal	206	1.80	-	38.67	9.17	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.59976G	47.04	83.54	-36.50	44.34	1	Vertical	161	2.54	-	37.76	14.94	50.00
AV	18.59886G	33.29	63.54	-30.25	30.59	1	Vertical	161	2.54	-	37.76	14.94	50.00

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.58986G	47.16	83.54	-36.38	44.47	1	Horizontal	158	2.74	-	37.76	14.94	50.01
AV	18.59586G	33.28	63.54	-30.26	30.58	1	Horizontal	158	2.74	-	37.76	14.94	50.00

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.887G	61.55	88.20	-26.65	52.87	3	Vertical	71	1.26	-	34.87	6.60	32.79
RMS	5.925G	50.20	68.20	-18.00	41.41	3	Vertical	71	1.26	-	35.00	6.60	32.81
PK	6.4118G	116.70	Inf	-Inf	107.01	3	Vertical	71	1.26	-	35.55	7.00	32.86
RMS	6.4118G	106.41	Inf	-Inf	96.72	3	Vertical	71	1.26	-	35.55	7.00	32.86
PK	7.1606G	64.27	88.20	-23.93	53.21	3	Vertical	71	1.26	-	36.94	7.22	33.10
RMS	7.215G	53.45	68.20	-14.75	42.26	3	Vertical	71	1.26	-	37.10	7.22	33.13

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.727G	60.80	88.20	-27.40	52.71	3	Horizontal	60	1.80	-	34.22	6.60	32.73
RMS	5.9222G	50.22	68.20	-17.98	41.44	3	Horizontal	60	1.80	-	34.99	6.60	32.81
PK	6.4118G	108.25	Inf	-Inf	98.56	3	Horizontal	60	1.80	-	35.55	7.00	32.86
RMS	6.4118G	97.50	Inf	-Inf	87.81	3	Horizontal	60	1.80	-	35.55	7.00	32.86
PK	7.183G	64.26	88.20	-23.94	53.14	3	Horizontal	60	1.80	-	37.03	7.21	33.12
RMS	7.1894G	53.36	68.20	-14.84	42.21	3	Horizontal	60	1.80	-	37.06	7.21	33.12

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.82154G	60.88	88.20	-27.32	43.19	3	Vertical	274	1.80	-	39.22	9.37	30.90
RMS	12.82136G	46.68	68.20	-21.52	28.99	3	Vertical	274	1.80	-	39.22	9.37	30.90

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8213G	63.01	88.20	-25.19	45.32	3	Horizontal	199	1.86	-	39.22	9.37	30.90
RMS	12.8213G	48.66	68.20	-19.54	30.97	3	Horizontal	199	1.86	-	39.22	9.37	30.90

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
01-C-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.23744G	48.13	83.54	-35.41	44.87	1	Vertical	92	1.47	-	37.72	15.19	49.65
AV	19.23072G	33.72	63.54	-29.82	30.46	1	Vertical	92	1.47	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 16
01-C-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2597G	47.22	83.54	-36.32	43.96	1	Horizontal	17	1.31	-	37.71	15.20	49.65
AV	19.23096G	33.75	63.54	-29.79	30.49	1	Horizontal	17	1.31	-	37.72	15.19	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.8928G	53.79	54.00	-0.21	3	Horizontal	199	1.80	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.25
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9114G	74.49	88.20	-13.71	65.74	3	Vertical	90	1.79	-	34.95	6.60	32.80
RMS	5.9058G	51.54	68.20	-16.66	42.82	3	Vertical	90	1.79	-	34.92	6.60	32.80
PK	5.947G	124.47	Inf	-Inf	115.60	3	Vertical	90	1.79	-	35.09	6.60	32.82
RMS	5.9466G	111.15	Inf	-Inf	102.28	3	Vertical	90	1.79	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8934G	59.51	74.00	-14.49	43.62	3	Vertical	230	1.80	-	38.50	8.97	31.58
AV	11.8928G	46.91	54.00	-7.09	31.02	3	Vertical	230	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 13.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8932G	67.35	74.00	-6.65	51.46	3	Horizontal	199	1.80	-	38.50	8.97	31.58
AV	11.8928G	53.79	54.00	-0.21	37.90	3	Horizontal	199	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7786G	59.78	88.20	-28.42	53.67	3	Vertical	66	1.80	-	34.20	7.40	35.49
RMS	5.9086G	47.93	68.20	-20.27	41.34	3	Vertical	66	1.80	-	34.63	7.51	35.55
PK	6.1866G	118.28	Inf	-Inf	110.97	3	Vertical	66	1.80	-	35.15	7.69	35.53
RMS	6.1866G	106.84	Inf	-Inf	99.53	3	Vertical	66	1.80	-	35.15	7.69	35.53

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3606G	55.06	74.00	-18.94	40.53	3	Vertical	321	1.93	-	38.86	11.09	35.42
AV	12.3764G	42.09	54.00	-11.91	27.52	3	Vertical	321	1.93	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.415G	55.65	74.00	-18.35	41.05	3	Horizontal	12	2.29	-	38.88	11.13	35.41
AV	12.3762G	42.14	54.00	-11.86	27.57	3	Horizontal	12	2.29	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.582G	46.33	83.54	-37.21	43.65	1	Vertical	58	1.71	-	37.77	14.93	50.02
AV	18.628G	32.85	63.54	-30.69	30.12	1	Vertical	58	1.71	-	37.75	14.95	49.97

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.552G	46.07	83.54	-37.47	43.42	1	Horizontal	359	2.26	-	37.78	14.92	50.05
AV	18.6326G	32.91	63.54	-30.63	30.18	1	Horizontal	359	2.26	-	37.75	14.95	49.97

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.8742G	59.82	88.20	-28.38	53.44	3	Vertical	66	1.80	-	34.45	7.47	35.54
RMS	5.9062G	47.93	68.20	-20.27	41.35	3	Vertical	66	1.80	-	34.62	7.51	35.55
PK	6.4086G	119.49	Inf	-Inf	112.34	3	Vertical	66	1.80	-	34.87	7.72	35.44
RMS	6.4086G	103.77	Inf	-Inf	96.62	3	Vertical	66	1.80	-	34.87	7.72	35.44
PK	7.1446G	61.85	88.20	-26.35	53.11	3	Vertical	66	1.80	-	36.07	8.20	35.53
RMS	7.199G	50.61	68.20	-17.59	41.56	3	Vertical	66	1.80	-	36.39	8.20	35.54

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8214G	57.11	88.20	-31.09	40.98	3	Vertical	261	1.52	-	39.32	11.46	34.65
RMS	12.872G	42.97	68.20	-25.23	26.63	3	Vertical	261	1.52	-	39.37	11.50	34.53

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8414G	56.87	88.20	-31.33	40.66	3	Horizontal	221	1.09	-	39.34	11.47	34.60
RMS	12.867G	43.04	68.20	-25.16	26.73	3	Horizontal	221	1.09	-	39.37	11.49	34.55

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 10.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2328G	47.03	83.54	-36.51	43.77	1	Vertical	8	1.25	-	37.72	15.19	49.65
AV	19.214G	33.79	63.54	-29.75	30.50	1	Vertical	8	1.25	-	37.74	15.19	49.64

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 10.75
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.239G	47.04	83.54	-36.50	43.78	1	Horizontal	300	1.31	-	37.71	15.20	49.65
AV	19.2356G	33.83	63.54	-29.71	30.57	1	Horizontal	300	1.31	-	37.72	15.19	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.8952G	53.85	54.00	-0.15	3	Horizontal	205	1.80	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 14.25
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.9174G	82.83	88.20	-5.37	74.07	3	Vertical	69	1.50	-	34.97	6.60	32.81
RMS	5.9178G	53.72	68.20	-14.48	44.96	3	Vertical	69	1.50	-	34.97	6.60	32.81
PK	5.949G	122.32	Inf	-Inf	113.44	3	Vertical	69	1.50	-	35.10	6.60	32.82
RMS	5.9474G	108.31	Inf	-Inf	99.44	3	Vertical	69	1.50	-	35.09	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 14.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.8972G	58.51	74.00	-15.49	42.62	3	Vertical	230	1.78	-	38.50	8.97	31.58
AV	11.8952G	46.84	54.00	-7.16	30.95	3	Vertical	230	1.78	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 14.25
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.895G	65.67	74.00	-8.33	49.78	3	Horizontal	205	1.80	-	38.50	8.97	31.58
AV	11.8952G	53.85	54.00	-0.15	37.96	3	Horizontal	205	1.80	-	38.50	8.97	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.6518G	58.88	88.20	-29.32	52.42	3	Vertical	68	1.73	-	34.49	7.40	35.43
RMS	5.9066G	47.76	68.20	-20.44	41.17	3	Vertical	68	1.73	-	34.63	7.51	35.55
PK	6.1894G	117.89	Inf	-Inf	110.56	3	Vertical	68	1.73	-	35.16	7.69	35.52
RMS	6.1866G	106.21	Inf	-Inf	98.90	3	Vertical	68	1.73	-	35.15	7.69	35.53

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3782G	58.50	74.00	-15.50	43.93	3	Vertical	316	2.47	-	38.88	11.10	35.41
AV	12.3756G	44.61	54.00	-9.39	30.04	3	Vertical	316	2.47	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3748G	62.44	74.00	-11.56	47.89	3	Horizontal	205	2.35	-	38.87	11.10	35.42
AV	12.3754G	47.46	54.00	-6.54	32.89	3	Horizontal	205	2.35	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.6156G	46.83	83.54	-36.71	44.11	1	Vertical	68	2.58	-	37.75	14.95	49.98
AV	18.6254G	32.96	63.54	-30.58	30.23	1	Vertical	68	2.58	-	37.75	14.95	49.97

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 13.5
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5912G	46.20	83.54	-37.34	43.51	1	Horizontal	17	1.49	-	37.76	14.94	50.01
AV	18.626G	32.94	63.54	-30.60	30.21	1	Horizontal	17	1.49	-	37.75	14.95	49.97

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.631G	59.07	88.20	-29.13	52.55	3	Vertical	65	1.79	-	34.54	7.40	35.42
RMS	5.9222G	47.96	68.20	-20.24	41.31	3	Vertical	65	1.79	-	34.69	7.52	35.56
PK	6.4086G	119.65	Inf	-Inf	112.50	3	Vertical	65	1.79	-	34.87	7.72	35.44
RMS	6.4086G	106.58	Inf	-Inf	99.43	3	Vertical	65	1.79	-	34.87	7.72	35.44
PK	7.199G	60.76	88.20	-27.44	51.71	3	Vertical	65	1.79	-	36.39	8.20	35.54
RMS	7.199G	50.75	68.20	-17.45	41.70	3	Vertical	65	1.79	-	36.39	8.20	35.54

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8148G	55.97	88.20	-32.23	39.88	3	Vertical	360	1.45	-	39.31	11.45	34.67
RMS	12.8162G	41.96	68.20	-26.24	25.85	3	Vertical	360	1.45	-	39.32	11.45	34.66

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8184G	60.20	88.20	-28.00	44.09	3	Horizontal	204	2.50	-	39.32	11.45	34.66
RMS	12.8162G	46.24	68.20	-21.96	30.13	3	Horizontal	204	2.50	-	39.32	11.45	34.66

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 13.75
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.2468G	47.18	83.54	-36.36	43.93	1	Vertical	329	1.80	-	37.70	15.20	49.65
AV	19.2528G	33.88	63.54	-29.66	30.63	1	Vertical	329	1.80	-	37.70	15.20	49.65

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 13.75
03-D-E-2


Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.257G	47.34	83.54	-36.20	44.08	1	Horizontal	217	1.69	-	37.71	15.20	49.65
AV	19.2282G	33.88	63.54	-29.66	30.61	1	Horizontal	217	1.69	-	37.73	15.19	49.65

Summary

Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Dist (m)	Condition	Azimuth (°)	Height (m)	Comments
5.925-6.425GHz	-	-	-	-	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	AV	11.901G	53.82	54.00	-0.18	3	Horizontal	205	1.80	-

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15.5
01-M-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.917G	79.23	88.20	-8.97	70.47	3	Vertical	89	1.53	-	34.97	6.60	32.81
RMS	5.925G	58.60	68.20	-9.60	49.81	3	Vertical	89	1.53	-	35.00	6.60	32.81
PK	5.9522G	119.94	Inf	-Inf	111.05	3	Vertical	89	1.53	-	35.11	6.60	32.82
RMS	5.9518G	108.83	Inf	-Inf	99.94	3	Vertical	89	1.53	-	35.11	6.60	32.82

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9012G	58.80	74.00	-15.20	42.90	3	Vertical	231	1.80	-	38.50	8.98	31.58
AV	11.9012G	47.09	54.00	-6.91	31.19	3	Vertical	231	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

5955MHz_TnomVnom




EUT Y_2TX
Setting 15.5
01-M-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	11.9014G	66.19	74.00	-7.81	50.29	3	Horizontal	205	1.80	-	38.50	8.98	31.58
AV	11.901G	53.82	54.00	-0.18	37.92	3	Horizontal	205	1.80	-	38.50	8.98	31.58

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.7358G	58.92	88.20	-29.28	52.76	3	Vertical	68	1.79	-	34.23	7.40	35.47
RMS	5.9234G	47.85	68.20	-20.35	41.20	3	Vertical	68	1.79	-	34.69	7.52	35.56
PK	6.1922G	117.28	Inf	-Inf	109.93	3	Vertical	68	1.79	-	35.17	7.70	35.52
RMS	6.1922G	107.96	Inf	-Inf	100.61	3	Vertical	68	1.79	-	35.17	7.70	35.52

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3826G	56.92	74.00	-17.08	42.34	3	Vertical	294	2.47	-	38.88	11.11	35.41
AV	12.3802G	42.30	54.00	-11.70	27.73	3	Vertical	294	2.47	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.3828G	62.41	74.00	-11.59	47.83	3	Horizontal	207	2.46	-	38.88	11.11	35.41
AV	12.3802G	47.31	54.00	-6.69	32.74	3	Horizontal	207	2.46	-	38.88	11.10	35.41

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.635G	46.35	83.54	-37.19	43.62	1	Vertical	267	2.36	-	37.75	14.95	49.97
AV	18.6278G	32.97	63.54	-30.57	30.24	1	Vertical	267	2.36	-	37.75	14.95	49.97

802.11ax HEW20_Nss1,(MCS0)_2TX

6195MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	18.5756G	46.13	83.54	-37.41	43.45	1	Horizontal	77	1.46	-	37.77	14.93	50.02
AV	18.622G	32.98	63.54	-30.56	30.26	1	Horizontal	77	1.46	-	37.75	14.95	49.98

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2-10

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	5.6406G	58.69	88.20	-29.51	52.19	3	Vertical	69	1.74	-	34.52	7.40	35.42
RMS	5.925G	47.80	68.20	-20.40	41.14	3	Vertical	69	1.74	-	34.70	7.52	35.56
PK	6.4118G	117.29	Inf	-Inf	110.16	3	Vertical	69	1.74	-	34.85	7.72	35.44
RMS	6.4118G	107.08	Inf	-Inf	99.95	3	Vertical	69	1.74	-	34.85	7.72	35.44
PK	7.1382G	61.47	88.20	-26.73	52.77	3	Vertical	69	1.74	-	36.03	8.20	35.53
RMS	7.199G	50.57	68.20	-17.63	41.52	3	Vertical	69	1.74	-	36.39	8.20	35.54

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8216G	55.80	88.20	-32.40	39.67	3	Vertical	294	1.79	-	39.32	11.46	34.65
RMS	12.8214G	42.44	68.20	-25.76	26.31	3	Vertical	294	1.79	-	39.32	11.46	34.65

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	12.8214G	60.68	88.20	-27.52	44.55	3	Horizontal	207	2.05	-	39.32	11.46	34.65
RMS	12.8212G	47.50	68.20	-20.70	31.37	3	Horizontal	207	2.05	-	39.32	11.46	34.65

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom




EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.258G	47.77	83.54	-35.77	44.51	1	Vertical	0	2.93	-	37.71	15.20	49.65
AV	19.2162G	33.97	63.54	-29.57	30.68	1	Vertical	0	2.93	-	37.74	15.19	49.64

802.11ax HEW20_Nss1,(MCS0)_2TX

6415MHz_TnomVnom



EUT Y_2TX
Setting 16
03-D-E-2

Type	Freq	Level	Limit	Margin	Raw	Dist	Condition	Azimuth	Height	Comment	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dBuV)	(m)		(°)	(m)		(dB)	(dB)	(dB)
PK	19.258G	47.53	83.54	-36.01	44.27	1	Horizontal	119	2.61	-	37.71	15.20	49.65
AV	19.236G	33.93	63.54	-29.61	30.67	1	Horizontal	119	2.61	-	37.72	15.19	49.65

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9575G	-9.73	5.9933G	-59.84	-49.73	-10.11	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1937G	-9.89	6.2372G	-59.31	-49.89	-9.42	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4178G	-9.74	6.3655G	-59.01	-49.74	-9.27	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


5965MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.961G	-7.76	6.0298G	-57.72	-47.76	-9.96	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


6205MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.21379G	-7.50	6.2678G	-56.93	-47.50	-9.43	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


6405MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.39241G	-7.72	6.3426G	-56.64	-47.72	-8.92	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


5985MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.96022G	-4.93	5.9422G	-33.68	-25.18	-8.50	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


6225MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.19063G	-4.83	6.1822G	-33.25	-25.08	-8.17	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


6385MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.36022G	-4.87	6.3422G	-33.58	-25.13	-8.45	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6025MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.03859G	-1.88	6.1818G	-29.11	-22.27	-6.84	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6185MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.189G	-2.03	6.341G	-29.44	-22.37	-7.07	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6345MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.3402G	-1.79	6.5018G	-28.68	-22.16	-6.52	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9575G	-9.73	5.9933G	-59.84	-49.73	-10.11	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1937G	-9.89	6.2372G	-59.31	-49.89	-9.42	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4178G	-9.74	6.3655G	-59.01	-49.74	-9.27	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


5965MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.961G	-7.76	6.0298G	-57.72	-47.76	-9.96	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


6205MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.21379G	-7.50	6.2678G	-56.93	-47.50	-9.43	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


6405MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.39241G	-7.72	6.3426G	-56.64	-47.72	-8.92	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


5985MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.96022G	-4.93	5.9422G	-33.68	-25.18	-8.50	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


6225MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.19063G	-4.83	6.1822G	-33.25	-25.08	-8.17	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


6385MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.36022G	-4.87	6.3422G	-33.58	-25.13	-8.45	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6025MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.03859G	-1.88	6.1818G	-29.11	-22.27	-6.84	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6185MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.189G	-2.03	6.341G	-29.44	-22.37	-7.07	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6345MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.3402G	-1.79	6.5018G	-28.68	-22.16	-6.52	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9575G	-9.73	5.9933G	-59.84	-49.73	-10.11	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1937G	-9.89	6.2372G	-59.31	-49.89	-9.42	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4178G	-9.74	6.3655G	-59.01	-49.74	-9.27	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


5965MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.961G	-7.76	6.0298G	-57.72	-47.76	-9.96	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


6205MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.21379G	-7.50	6.2678G	-56.93	-47.50	-9.43	1

802.11ax HEW40_Nss1,(MCS0)_1TX MASK


6405MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.39241G	-7.72	6.3426G	-56.64	-47.72	-8.92	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


5985MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.96022G	-4.93	5.9422G	-33.68	-25.18	-8.50	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


6225MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.19063G	-4.83	6.1822G	-33.25	-25.08	-8.17	1

802.11ax HEW80_Nss1,(MCS0)_1TX MASK


6385MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.36022G	-4.87	6.3422G	-33.58	-25.13	-8.45	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6025MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.03859G	-1.88	6.1818G	-29.11	-22.27	-6.84	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6185MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.189G	-2.03	6.341G	-29.44	-22.37	-7.07	1

802.11ax HEW160_Nss1,(MCS0)_1TX MASK


6345MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.3402G	-1.79	6.5018G	-28.68	-22.16	-6.52	1

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.96G	-16.23	5.9913G	-69.58	-56.23	-13.35	1
5.9599G	-16.03	5.9873G	-69.72	-56.03	-13.69	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1938G	-16.36	6.2268G	-69.09	-56.36	-12.73	1
6.1961G	-15.70	6.2262G	-69.09	-55.70	-13.39	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4138G	-16.19	6.3833G	-68.58	-56.19	-12.39	1
6.4162G	-15.60	6.3835G	-68.62	-55.60	-13.02	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


5965MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.97379G	-13.53	6.0304G	-66.48	-53.53	-12.95	1
5.97379G	-14.01	6.0288G	-66.47	-54.01	-12.46	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


6205MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.21359G	-13.88	6.2684G	-66.00	-53.88	-12.12	1
6.2012G	-14.09	6.2688G	-65.80	-54.09	-11.71	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


6405MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4012G	-13.81	6.3412G	-66.69	-53.81	-12.88	1
6.401G	-13.97	6.3418G	-66.67	-53.97	-12.70	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


5985MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.95983G	-10.65	5.9422G	-39.48	-30.90	-8.58	1
5.96022G	-11.10	6.0278G	-39.55	-31.38	-8.17	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


6225MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.19983G	-10.75	6.1822G	-39.39	-31.01	-8.38	1
6.20022G	-10.97	6.1822G	-39.49	-31.25	-8.24	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


6385MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.35103G	-10.56	6.3422G	-39.15	-30.81	-8.34	1
6.36022G	-10.54	6.3422G	-39.54	-30.82	-8.72	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6025MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.0202G	-7.83	6.181G	-42.99	-35.12	-7.87	1
6.0298G	-7.80	6.2226G	-50.42	-40.86	-9.56	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6185MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.17781G	-7.89	6.341G	-43.74	-35.20	-8.54	1
6.1898G	-7.82	6.3434G	-46.03	-35.37	-10.66	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6345MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.3402G	-7.70	6.5018G	-43.40	-35.06	-8.34	1
6.35939G	-8.01	6.4882G	-45.15	-34.05	-11.10	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.96G	-16.23	5.9913G	-69.58	-56.23	-13.35	1
5.9599G	-16.03	5.9873G	-69.72	-56.03	-13.69	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1938G	-16.36	6.2268G	-69.09	-56.36	-12.73	1
6.1961G	-15.70	6.2262G	-69.09	-55.70	-13.39	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4138G	-16.19	6.3833G	-68.58	-56.19	-12.39	1
6.4162G	-15.60	6.3835G	-68.62	-55.60	-13.02	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


5965MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.97379G	-13.53	6.0304G	-66.48	-53.53	-12.95	1
5.97379G	-14.01	6.0288G	-66.47	-54.01	-12.46	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


6205MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.21359G	-13.88	6.2684G	-66.00	-53.88	-12.12	1
6.2012G	-14.09	6.2688G	-65.80	-54.09	-11.71	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


6405MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4012G	-13.81	6.3412G	-66.69	-53.81	-12.88	1
6.401G	-13.97	6.3418G	-66.67	-53.97	-12.70	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


5985MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.95983G	-10.65	5.9422G	-39.48	-30.90	-8.58	1
5.96022G	-11.10	6.0278G	-39.55	-31.38	-8.17	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


6225MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.19983G	-10.75	6.1822G	-39.39	-31.01	-8.38	1
6.20022G	-10.97	6.1822G	-39.49	-31.25	-8.24	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


6385MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.35103G	-10.56	6.3422G	-39.15	-30.81	-8.34	1
6.36022G	-10.54	6.3422G	-39.54	-30.82	-8.72	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6025MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.0202G	-7.83	6.181G	-42.99	-35.12	-7.87	1
6.0298G	-7.80	6.2226G	-50.42	-40.86	-9.56	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6185MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.17781G	-7.89	6.341G	-43.74	-35.20	-8.54	1
6.1898G	-7.82	6.3434G	-46.03	-35.37	-10.66	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6345MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.3402G	-7.70	6.5018G	-43.40	-35.06	-8.34	1
6.35939G	-8.01	6.4882G	-45.15	-34.05	-11.10	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.96G	-16.23	5.9913G	-69.58	-56.23	-13.35	1
5.9599G	-16.03	5.9873G	-69.72	-56.03	-13.69	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1938G	-16.36	6.2268G	-69.09	-56.36	-12.73	1
6.1961G	-15.70	6.2262G	-69.09	-55.70	-13.39	2

802.11ax HEW20-BF_Nss1,(MCS0)_2TX MASK


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4138G	-16.19	6.3833G	-68.58	-56.19	-12.39	1
6.4162G	-15.60	6.3835G	-68.62	-55.60	-13.02	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


5965MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.97379G	-13.53	6.0304G	-66.48	-53.53	-12.95	1
5.97379G	-14.01	6.0288G	-66.47	-54.01	-12.46	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


6205MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.21359G	-13.88	6.2684G	-66.00	-53.88	-12.12	1
6.2012G	-14.09	6.2688G	-65.80	-54.09	-11.71	2

802.11ax HEW40-BF_Nss1,(MCS0)_2TX MASK


6405MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4012G	-13.81	6.3412G	-66.69	-53.81	-12.88	1
6.401G	-13.97	6.3418G	-66.67	-53.97	-12.70	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


5985MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.95983G	-10.65	5.9422G	-39.48	-30.90	-8.58	1
5.96022G	-11.10	6.0278G	-39.55	-31.38	-8.17	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


6225MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.19983G	-10.75	6.1822G	-39.39	-31.01	-8.38	1
6.20022G	-10.97	6.1822G	-39.49	-31.25	-8.24	2

802.11ax HEW80-BF_Nss1,(MCS0)_2TX MASK


6385MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.35103G	-10.56	6.3422G	-39.15	-30.81	-8.34	1
6.36022G	-10.54	6.3422G	-39.54	-30.82	-8.72	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6025MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.0202G	-7.83	6.181G	-42.99	-35.12	-7.87	1
6.0298G	-7.80	6.2226G	-50.42	-40.86	-9.56	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6185MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.17781G	-7.89	6.341G	-43.74	-35.20	-8.54	1
6.1898G	-7.82	6.3434G	-46.03	-35.37	-10.66	2

802.11ax HEW160-BF_Nss1,(MCS0)_2TX MASK


6345MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.3402G	-7.70	6.5018G	-43.40	-35.06	-8.34	1
6.35939G	-8.01	6.4882G	-45.15	-34.05	-11.10	2

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94661G	-9.83	5.9453G	-18.92	-10.33	-8.59	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18701G	-9.81	6.1853G	-18.73	-11.21	-7.52	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40711G	-9.68	6.4054G	-14.59	-10.88	-3.71	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94881G	-9.53	5.9453G	-19.79	-10.33	-9.46	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18871G	-9.74	6.1853G	-19.58	-10.84	-8.74	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40881G	-9.78	6.4053G	-19.38	-10.88	-8.50	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9524G	-9.67	5.9453G	-17.40	-9.87	-7.53	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1925G	-9.64	6.1853G	-17.08	-10.44	-6.64	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4118G	-9.78	6.4052G	-22.08	-11.68	-10.40	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94661G	-9.83	5.9453G	-18.92	-10.33	-8.59	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18701G	-9.81	6.1853G	-18.73	-11.21	-7.52	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40711G	-9.68	6.4054G	-14.59	-10.88	-3.71	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94881G	-9.53	5.9453G	-19.79	-10.33	-9.46	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18871G	-9.74	6.1853G	-19.58	-10.84	-8.74	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40881G	-9.78	6.4053G	-19.38	-10.88	-8.50	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9524G	-9.67	5.9453G	-17.40	-9.87	-7.53	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1925G	-9.64	6.1853G	-17.08	-10.44	-6.64	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4118G	-9.78	6.4052G	-22.08	-11.68	-10.40	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94661G	-9.83	5.9453G	-18.92	-10.33	-8.59	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18701G	-9.81	6.1853G	-18.73	-11.21	-7.52	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40711G	-9.68	6.4054G	-14.59	-10.88	-3.71	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94881G	-9.53	5.9453G	-19.79	-10.33	-9.46	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18871G	-9.74	6.1853G	-19.58	-10.84	-8.74	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40881G	-9.78	6.4053G	-19.38	-10.88	-8.50	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9524G	-9.67	5.9453G	-17.40	-9.87	-7.53	1

802.11ax HEW20_Nss1,(MCS0)_1TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1925G	-9.64	6.1853G	-17.08	-10.44	-6.64	1

802.11ax HEW20_Nss1,(MCS0)_1TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4118G	-9.78	6.4052G	-22.08	-11.68	-10.40	1

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94871G	-15.71	5.9453G	-26.37	-17.11	-9.26	1
5.94871G	-15.51	5.9453G	-26.37	-17.21	-9.16	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18871G	-15.68	6.1853G	-25.73	-17.08	-8.65	1
6.18871G	-15.49	6.1853G	-25.94	-17.19	-8.75	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40871G	-15.94	6.4053G	-25.90	-17.04	-8.86	1
6.40861G	-15.68	6.4053G	-25.51	-17.08	-8.43	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94701G	-15.65	5.9453G	-24.94	-17.05	-7.89	1
5.94701G	-15.89	5.9454G	-20.92	-16.19	-4.73	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18711G	-15.71	6.1854G	-20.62	-16.01	-4.61	1
6.18711G	-15.58	6.1854G	-20.55	-17.38	-3.17	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40701G	-15.90	6.4053G	-24.75	-17.00	-7.75	1
6.40721G	-15.83	6.4054G	-20.67	-17.03	-3.64	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9524G	-15.99	5.9453G	-24.37	-16.49	-7.88	1
5.9524G	-15.78	5.9453G	-23.76	-16.58	-7.18	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1925G	-15.51	6.1853G	-23.72	-15.71	-8.01	1
6.1924G	-15.60	6.1853G	-23.97	-16.10	-7.87	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4124G	-15.84	6.4053G	-24.59	-16.04	-8.55	1
6.4124G	-15.75	6.4053G	-24.18	-16.55	-7.63	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94701G	-15.65	5.9453G	-24.94	-17.05	-7.89	1
5.94701G	-15.89	5.9454G	-20.92	-16.19	-4.73	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18711G	-15.71	6.1854G	-20.62	-16.01	-4.61	1
6.18711G	-15.58	6.1854G	-20.55	-17.38	-3.17	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40701G	-15.90	6.4053G	-24.75	-17.00	-7.75	1
6.40721G	-15.83	6.4054G	-20.67	-17.03	-3.64	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94871G	-15.71	5.9453G	-26.37	-17.11	-9.26	1
5.94871G	-15.51	5.9453G	-26.37	-17.21	-9.16	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18871G	-15.68	6.1853G	-25.73	-17.08	-8.65	1
6.18871G	-15.49	6.1853G	-25.94	-17.19	-8.75	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40871G	-15.94	6.4053G	-25.90	-17.04	-8.86	1
6.40861G	-15.68	6.4053G	-25.51	-17.08	-8.43	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9524G	-15.99	5.9453G	-24.37	-16.49	-7.88	1
5.9524G	-15.78	5.9453G	-23.76	-16.58	-7.18	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1925G	-15.51	6.1853G	-23.72	-15.71	-8.01	1
6.1924G	-15.60	6.1853G	-23.97	-16.10	-7.87	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4124G	-15.84	6.4053G	-24.59	-16.04	-8.55	1
6.4124G	-15.75	6.4053G	-24.18	-16.55	-7.63	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94701G	-15.65	5.9453G	-24.94	-17.05	-7.89	1
5.94701G	-15.89	5.9454G	-20.92	-16.19	-4.73	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18711G	-15.71	6.1854G	-20.62	-16.01	-4.61	1
6.18711G	-15.58	6.1854G	-20.55	-17.38	-3.17	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40701G	-15.90	6.4053G	-24.75	-17.00	-7.75	1
6.40721G	-15.83	6.4054G	-20.67	-17.03	-3.64	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.94871G	-15.71	5.9453G	-26.37	-17.11	-9.26	1
5.94871G	-15.51	5.9453G	-26.37	-17.21	-9.16	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.18871G	-15.68	6.1853G	-25.73	-17.08	-8.65	1
6.18871G	-15.49	6.1853G	-25.94	-17.19	-8.75	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**


6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.40871G	-15.94	6.4053G	-25.90	-17.04	-8.86	1
6.40861G	-15.68	6.4053G	-25.51	-17.08	-8.43	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


5955MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
5.9524G	-15.99	5.9453G	-24.37	-16.49	-7.88	1
5.9524G	-15.78	5.9453G	-23.76	-16.58	-7.18	2

802.11ax HEW20_Nss1,(MCS0)_2TX MASK


6195MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.1925G	-15.51	6.1853G	-23.72	-15.71	-8.01	1
6.1924G	-15.60	6.1853G	-23.97	-16.10	-7.87	2

802.11ax HEW20_Nss1,(MCS0)_2TX **MASK**

6415MHz_TnomVnom



Ref(Hz)	Ref(dBm)	Freq(Hz)	Level(dBm)	Limit(dBm)	Margin(dB)	Port
6.4124G	-15.84	6.4053G	-24.59	-16.04	-8.55	1
6.4124G	-15.75	6.4053G	-24.18	-16.55	-7.63	2

Contention Based protocol 802.11ax HEW20											
UNII Band	**Channel**	**Bandwidth (MHz)**	**Frequency (MHz)**	**Interference frequency (MHz)**		**AWGN Threshold Level (dBm)**	**EUT Status**	**Number of Detected (out of 10 times)**	**Detection Ratio (%)**	**Limit (%)**	**Test Result**
5	53	20	6215	Center	6215	-62	Stop Transmission	9	90	90	PASS
						-63	Stop & with beacon	-			
						-82	Start Transmission	-			


Note:
1. EUT antenna gain = Band 5= 0 dBi considered in the measurement path loss.
2. Measurement use conducted measurement at the antenna connector.

Contention Based protocol 802.11ax HEW160											
UNII Band	**Channel**	**Bandwidth (MHz)**	**Frequency (MHz)**	**Interference frequency (MHz)**		**AWGN Threshold Level (dBm)**	**EUT Status**	**Number of Detected (out of 10 times)**	**Detection Ratio (%)**	**Limit (%)**	**Test Result**
5	47	160	6185	Low edge	6110	-62.00	Stop Transmission	9	90	90	PASS
						-63.00	Stop & with beacon	-			
						-82.00	Start Transmission	-			
				Center	6185	-62.00	Stop Transmission	9	90	90	PASS
						-63.00	Stop & with beacon	-			
						-82.00	Start Transmission	-			
				High edge	6260	-62.00	Stop Transmission	9	90	90	PASS
						-63.00	Stop & with beacon	-			
						-82.00	Start Transmission	-			

Note:
1. EUT antenna gain = Band 5= 0 dBi considered in the measurement path loss.
2. Measurement use conducted measurement at the antenna connector.

Bandwidth: 20MHz

Traffic Loading Plot




Traffic Loading Calculation


R&S | Agilent

VISA session	Threshold (dBm)	Marker 1 (sec)	Space Time of Point	No. of Pulse
GPIB0::20:	-40	0	0.000003	27715
	Mean Level (dBm)	Marker 2 (sec)	Mark 1 Point	Close TX Time(sec)
	-6.63	0.1	1	86.609375m
	RMS Level (dBm)	Total Trace of Points	Mark 2 Point	Duty (%)
	-6.61	32001	32001	86.61


Incumbent signal (AWGN) Plot
Bandwidth: 20MHz
Frequency (MHz): 6215 MHz




Bandwidth: 160MHz
Frequency (MHz): 6110 MHz





Frequency (MHz): 6185 MHz




Frequency (MHz): 6260 MHz




Contention-Based Protocol Plot
Bandwidth: 20MHz
Test CH 53 ; Incumbent signal 6215 MHz

Note : M1 : Inject AWGN signal
Bandwidth: 160MHz
Test CH 47 ; Incumbent signal 6110 MHz

Note : M1 : Inject AWGN signal

Test CH 47 ; Incumbent signal 6185 MHz



Note : M1 : Inject AWGN signal

Test CH 47 ; Incumbent signal 6260 MHz



Note : M1 : Inject AWGN signal

Contention Based protocol 802.11ax HEW20											
UNII Band	**Channel**	**Bandwidth (MHz)**	**Frequency (MHz)**	**Interference frequency (MHz)**		**AWGN Threshold Level (dBm)**	**EUT Status**	**Number of Detected (out of 10 times)**	**Detection Ratio (%)**	**Limit (%)**	**Test Result**
5	53	20	6215	Center	6215	-67	Stop Transmission	9	90	90	PASS
						-66	Stop & with beacon	-			
						-82	Start Transmission	-			


Note:
1. EUT antenna gain = Band 5= -5 dBi considered in the measurement path loss.
2. Measurement use conducted measurement at the antenna connector.

Contention Based protocol 802.11ax HEW160											
UNII Band	**Channel**	**Bandwidth (MHz)**	**Frequency (MHz)**	**Interference frequency (MHz)**		**AWGN Threshold Level (dBm)**	**EUT Status**	**Number of Detected (out of 10 times)**	**Detection Ratio (%)**	**Limit (%)**	**Test Result**
5	47	160	6185	Low edge	6110	-72.00	Stop Transmission	9	90	90	PASS
						-71.00	Stop & with beacon	-			
						-82.00	Start Transmission	-			
				Center	6185	-67.00	Stop Transmission	9	90	90	PASS
						-66.00	Stop & with beacon	-			
						-82.00	Start Transmission	-			
				High edge	6260	-67.00	Stop Transmission	9	90	90	PASS
						-66.00	Stop & with beacon	-			
						-82.00	Start Transmission	-			

Note:
1. EUT antenna gain = Band 5= -5 dBi considered in the measurement path loss.
2. Measurement use conducted measurement at the antenna connector.

Bandwidth: 20MHz

Traffic Loading Plot




Traffic Loading Calculation

R&S | Agilent


VISA session: GPIB0::20:

Threshold (dBm)	Marker 1 (sec)	Space Time of Point	No. of Pulse
-40	0	0.000003	27715
Mean Level (dBm)	**Marker 2 (sec)**	**Mark 1 Point**	**Close TX Time(sec)**
-6.63	0.1	1	86.609375m
RMS Level (dBm)	**Total Trace of Points**	**Mark 2 Point**	**Duty (%)**
-6.61	32001	32001	86.61


Incumbent signal (AWGN) Plot
Bandwidth: 20MHz
Frequency (MHz): 6215 MHz




Bandwidth: 160MHz
Frequency (MHz): 6110 MHz




Frequency (MHz): 6185 MHz




Frequency (MHz): 6260 MHz



Contention-Based Protocol Plot
Bandwidth: 20MHz
Test CH 53 ; Incumbent signal 6215 MHz




Note : M1 : Inject AWGN signal
Bandwidth: 160MHz
Test CH 47 ; Incumbent signal 6110 MHz




Note : M1 : Inject AWGN signal

Test CH 47 ; Incumbent signal 6185 MHz



Note : M1 : Inject AWGN signal

Test CH 47 ; Incumbent signal 6260 MHz



Note : M1 : Inject AWGN signal

Summary

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit	Port	Remark
5.925-6.425GHz	-	-	-	-	-	-	-
802.11ax HEW20_Nss1,(MCS0)_2TX	Pass	6.175G	6.17494G	9.7154	Within Band	1	0 min
802.11ax HEW40_Nss1,(MCS0)_2TX	Pass	6.165G	6.16494G	9.7311	Within Band	1	0 min
802.11ax HEW80_Nss1,(MCS0)_2TX	Pass	6.145G	6.14494G	9.7628	Within Band	1	2 min
802.11ax HEW160_Nss1,(MCS0)_2TX	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min

Result

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
802.11ax HEW20_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
6175MHz_-30°C	Pass	6.175G	6.174955G	7.2865	Within Band	1	0 min
6175MHz_-30°C	Pass	6.175G	6.174951G	7.8937	Within Band	1	2 min
6175MHz_-30°C	Pass	6.175G	6.174948G	8.501	Within Band	1	5 min
6175MHz_-30°C	Pass	6.175G	6.174946G	8.8046	Within Band	1	10 min
6175MHz_-20°C	Pass	6.175G	6.174944G	9.1082	Within Band	1	0 min
6175MHz_-20°C	Pass	6.175G	6.174946G	8.8046	Within Band	1	2 min
6175MHz_-20°C	Pass	6.175G	6.174948G	8.501	Within Band	1	5 min
6175MHz_-20°C	Pass	6.175G	6.174948G	8.501	Within Band	1	10 min
6175MHz_-10°C	Pass	6.175G	6.17494G	9.7154	Within Band	1	0 min
6175MHz_-10°C	Pass	6.175G	6.17494G	9.7154	Within Band	1	2 min
6175MHz_-10°C	Pass	6.175G	6.17494G	9.7154	Within Band	1	5 min
6175MHz_-10°C	Pass	6.175G	6.174946G	8.8046	Within Band	1	10 min
6175MHz_0°C	Pass	6.175G	6.174948G	8.501	Within Band	1	0 min
6175MHz_0°C	Pass	6.175G	6.174946G	8.8046	Within Band	1	2 min
6175MHz_0°C	Pass	6.175G	6.174946G	8.8046	Within Band	1	5 min
6175MHz_0°C	Pass	6.175G	6.174948G	8.501	Within Band	1	10 min
6175MHz_10°C	Pass	6.175G	6.174949G	8.1974	Within Band	1	0 min
6175MHz_10°C	Pass	6.175G	6.174949G	8.1974	Within Band	1	2 min
6175MHz_10°C	Pass	6.175G	6.174951G	7.8937	Within Band	1	5 min
6175MHz_10°C	Pass	6.175G	6.174953G	7.5901	Within Band	1	10 min
6175MHz_20°C	Pass	6.175G	6.174957G	6.9829	Within Band	1	0 min
6175MHz_20°C	Pass	6.175G	6.174955G	7.2865	Within Band	1	2 min
6175MHz_20°C	Pass	6.175G	6.174957G	6.9829	Within Band	1	5 min
6175MHz_20°C	Pass	6.175G	6.174957G	6.9829	Within Band	1	10 min
6175MHz_30°C	Pass	6.175G	6.174957G	6.9829	Within Band	1	0 min
6175MHz_30°C	Pass	6.175G	6.174959G	6.6793	Within Band	1	2 min
6175MHz_30°C	Pass	6.175G	6.174961G	6.3757	Within Band	1	5 min
6175MHz_30°C	Pass	6.175G	6.174961G	6.3757	Within Band	1	10 min
6175MHz_40°C	Pass	6.175G	6.174961G	6.3757	Within Band	1	0 min
6175MHz_40°C	Pass	6.175G	6.174964G	5.7685	Within Band	1	2 min
6175MHz_40°C	Pass	6.175G	6.174964G	5.7685	Within Band	1	5 min
6175MHz_40°C	Pass	6.175G	6.174964G	5.7685	Within Band	1	10 min
6175MHz_50°C	Pass	6.175G	6.174968G	5.1613	Within Band	1	0 min
6175MHz_50°C	Pass	6.175G	6.174968G	5.1613	Within Band	1	2 min
6175MHz_50°C	Pass	6.175G	6.174968G	5.1613	Within Band	1	5 min
6175MHz_50°C	Pass	6.175G	6.17497G	4.8577	Within Band	1	10 min
6175MHz_60°C	Pass	6.175G	6.174961G	6.3757	Within Band	1	0 min
6175MHz_60°C	Pass	6.175G	6.174963G	6.0721	Within Band	1	2 min
6175MHz_60°C	Pass	6.175G	6.174963G	6.0721	Within Band	1	5 min
6175MHz_60°C	Pass	6.175G	6.174963G	6.0721	Within Band	1	10 min
6175MHz_70°C	Pass	6.175G	6.174966G	5.4649	Within Band	1	0 min
6175MHz_70°C	Pass	6.175G	6.174964G	5.7685	Within Band	1	2 min
6175MHz_70°C	Pass	6.175G	6.174968G	5.1613	Within Band	1	5 min
6175MHz_70°C	Pass	6.175G	6.174968G	5.1613	Within Band	1	10 min
6175MHz_138V	Pass	6.175G	6.17497G	4.8577	Within Band	1	0 min
6175MHz_138V	Pass	6.175G	6.174972G	4.5541	Within Band	1	2 min
6175MHz_138V	Pass	6.175G	6.174972G	4.5541	Within Band	1	5 min
6175MHz_138V	Pass	6.175G	6.174972G	4.5541	Within Band	1	10 min
6175MHz_120V	Pass	6.175G	6.174972G	4.5541	Within Band	1	0 min
6175MHz_120V	Pass	6.175G	6.174976G	3.9469	Within Band	1	2 min
6175MHz_120V	Pass	6.175G	6.174976G	3.9469	Within Band	1	5 min
6175MHz_120V	Pass	6.175G	6.174976G	3.9469	Within Band	1	10 min
6175MHz_102V	Pass	6.175G	6.174976G	3.9469	Within Band	1	0 min
6175MHz_102V	Pass	6.175G	6.174979G	3.3397	Within Band	1	2 min

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
6175MHz_102V	Pass	6.175G	6.174979G	3.3397	Within Band	1	5 min
6175MHz_102V	Pass	6.175G	6.174979G	3.3397	Within Band	1	10 min
802.11ax HEW40_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
6165MHz_-30°C	Pass	6.165G	6.165011G	1.8246	Within Band	1	0 min
6165MHz_-30°C	Pass	6.165G	6.165011G	1.8246	Within Band	1	2 min
6165MHz_-30°C	Pass	6.165G	6.165011G	1.8246	Within Band	1	5 min
6165MHz_-30°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	10 min
6165MHz_-20°C	Pass	6.165G	6.165011G	1.8246	Within Band	1	0 min
6165MHz_-20°C	Pass	6.165G	6.165011G	1.8246	Within Band	1	2 min
6165MHz_-20°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	5 min
6165MHz_-20°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	10 min
6165MHz_-10°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	0 min
6165MHz_-10°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	2 min
6165MHz_-10°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	5 min
6165MHz_-10°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	10 min
6165MHz_0°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	0 min
6165MHz_0°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	2 min
6165MHz_0°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	5 min
6165MHz_0°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	10 min
6165MHz_10°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	0 min
6165MHz_10°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	2 min
6165MHz_10°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	5 min
6165MHz_10°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	10 min
6165MHz_20°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	0 min
6165MHz_20°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	2 min
6165MHz_20°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	5 min
6165MHz_20°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	10 min
6165MHz_30°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	0 min
6165MHz_30°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	2 min
6165MHz_30°C	Pass	6.165G	6.165011G	1.8246	Within Band	1	5 min
6165MHz_30°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	10 min
6165MHz_40°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	0 min
6165MHz_40°C	Pass	6.165G	6.165019G	3.041	Within Band	1	2 min
6165MHz_40°C	Pass	6.165G	6.165019G	3.041	Within Band	1	5 min
6165MHz_40°C	Pass	6.165G	6.165019G	3.041	Within Band	1	10 min
6165MHz_50°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	0 min
6165MHz_50°C	Pass	6.165G	6.165015G	2.4328	Within Band	1	2 min
6165MHz_50°C	Pass	6.165G	6.165019G	3.041	Within Band	1	5 min
6165MHz_50°C	Pass	6.165G	6.165019G	3.041	Within Band	1	10 min
6165MHz_60°C	Pass	6.165G	6.16494G	9.7311	Within Band	1	0 min
6165MHz_60°C	Pass	6.165G	6.164944G	9.1229	Within Band	1	2 min
6165MHz_60°C	Pass	6.165G	6.164944G	9.1229	Within Band	1	5 min
6165MHz_60°C	Pass	6.165G	6.16494G	9.7311	Within Band	1	10 min
6165MHz_70°C	Pass	6.165G	6.164948G	8.5148	Within Band	1	0 min
6165MHz_70°C	Pass	6.165G	6.16494G	9.7311	Within Band	1	2 min
6165MHz_70°C	Pass	6.165G	6.16494G	9.7311	Within Band	1	5 min
6165MHz_70°C	Pass	6.165G	6.16494G	9.7311	Within Band	1	10 min
6165MHz_138V	Pass	6.165G	6.165022G	3.6492	Within Band	1	0 min
6165MHz_138V	Pass	6.165G	6.165019G	3.041	Within Band	1	2 min
6165MHz_138V	Pass	6.165G	6.165015G	2.4328	Within Band	1	5 min
6165MHz_138V	Pass	6.165G	6.165022G	3.6492	Within Band	1	10 min
6165MHz_120V	Pass	6.165G	6.165019G	3.041	Within Band	1	0 min
6165MHz_120V	Pass	6.165G	6.165022G	3.6492	Within Band	1	2 min
6165MHz_120V	Pass	6.165G	6.165019G	3.041	Within Band	1	5 min
6165MHz_120V	Pass	6.165G	6.165022G	3.6492	Within Band	1	10 min
6165MHz_102V	Pass	6.165G	6.165022G	3.6492	Within Band	1	0 min

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
6165MHz_102V	Pass	6.165G	6.165019G	3.041	Within Band	1	2 min
6165MHz_102V	Pass	6.165G	6.165022G	3.6492	Within Band	1	5 min
6165MHz_102V	Pass	6.165G	6.165019G	3.041	Within Band	1	10 min
802.11ax HEW80_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
6145MHz_-30°C	Pass	6.145G	6.144978G	3.6611	Within Band	1	0 min
6145MHz_-30°C	Pass	6.145G	6.144978G	3.6611	Within Band	1	2 min
6145MHz_-30°C	Pass	6.145G	6.144978G	3.6611	Within Band	1	5 min
6145MHz_-30°C	Pass	6.145G	6.144985G	2.4407	Within Band	1	10 min
6145MHz_-20°C	Pass	6.145G	6.144985G	2.4407	Within Band	1	0 min
6145MHz_-20°C	Pass	6.145G	6.144985G	2.4407	Within Band	1	2 min
6145MHz_-20°C	Pass	6.145G	6.144985G	2.4407	Within Band	1	5 min
6145MHz_-20°C	Pass	6.145G	6.144985G	2.4407	Within Band	1	10 min
6145MHz_-10°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	0 min
6145MHz_-10°C	Pass	6.145G	6.144985G	2.4407	Within Band	1	2 min
6145MHz_-10°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	5 min
6145MHz_-10°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	10 min
6145MHz_0°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	0 min
6145MHz_0°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	2 min
6145MHz_0°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	5 min
6145MHz_0°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	10 min
6145MHz_10°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	0 min
6145MHz_10°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	2 min
6145MHz_10°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	5 min
6145MHz_10°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	10 min
6145MHz_20°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	0 min
6145MHz_20°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	2 min
6145MHz_20°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	5 min
6145MHz_20°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	10 min
6145MHz_30°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	0 min
6145MHz_30°C	Pass	6.145G	6.145G	0	Within Band	1	2 min
6145MHz_30°C	Pass	6.145G	6.145G	0	Within Band	1	5 min
6145MHz_30°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	10 min
6145MHz_40°C	Pass	6.145G	6.145G	0	Within Band	1	0 min
6145MHz_40°C	Pass	6.145G	6.145G	0	Within Band	1	2 min
6145MHz_40°C	Pass	6.145G	6.145G	0	Within Band	1	5 min
6145MHz_40°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	10 min
6145MHz_50°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	0 min
6145MHz_50°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	2 min
6145MHz_50°C	Pass	6.145G	6.144993G	1.2204	Within Band	1	5 min
6145MHz_50°C	Pass	6.145G	6.145G	0	Within Band	1	10 min
6145MHz_60°C	Pass	6.145G	6.144948G	8.5425	Within Band	1	0 min
6145MHz_60°C	Pass	6.145G	6.14494G	9.7628	Within Band	1	2 min
6145MHz_60°C	Pass	6.145G	6.14494G	9.7628	Within Band	1	5 min
6145MHz_60°C	Pass	6.145G	6.144955G	7.3221	Within Band	1	10 min
6145MHz_70°C	Pass	6.145G	6.144948G	8.5425	Within Band	1	0 min
6145MHz_70°C	Pass	6.145G	6.144948G	8.5425	Within Band	1	2 min
6145MHz_70°C	Pass	6.145G	6.144948G	8.5425	Within Band	1	5 min
6145MHz_70°C	Pass	6.145G	6.144948G	8.5425	Within Band	1	10 min
6145MHz_138V	Pass	6.145G	6.144993G	1.2204	Within Band	1	0 min
6145MHz_138V	Pass	6.145G	6.144993G	1.2204	Within Band	1	2 min
6145MHz_138V	Pass	6.145G	6.145G	0	Within Band	1	5 min
6145MHz_138V	Pass	6.145G	6.145G	0	Within Band	1	10 min
6145MHz_120V	Pass	6.145G	6.145G	0	Within Band	1	0 min
6145MHz_120V	Pass	6.145G	6.145G	0	Within Band	1	2 min
6145MHz_120V	Pass	6.145G	6.145G	0	Within Band	1	5 min
6145MHz_120V	Pass	6.145G	6.145G	0	Within Band	1	10 min


Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
6145MHz_102V	Pass	6.145G	6.145G	0	Within Band	1	0 min
6145MHz_102V	Pass	6.145G	6.145G	0	Within Band	1	2 min
6145MHz_102V	Pass	6.145G	6.144993G	1.2204	Within Band	1	5 min
6145MHz_102V	Pass	6.145G	6.145G	0	Within Band	1	10 min
802.11ax HEW160_Nss1,(MCS0)_2TX	-	-	-	-	-	-	-
6185MHz_-30°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_-30°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_-30°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_-30°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min
6185MHz_-20°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_-20°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_-20°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_-20°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min
6185MHz_-10°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_-10°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_-10°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_-10°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min
6185MHz_0°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_0°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_0°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_0°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min
6185MHz_10°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_10°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_10°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_10°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min
6185MHz_20°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_20°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_20°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_20°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min
6185MHz_30°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_30°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_30°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_30°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min
6185MHz_40°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_40°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_40°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_40°C	Pass	6.185G	6.18491G	14.5495	Within Band	1	10 min
6185MHz_50°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_50°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_50°C	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_50°C	Pass	6.185G	6.184895G	16.9744	Within Band	1	10 min
6185MHz_60°C	Pass	6.185G	6.18494G	9.6997	Within Band	1	0 min
6185MHz_60°C	Pass	6.185G	6.18494G	9.6997	Within Band	1	2 min
6185MHz_60°C	Pass	6.185G	6.18494G	9.6997	Within Band	1	5 min
6185MHz_60°C	Pass	6.185G	6.18494G	9.6997	Within Band	1	10 min
6185MHz_70°C	Pass	6.185G	6.18497G	4.8498	Within Band	1	0 min
6185MHz_70°C	Pass	6.185G	6.18497G	4.8498	Within Band	1	2 min
6185MHz_70°C	Pass	6.185G	6.18497G	4.8498	Within Band	1	5 min
6185MHz_70°C	Pass	6.185G	6.184955G	7.2748	Within Band	1	10 min
6185MHz_138V	Pass	6.185G	6.184895G	16.9744	Within Band	1	0 min
6185MHz_138V	Pass	6.185G	6.184895G	16.9744	Within Band	1	2 min
6185MHz_138V	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_138V	Pass	6.185G	6.184895G	16.9744	Within Band	1	10 min
6185MHz_120V	Pass	6.185G	6.184895G	16.9744	Within Band	1	0 min
6185MHz_120V	Pass	6.185G	6.18488G	19.3994	Within Band	1	2 min
6185MHz_120V	Pass	6.185G	6.184895G	16.9744	Within Band	1	5 min

Mode	Result	Ch (Hz)	Center (Hz)	ppm	Limit (ppm)	Port	Remark
6185MHz_120V	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min
6185MHz_102V	Pass	6.185G	6.18488G	19.3994	Within Band	1	0 min
6185MHz_102V	Pass	6.185G	6.184895G	16.9744	Within Band	1	2 min
6185MHz_102V	Pass	6.185G	6.18488G	19.3994	Within Band	1	5 min
6185MHz_102V	Pass	6.185G	6.18488G	19.3994	Within Band	1	10 min

Summary


Mode	Result	Type	Freq (Hz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Condition
Mode 5	Pass	AV	1.92003G	41.31	54.00	-12.69	Horizontal

Mode 5



Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comment	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB/m)	(m)		(°)	(m)		(dBuV/m)	(dB/m)	(dB)	(dB)
PK	1.91998G	44.51	74.00	-29.49	-4.72	3	Vertical	152	1.83	-	49.23	27.06	3.02	34.80
AV	1.91998G	40.77	54.00	-13.23	-4.72	3	Vertical	152	1.83	"Worst"	45.49	27.06	3.02	34.80

Mode 5



Type	Freq	Level	Limit	Margin	Factor	Dist	Condition	Azimuth	Height	Comment	Raw	AF	CL	PA
	(Hz)	(dBuV/m)	(dBuV/m)	(dB)	(dB/m)	(m)		(°)	(m)		(dBuV/m)	(dB/m)	(dB)	(dB)
PK	1.91996G	45.26	74.00	-28.74	-4.72	3	Horizontal	124	2.26	-	49.98	27.06	3.02	34.80
AV	1.92003G	41.31	54.00	-12.69	-4.72	3	Horizontal	124	2.26	"Worst"	46.03	27.06	3.02	34.80


1. Photographs of Conducted Emissions Test Configuration

Test Mode: Mode 2

FRONT VIEW



REAR VIEW




CLOSE VIEW


NFA652C00_2V0
n650-8v1Ev1Rv1
W: 00e04c0c0363
B: 00e04c6e0363


2. Photographs of Radiated Emissions Test Configuration

Test Configuration: 30MHz~1GHz / Test Mode: Mode 3

FRONT VIEW



REAR VIEW




CLOSE VIEW




Test Configuration: Above 1GHz

Test Mode: Mode 1


FRONT VIEW



REAR VIEW




CLOSE VIEW



Test Mode: Mode 2


FRONT VIEW



REAR VIEW




CLOSE VIEW




Test Mode: Mode 3


FRONT VIEW



REAR VIEW



CLOSE VIEW



———THE END———